

Differential SMA Probe Family

P7313SMA Datasheet



The P7313SMA probe provides a high fidelity, low noise, differential input connection for Tektronix real-time oscilloscopes. This probe also includes features that enable proper termination for high-speed serial buses.

Features & benefits

- >13.0 GHz bandwidth, 16 GHz with DSP filtering
- 50 Ω termination network, differential SMA inputs
- Industry-leading differential return loss and VSWR
- High-bandwidth differential amplifier with excellent CMRR
- Internal termination voltage generator can be controlled by the oscilloscope, by an external source, or automatically by the probe
- Phase-matched SMA cables (38 inch length, <1 ps skew) with cable loss compensation
- Switchable gain for extended dynamic range
- Auxiliary (inverted) output for use with spectrum analyzers, network analyzers, or as a clock recovery trigger source
- TekConnect™ Interface

Applications

- PCI Express
- Serial ATA
- USB
- MIPI M-PHY
- HDMI
- DisplayPort

Tektronix Differential SMA probes

Tektronix differential SMA probes are designed for measuring differential signals in a 50 Ω signaling environment, providing the ability to convert from a differential SMA signal path to a single oscilloscope input channel. Many of today's high-speed serial data standards employ differential signaling on multiple lanes that are challenging to measure simultaneously on a single oscilloscope. The Tektronix Differential P7300 SMA Probes provide the ability to measure a high-speed differential signal on each channel of a multiple-channel oscilloscope. The right oscilloscope can simultaneously acquire up to four high-speed differential signals with the use of four differential SMA probes. As an added benefit, the SMA inputs on the probes connect to high-quality 50 Ω terminations that offer industry-leading return loss, a critical specification that is very important in compliance testing as frequencies increase.

Tektronix Differential P7300 SMA Probes also provide a common mode DC voltage input to the termination network. The termination voltage can be supplied either externally by the user or internally by the oscilloscope. In addition, there is also an automatic mode that senses the common mode voltage of the input signal and automatically sets the termination voltage to match. The P7313SMA has an extended termination voltage range that makes it ideal for testing differential standards with high common mode voltages such as HDMI.

Taken together, the high-speed differential amplifier, superior 50 Ω terminations, low return loss, flexible termination voltage, and quality phase-matched SMA cables create a world-class differential acquisition system when used with Tektronix oscilloscopes.

Specifications

All specifications are guaranteed unless noted otherwise.

Bandwidth, typical >13.0 GHz (16 GHz with DSP filtering)

Rise time

10 to 90% <40 ps

10 to 80%, typical <25 ps

Attenuation 2.5X or 12.5X, user selectable

Differential input range 0.800 V_{p-p} (2.5X)
3.6 V_{p-p} (12.5X)

Common Mode input range +3.6/-2.5 V

Termination voltage range +3.6/-2.5 V

Noise, referred to input <13 nV/√Hz (2.5X)
<40 nV/√Hz (12.5X)

Differential return loss <30 dB to 500 MHz (VSWR<1.065:1)
<20 dB to 6.5 GHz (VSWR<1.22:1)
<15 dB to 10 GHz (VSWR<1.43:1)
<12 dB to 13 GHz (VSWR<1.67:1)

CMRR >50 dB to 1 GHz
>35 dB to 2.5 GHz
>25 dB to 5 GHz
>20 dB to 10 GHz
>15 dB to 13 GHz

Maximum voltage (non destructive) ±5 V (DC + peak AC)

Interface TekConnect®

Ordering information

Models

P7313SMA

>13.0 GHz Differential SMA Probe for TekConnect® Interface

Includes standard accessories listed below, Calibration Data Report (Opt. D1), Certificate of Traceable Calibration, One year warranty

Standard accessories

Description	Reorder part number
Pouch, nylon carrying case with inserts	016-1952-xx
User manual – printed Includes Reply Card and CD	020-2720-xx English 020-2737-xx Simplified Chinese 020-2738-xx Japanese
Phase-matched dual SMA cables (38 in.), 1 pair	174-5771-xx
SMA 50 Ω terminator, 3 each	015-1022-xx
SMA Short	015-1020-xx
SMA female to BNC male adapter	015-0572-xx
Banana plug to 0.080 in. diameter pin jack cable adapter, red (4 ft.)	012-1674-xx
Banana plug to 0.080 in. diameter pin jack cable adapter, black (4 ft.)	012-1675-xx
0.040 in. diameter pin jack to 0.08 in. diameter Pin Plug Adapter, Black, 2 each	012-1676-xx
Antistatic wrist strap	006-3415-xx

Recommended accessories

- Phase Adjuster, 2 required (part number 015-0708-xx)
- DSA8300 Series TekConnect Probe Interface (part number 80A03)
- Real-time Spectrum Analyzer TekConnect Probe Adapter (part number RTPA2A)

Options

Service options

Opt. C3	Calibration Service 3 Years
Opt. C5	Calibration Service 5 Years
Opt. CA1	Single Calibration or Functional Verification
Opt. D3	Calibration Data Report 3 Years (with Opt. C3)
Opt. D5	Calibration Data Report 5 Years (with Opt. C5)
Opt. R5	Repair Service 5 Years (including warranty)

Language options

Opt. L0	English manual
Opt. L5	Japanese manual
Opt. L7	Simplified Chinese manual

Datasheet



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.



Product(s) complies with IEEE Standard 488.1-1987, RS-232-C, and with Tektronix Standard Codes and Formats.

ASEAN / Australasia (65) 6356 3900
Belgium 00800 2255 4835*
Central East Europe and the Baltics +41 52 675 3777
Finland +41 52 675 3777
Hong Kong 400 820 5835
Japan 81 (3) 6714 3010
Middle East, Asia, and North Africa +41 52 675 3777
People's Republic of China 400 820 5835
Republic of Korea +822 6917 5084, 822 6917 5080
Spain 00800 2255 4835*
Taiwan 886 (2) 2656 6688

Austria 00800 2255 4835*
Brazil +55 (11) 3759 7627
Central Europe & Greece +41 52 675 3777
France 00800 2255 4835*
India 000 800 650 1835
Luxembourg +41 52 675 3777
The Netherlands 00800 2255 4835*
Poland +41 52 675 3777
Russia & CIS +7 (495) 6647564
Sweden 00800 2255 4835*
United Kingdom & Ireland 00800 2255 4835*

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
Canada 1 800 833 9200
Denmark +45 80 88 1401
Germany 00800 2255 4835*
Italy 00800 2255 4835*
Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90
Norway 800 16098
Portugal 80 08 12370
South Africa +41 52 675 3777
Switzerland 00800 2255 4835*
USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tek.com.

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.



14 Mar 2016 51W-17350-7

www.tek.com

Tektronix®

