







NLS-HR1070

HANDHELD BARCODE SCANNER

FEATURES

O Ergonomic Lightweight Design

This ergonomic lightweight scanner fits comfortably in any user's hands to reduce the fatigue of long-time operation, ideally suited for scan-intensive applications.

O Cost-effective Solution

HR1070 delivers aggressive scanning capabilities and excellent user experiences at an attractive price.

O Snappy Scanning Performance

HR1070 offers an impressive read rate of up to 300 scans per second, helping boost productivity and profitability.







NLS-HR1070

Performance

Typical Depth of Field*

Image Sensor Linear imager

Illumination Red LED (610nm~640nm)

Symbologies 1D EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code 93, ITF-6, ITF-14,

Interleaved 2 of 5, Industrial 25, Standard 2 of 5, Matrix 2 of 5, GSI Databar, Code 39, Code

11, MSI-Plessey, Plessey.

Resolution* ≥5mil

EAN-13 50mm-480mm (13mil)

Code 39 50mm-180mm (5mil)

Scan Angle** Pitch: ±60°, Roll: 30°, Skew: ±60°

Min Symbol Contrast*

Scan Rate 300 scans per second

Physical

Interface USB

Input Voltage DC5V

Current@5VDC Operating 60mA±10mA Standby 15mA±5mA

Maximum <130mA

Dimensions (L×W×H) 160×95×65mm

Weight 220g (USB cable included)
Notification Beep, LED indicator

Environmental

Operating Temperature -20°C to 60°C (-4°F to 140°F) Storage Temperature -40°C ~+85°C (-40°F to 185°F) Humidity 5%-95% (non-condensing)

Certificates

Certificates & Protection FCC Part15 Class B, CE EMC Class B

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample printed barcodes made by Newland.

**Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp;

1D: EAN-13 (13mil).

Specifications are subject to change without notice.

Version: VI.1

Add: No.1 Rujiang West Rd.,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax: +86-591-83979216
Email: info@nlscan.com
Web: www.newlandaidc.com

North America&Latin America

Add: 46559 Fremont Blvd.,
Fremont, CA 94538, USA
Tel: +1510 490 3888
Fax: +1510 490 3887
Email: info@nlscan.com
Web: www.newlandamerica.com

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tet: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com
Web: www.newland-id.com

Asia Pacific

Taiwan:
Add: 7F-6, No. 268, Liancheng Rd.,
Jhonghe Dist. 235, New Taipei City, Taiwan
Tel: +886 2 7731 5388
Email: info@newland-id.com.tw

