



UT204+ Digital clamp meter

- 1.Industrial electricity
- 2.Residential electricity
- 3.Air conditioning
- 4.Automobile

Specifications	Range	UT204+
AC current (A)	600A	±(2.5%+5)
DC current (A)	600A	±(2.5%+5)
AC voltage (V)	600V	±(0.8%+5)
AC voltage frequency(Hz)	10Hz~60kHz	±(0.5%+2)
DC voltage (A)	600V	±(0.5%+2)
Resistance (Ω)	60MΩ	±(0.8%+2)
Capacitance (F)	60mF	±(4%+5)
Temperature (°C)	-40°C~1000°C	±(1.5%+5)
Frequency (Hz)	10Hz~10MHz	±(0.1%+4)
Features		
Display count		6000
Auto range		√
Jaw opening		28mm
True RMS		√
NCV		√
Live wire test		√
Continuity test		√
Diode		√
MAX/MIN		√
Relative mode		√
Zero mode		√
Data hold		√
Low battery indication		√
Auto power off		√
General Characteristics		
Power	1.5V battery (R03) x 2	

Display	37mm x 25mm
Product color	Red and grey
Product net weight	235g
Product size	215mm x 63mm x 36mm
Standard accessories	Batteries, test leads, Themocouple
Standard individual packing	Gift box, Carring bag, English manual
Standard quantity per carton	40pcs
Standard carton measurement	485mm x 295mm x 385mm
Standard carton gross weight	17.3kg