

4 Wire Earth Resistance Tester



2734 ER

FEATURES

- Microprocessor-controlled with advanced safety features.
- 4-wire testing only.
- Automatic C spike check.
- Auto power-off.
- Auto data hold.
- Large LCD (2000 counts).
- Protective terminal cover.



AL-36

TEL-1505 S

SPECIFICATIONS

Measuring ranges	Earth Resistance	0-20Ω / 0-200Ω / 0-2000Ω
	Earth Voltage	0-200V AC
Accuracy	Earth Resistance	±2%rdg±3dgt
	Earth Voltage	±2%rdg±3dgt
Earth resistance resolution	0-20Ω	: 0.01Ω
	0-200Ω	: 0.1Ω
	0-2000Ω	: 1Ω
Temperature & humidity	Operating:	0°C~40°C ≤80% R.H.
	Storage:	-10°C~50°C ≤80% R.H.
Dimensions		205(L) x 90(W) x 55(D)mm
Weight (battery included)		Approx. 380g
Power source		1.5V (AA) x 6
Safety standards		EN 61010-1 CAT IV 200V
		EN 61326-1 EN 61557-1
		EN 61557-5
Accessories		Instruction manual
		Test leads (red-15m, black-10m, yellow-10m, green-5m)
		Auxiliary earth spikes
		Carry case
		Batteries

Earth Resistance Measurement

