SPECIFICATIONS

Programmable DC Power Supply

MODEL : OPE-805S

ODA TECHNOLOGIES
www.odacore.com

Parameter			Specifications	
Output rating(@0℃ ~ 40℃)			0 to 80V / 0 to 5A	
Output WATT			400W	
Programming Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage		0.3% + 500mV	
	Current		0.2% + 25mA	
Readback Accuracy (@25℃ ±5℃)±(%of output + offset)	Voltage		0.3% + 500mV	
	Current		0.2% + 25mA	
Ripple and Noise(20Hz to 20MHz)	Voltage		≤ 3mVp-p	
	Current		≤ 2mArms	
Load Regulation (@25℃ ±5℃)±(%of output + offset)	Voltage		0.01% + 2mV	
	Current		0.01% + 500㎂	
Line Regulation (@25℃ ±5℃)±(%of output + offset)	Voltage		0.01% + 2mV	
	Current		0.01% + 500㎂	
Resolution	Programming/Readback		≤ 30mV / ≤ 1.5mA	
	Display Meter		100mV / 10mA	
Temperature Coefficient ±(%of output + offset) After a 30-minute warm-up	Voltage		0.02% + 10mV	
	Current		0.02% + 3mA	
Stability ±(%of output + offset) After a 1 hour warm-up	Voltage		0.1% + 5mV	
	Current		0.2% + 5mA	
Transient Response Time			Less than 50㎲ for output to recover to within 50mV following a change in output current from full load to half load or vice versa	
Voltage Programming Speed (10% ~ 90%)	No load	Rising time	≤ 120㎳	
		Falling time	≤3.6s	
	Half load	Rising time	≤ 120㎳	
		Falling time	≤ 15㎳	
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF		No overshoot, undershoot : ≤0V ~ ≥ -0.3V	
	Voltage Output Setting		No overshoot, No undershoot	
Remote Interface			RS232C Standard (RS485 Option)	
Programming Language			SCPI(Standard Commands for Programmable Instruments)	
Command Processing Average Time (@19200bps)	Output Setting		Voltage & Current Setting	10ms
			Voltage & Current Query	12ms
	Measurement		Voltage & Current Query	15ms
	The Other		Setting & Query	32ms
State Storage Memory			Five user-configurable(voltage,current)stored states	
Operation Temperature Range			0℃ ~ 40℃ for full rated output. At higher temperatures the output current is derated linearly to 50% at 55℃ maximum temperature	
Cooling			Isolation DC FAN	
Output Terminal Isolated (maximum, from chassis ground)			±30V output is ±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals	
AC Input Ratings	Standard		220V ± 10% 50~60Hz	
	Option		100V ± 10% 50~60Hz	
			230V ± 10% 50~60Hz	
Calibration Interval	Recommended		1 year	
Dimensions	Standard		426mm(W) * 177mm(H) * 505mm(D) 19-inch 4U Standard Size	
	Option		300mm(W) * 150mm(H) * 465mm(D) Non Standard Small Size	
Maximum Input Power(full load)			1066.6W	
Weight	Net weight		13㎏	
	Gross weight		14.5㎏	