

Pistol Pulse Tools

Auto Shut-Off & Non Shut-Off

flexPower
by mountz



KEY FEATURES

- Various models that range from 4.4 - 154.9 lbf.ft
- Designed to enhance cycle time with high-speed rundown.
- Excellent power-to-weight ratio.
- Safe ergonomic selection - low noise decibels, minimal vibration & reaction free operation.
- Comfortable rubberized non-slip grips for easy handling and excellent thermal ergonomics.
- Specially designed pulse fluid extends life between oil changes - provides better stability. Double sealing increases performance - reduces maintenance.
- Shut-off and non shut-off models.
- Ergonomically safer than harmful hammering and vibration of impact wrenches.
- Pin Dentent included with square drive models.

| AUTO SHUT-OFF | | NON SHUT-OFF | | Drive Type | Torque Ranges | | Free Speed (RPM) | Weight | | P/W Ratio Nm/ Kgs. | Length in. | Noise Level dBA | Average Air Consumption | | Hose Size mm |
|---------------|--------|--------------|--------|------------|---------------|-----------|------------------|--------|------|--------------------|------------|-----------------|--------------------------|---------------------------|--------------|
| Model | Item # | Model | Item # | | lbf.ft | N.m | | lbs. | Kgs. | | | | m ³ /min. CMM | ft ³ /min. CFM | |
| FLEXS-30P | 360168 | FLEX-30P | 360169 | 3/8" Sq Dr | 4.4 - 9.2 | 6 - 12.5 | 4400 | 2.0 | 0.88 | 14.2 | 6.7 | 78.0 | 0.25 | 8.80 | 6.5 |
| FLEXS-30PX | 360100 | FLEX-30PX | 360111 | 1/4" F/Hex | 4.4 - 9.2 | 6 - 12.5 | 4400 | 2.0 | 0.88 | 14.2 | 6.7 | 78.0 | 0.25 | 8.80 | 6.5 |
| FLEXS-40PX | 360101 | FLEX-40PX | 360112 | 1/4" F/Hex | 7.4 - 13.2 | 10 - 18 | 4400 | 2.0 | 0.91 | 19.8 | 6.7 | 78.0 | 0.25 | 8.80 | 6.5 |
| FLEXS-40P | 360102 | FLEX-40P | 360113 | 3/8" Sq Dr | 8.1 - 14 | 11 - 19 | 4400 | 2.0 | 0.91 | 20.9 | 6.6 | 78.0 | 0.25 | 8.80 | 6.5 |
| FLEXS-50PX | 360103 | FLEX-50PX | 360114 | 1/4" F/Hex | 10.3 - 19.1 | 14 - 26 | 7200 | 2.0 | 0.91 | 28.6 | 6.7 | 80.0 | 0.35 | 12.30 | 6.5 |
| FLEXS-50P | 360104 | FLEX-50P | 360115 | 3/8" Sq Dr | 11.1 - 19.9 | 15 - 27 | 7200 | 2.0 | 0.91 | 29.7 | 6.6 | 80.0 | 0.35 | 12.30 | 6.5 |
| FLEXS-60PX | 360105 | FLEX-60PX | 360116 | 1/4" F/Hex | 14.8 - 22.1 | 20 - 30 | 6200 | 2.2 | 1.00 | 30.0 | 7.1 | 82.0 | 0.40 | 14.10 | 8 |
| FLEXS-60P | 360106 | FLEX-60P | 360117 | 3/8" Sq Dr | 16.2 - 25.8 | 22 - 35 | 6200 | 2.2 | 0.91 | 38.5 | 7.0 | 82.0 | 0.40 | 14.10 | 8 |
| FLEXS-65P | 360154 | FLEX-65P | 360158 | 3/8" Sq Dr | 21.4 - 32.2 | 29 - 45 | 4800 | 2.4 | 1.1 | 41.7 | 7.4 | 82.0 | 0.43 | 15.20 | 8 |
| FLEXS-70PX | 360166 | FLEX-70PX | 360167 | 1/4" F/Hex | 22.8 - 34.6 | 31 - 47 | 7200 | 3 | 1.4 | 34.8 | 7.8 | 82.0 | 0.45 | 15.90 | 8 |
| FLEXS-70P | 360155 | FLEX-70P | 360159 | 3/8" Sq Dr | 25.8 - 39.8 | 35 - 54 | 5400 | 2.4 | 1.1 | 50.0 | 7.4 | 82.0 | 0.45 | 15.90 | 8 |
| FLEXS-80P | 360156 | FLEX-80P | 360160 | 3/8" Sq Dr | 35.4 - 50.1 | 48 - 68 | 5400 | 2.7 | 1.2 | 56.2 | 7.6 | 82.0 | 0.50 | 17.60 | 8 |
| FLEXS-90P | 360108 | FLEX-90P | 360119 | 1/2" Sq Dr | 47.2 - 66.4 | 64 - 90 | 5400 | 3.4 | 1.55 | 58.1 | 7.9 | 83.0 | 0.53 | 18.70 | 8 |
| FLEXS-100P | 360109 | FLEX-100P | 360120 | 1/2" Sq Dr | 62.7 - 88.5 | 85 - 120 | 5300 | 4.1 | 1.86 | 64.6 | 8.2 | 84.0 | 0.55 | 19.40 | 8 |
| FLEXS-130P | 360110 | FLEX-130P | 360121 | 1/2" Sq Dr | 90.7 - 109.2 | 123 - 148 | 3600 | 5.0 | 2.25 | 65.8 | 8.5 | 86.0 | 0.73 | 25.60 | 11 |
| FLEXS-150P | 360152 | FLEX-150P | 360153 | 3/4" Sq Dr | 121.7 - 154.9 | 165 - 210 | 3600 | 6.83 | 3.1 | 67.7 | 9.3 | 86.0 | 0.73 | 25.60 | 11 |

NOTE!

Recommended air pressure is 85 PSI. Use a high quality air filter regulator and lubricator to ensure stable air pressure for optimal performance and for removal of moisture and other potential debris that can reduce the longevity and performance of pneumatic tools.

All specified torque ranges were established statically on a Mountz (TorqueLab LTT Series) torque meter at a dynamic air pressure of 85 PSI (Pounds per Square Inch). The specified results should be used as guidance only in tool selection. In general, the torque range will be lower based on type of joint, air pressure, extension bars and/or extended sockets. A pulse tool is a discontinuous tool and added adapters or extensions create a dampening effect, thus lowering torque values. Tool selection as well as set up is recommended to be validated on the actual joint by use of a suitable calibrated torque wrench. We recommend a quality Mountz Digital torque wrench.



mountz
the torque tool specialists®

PISTOL PULSE
01.33

800.456.1828