



## KV4-Series

### Vapor Degreaser with Ultrasonic & Recovery System

#### Features

- Original BLT type transducer
- SUS 304 stainless steel tank
- Adaptable for continuous operation
- Adjustable LED thermocontroller
- Build-in independent recovery system
- Build-in water separator
- User friendly operation
- Custom made is available
- etc

\*\* Remark : This series MUST using together with industrial water chiller , pls. refer our KC Series / CoolFast Line



#### View Detail

Model:		KV-4012W	KV-4018W	KV-4024W	KV-4030W	KV-4036W
U/S TANK1 WORKING DIMENSION (mm)	L1	220	250	280	380	430
	W1	250	280	330	330	330
	H1	250	250	330	380	380
U/S TANK2 WORKING DIMENSION (mm)	L2	220	250	280	380	430
	W2	250	280	330	330	330
	H2	275	275	355	405	405
VAPOR TANK'S WORKING DIMENSION (mm)	L3	220	250	280	380	430
	W3	250	280	330	330	330
	H3	310	310	390	430	430

RECOVERY TANK'S WORKING DIMENSION (mm)	L4	220	250	280	380	430
	W4	250	280	330	330	330
	H4	250	250	330	380	380
OVERALL DIMENSION (mm)	L5	1716	1836	1956	2356	2556
	W5	608	658	728	728	728
	H5	1120	1120	1200	1250	1250
TANK'S TOTAL CAPACITY		59L	76L	130L	201L	228L
TANK'S MATERIAL	SUS 304					
HOUSING'S MATERIAL	SUS 304					
ULTRASONIC FREQUENCY*	28kHz / 40kHz					
TOTAL ULTRASONIC TRANSDUCER NO.		12	18	24	30	36
ULTRASONIC OUTPUT POWER (MAX.)		600W	900W	1200W	1500W	1800W
HEATER POWER ( PER U/S TANK 1&2 )		@1.5kW		@3kW		@4.5kW
HEATER POWER ( VAPOR TANK )		1.5kW		3kW		4.5kW
HEATER POWER ( RECOVERY TANK )		3.0kW	4.5kW	4.5kW	6.0kW	
POWER REQUIREMENT		AC 380V, $\Phi$ 3, 15AMP		AC 380V, $\Phi$ 3 + N, 30AMP		
ACCESSORY ( NOT INCLUDING )	CoolFasta 500R / 500W INDUSTRIAL WATER CHILLER					

Note: Special requirements (Size,Material,Frequency) can be made according to client's requirement, and OEM is welcome if the quantity is large.