

1000A Precision Current Shunt



Input terminals can be placed in the rear panel (option)



Lab Current Standard
1uA-1000A Current Range

AC & DC Current Shunt
AC & DC Current Meter

Features

- 0.01% High Accuracy
- 5 1/2 Digit AC & DC Current Meter
- Built-in Over Current Protection
- Less than 10ppm/°C (Range 1000A : less than 50ppm/°C)
- High Stability & Reliability
- **Input terminals can be placed in the rear panel (option)**
- Optional Interface : GPIB 、 RS232 、 USB 、 LAN.

Descriptions

- Model 1000A has five precision selectable Ultra stable Current Shunts which ranges from 0.0001 to 1Ω. The Shunt T/C is less than 10ppm, and the internal current meter will measure from 1μA to 1000Amps.
- The five shunts selector and internal 5 1/2 Digit AC & DC Current Meter displays the respective shunt current. Connect an external DVM into output (with 5 1/2 digit higher) will increase both resolution and current reading accuracy.

Applications

- AC & DC Current Meter
- AC & DC Current Sensor
- AC & DC Power Supply
- AC & DC Electronic Load
- AC & DC Power Meter

Specifications

Range	Shunt Value	DC Accuracy	* AC Accuracy		Max input DC/AC rms	Output Voltage
		± (% of reading)				
1000 A	0.0001 Ω	0.02% of Reading + 0.01% of Range	50~200Hz	0.1% (Reading+Range)	1000 A	1000A / 0.1V
			201~300Hz	0.2% (Reading+Range)		
			301~400Hz	0.4% (Reading+Range)		
200 A	0.001 Ω	0.02 %	0.10 %		250 A	200A / 0.2V
20 A	0.01 Ω	0.01 %	0.10 %		30 A	20A / 0.2V
2 A	0.1 Ω	0.01 %	0.10 %		4 A	2A / 0.2V
0.2 A	1 Ω	0.01 %	0.10 %		0.4 A	0.2A / 0.2V

All Shunt types are 4 terminal networks with calibration adjustments for each network.

5 1/2 Digit Ampere Meter

Range	Resolution	DC	* AC	
		Accuracy ± % of (reading + Range)		
1000 A	0.01 A~1000.00 A	0.02+0.01	50~200 Hz	0.5+0.1
			201~300 Hz	0.5+0.2
			301~400 Hz	0.5+0.4
200 A	0.001 A~199.999A / 200.00A~250.00A	0.02+0.005	0.5+0.05	
20 A	0.0001 A~19.9999A / 20.000A~30.000A	0.01+0.005	0.5+0.05	
2 A	0.01mA~1999.99mA / 2000.0mA~4000.0mA	0.01+0.005	0.5+0.05	
0.2 A	0.001mA~199.999mA / 200.00mA~400.00mA	0.01+0.005	0.5+0.05	

Temperature Range : 0 to 40°C : All specification apply for 23°C±2°C.

Temperature coefficient :

Range 0.2A 、 2A Less than 0.001% per °C (20 °C - 40 °C)

Range 20A Less than 0.002% per°C (20 °C - 40 °C)

Range 200A Less than 0.003% per°C (20 °C - 40 °C)

Range 1000A Less than 0.005% per °C (20 °C - 40 °C)

* AC Input : Range 0.2A 、 2A 、 20A 、 200A ≥ 5% of Range
Range 1000A ≥ 10% of Range

AC Power : 115/230 Vac ±10%, 50/60Hz switchable

Cooling : Force Fan Cooled

Weight : 13.5kg

Dimension : 440(W) x 88.9(H) x 410(D)mm

Order Information

▶ **1000A** Precision Current Shunt

▶ **1000A-R** Precision Current Shunt (Rear Input)

Optional interface : ① GPIB Card ② RS232 Card ③ USB Card ④ LAN Card