



Specification

Model	SH-CH-149G
Air Circulation	Forced
Temp Range	Ambient +5°C to 70°C (Ambient + 9°F to 158°F)
Temp Control	Microprocess Digital P I D Membrane touch controller
Time Range	00.00 to 99HR 59MIN (MIN SEC) Selectable Digital Counter Timer
Temp Accuracy & Stability	±0.1°C
Temp Uniformity	±0.5°C
Capacity	150 L
Dimension Internal (WxDxH)	555x450x600(mm) 21.85x17.72x23.62(inch)
Dimension External (WxDxH)	700x630x937(mm) 27.56x24.80x37.00(inch)
Net Weight	60 Kg
Material Internal	Stainless Steel
Material External	Steel Plate with Powder Heating Coated
Shelves	Movable epoxy coated wire shelves 2 Supplied (17 Maximum)
Electrical Requirements 120V ,50/60Hz, 1Φ	6.7 A
Heater	800 W
Electrical Requirements 230V ,50/60Hz, 1Φ	3.5 A

Feature

- Automatic reset function incoming power cut
- Buzzer on when set time arrived
- Door open alarm
- Electric leakage breaker
- Over temp controller

Option

- Programmable Controller
- Digital Recorder
- 2CH Hybrid Recorder
- RS-485 interface
- RS-232C interface