



## Specification

Model	SH-CH-500R
Air Circulation	Forced
Dimension Internal (WxDxH)	500×500×500(mm)×4Chambers 19.69×19.69×19.69(inch)×4Chambers
Dimension External (WxDxH)	1545×860×1775(mm) 60.82×33.85×69.88(inch)
Capacity	125Lx4Chambers, Total 500 L
Temp Uniformity	±0.5°C
Temp Accuracy	±0.1°C
Temp Range	-10°C to 60°C 14°F to 140°F
Temp Control	Microprocess P I D Digital Controller
Time Range	00.00 to 99HR 59 MIN (MIN SEC) Selectable Digital Counter Timer
Heater	4 KW
Refrigerator Compressor	1/4HP x 4 EA
Electrical Requirements 230V ,50/60Hz, 1Φ	22 A
Material Internal	Stainless Steel
Material External	Steel Plate with Power Heating Coated
Weight	260 Kg
Shelves	Movable epoxy coated wire shelves 2 Supplied / Chamber, total 8EA (15EA / Chamber, total 60EA, Maximum)

## Feature

- Automatic reset function incoming power cut
- Buzzer on When Set Time Arrived
- Electric leakage breaker
- Over temp controller
- Refrigerator over load protection

## Option

- Programmable Controller
- Digital Recorder
- 2CH Hybrid Recorder
- RS-485 interface
- RS-232C interface