



## Specification

Model	SH-CH-54G
Air Circulation	Forced
Temp Range	Ambient +5°C to 70°C (Ambient + 9°F to 158°F)
Temp Control	Microprocess Digital P I D Membrane touch controller
Time Range	00.00 to 99HR 59MIN (MIN SEC) Selectable Digital Counter Timer
Temp Accuracy & Stability	±0.1°C
Temp Uniformity	±0.5°C
Capacity	54 L
Dimension Internal (WxDxH)	380×340×420(mm) 14.96x13.39x16.54(inch)
Dimension External (WxDxH)	525x520x757(mm) 20.67x20.47x29.80(inch)
Net Weight	40 Kg
Material Internal	Stainless Steel
Material External	Steel Plate with Powder Heating Coated
Shelves	Movable epoxy coated wire shelves 2 Supplied (12 Maximum)
Electrical Requirements 120V ,50/60Hz, 1Φ	3.3 A
Heater	400 W
Electrical Requirements 230V ,50/60Hz, 1Φ	1.7 A

## Feature

- Automatic reset function incoming power cut
- Buzzer on when set time arrived
- Door open alarm
- Electric leakage breaker
- Over temp controller

## Option

- Programmable Controller
- Digital Recorder
- 2CH Hybrid Recorder
- RS-485 interface
- RS-232C interface