Specification

Model	SH-CH-800U2
Dimension Internal (WxDxH)	1000×800×1000(mm) 39.37x31.50x39.37(inch)
Dimension External (WxDxH)	1520x1325x2100(mm) 59.84x52.16x82.67(inch)
Capacity	800 L
Heater Capacity	8 KW
Temp Uniformity	±0.5℃
Temp Range	-50°C ~ 120°C(-58°F~248°F)
Cool Down Time	23°C ~ -40°C (73.4°F~-40°F) About 40min
Heating up Time	-40°C ~ 100°C (-40°F~212°F) About 40min
Temp Controller	Microprocess Prgrammable Controller Touch Screen Type
Material Internal	Stainless Steel
Material External	Steel Plate with Powder Heating Coated
Electrical Requirements 230V ,50/60Hz, 1Φ	33 A
Shelves	Movable stainless wire shelves 2 Supplied (31 Maximum)
Temp Accuracy & Stability	±0.1℃
Electrical Requirements 230V,50/60Hz, 3Φ	19.1 A
Weight	520 Kg

Feature

-Automatic reset function incoming power cut
-Over temp protection
-Electric leakage breaker
-Door open lamp display
-Fan motor over load protection
-Refrigerator over load protection

Option

-Digital recorder
-2CH Hybrid recorder
-Max temperature 150°C