



Specification

Model	SH-IDO-2250FH
Air Circulation	Forced
Temp Range	Ambient +10°C to 300°C (Ambient +18°F to 572°F)
Time Range	00.00 to 99HR 59MIN (MIN SEC) Selectable Digital Counter Timer
Temp & Time controller	Microprocess P I D Membrane Touch Digital controller
Heater Capacity	23 KW
Dimension Internal (WxDxH)	1600x930x1500(mm) 62.99x36.61x59.06(inch)
Dimension External (WxDxH)	2300x1145x2090(mm) 90.55x45.07x82.28(inch)
New Weight	644 Kg
Capacity	2232 L
Material Internal	Stainless Steel
Material External	Steel Plate With Powder Heating Coated
Shelves	6 Supplied (2EAx3, 96 Maximum)
Electrical Requirements 230V ,50/60Hz, 3Φ	60.5 A
Electrical Requirements 380V ,50/60Hz, 3Φ	35 A

Feature

- Automatic reset function incoming power cut
- Buzzer on when set time arrived
- Fan Motor overload protection
- Electric leakage breaker
- Over temp controller
- ※We accept custom-made order.

Option

- Programmable controller
- Digital recorder
- 2CH Hybrid recorder
- Moving Cart & Room cart
(Accessory will be movable stainless steel plate wide 3EA than 3ea x 2)
- RS-485 interface
- RS-232C interface