

Range XFP :	XFP020	XFP050	XFP120	XFP240	XFP320	XFP512
						

Performances :

Temperature range :	Température ambiante + 20 °C à 200 °C					
Standard maximum temperature :	200°C					
Temporal stability :	± °C	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2

Chamber dimensions :

Chamber volume :	dm ³	20	51	110	220	316	512
Width :	mm	250	320	470	470	650	800
Depth :	mm	320	500	500	1000	750	800
Height :	mm	250	320	470	470	650	800

External dimensions:

External volume :	m ³	0.21	0.35	0.66	1.14	1.34	1.73
Width :	mm	510	580	800	812	992	1130
Depth :	mm	585	765	820	1375	1095	1150
Height :	mm	715	785	1000	1018	1230	1330

Shelves :

Included / Maximum :		1 / 4	1 / 5	1 / 8	1 / 8	1 / 11	1 / 15
Dimensions W x D :	mm	224 x 280	294 x 460	444 x 460	444 x 960	624 x 710	772 x 760
Max Weight shelf/total :	kg	30 / 60	30 / 60	30 / 90	30 / 90	30 / 120	30 / 200

Autres informations :

Number of doors :		1	1	1	1	1	1
Door window W x H (option) :	mm				450x450		
Weight :	kg	60	85	175	170	320	370

Electrical data :

Heating power 200° :	Watts	800	1200	2400	3250	6000	9000
Power supply :	Volts	230V ~1P 50Hz 16A	230V ~1P 50Hz 16A	230V ~1P 50Hz 16A	230V ~1P 50Hz 20A	400V ~3P + N 50Hz 16A	400V ~3P + N 50Hz 20A

We reserve the right to make any technical modification without prior notice.