



FORCE 145 PLASTIC CARRY CASE



Overview

FORCE 145 PLASTIC CARRY CASE

cod. 815856

MMA inverter, electrode welding machine in direct current (DC).

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc.

Features:

- Compact and light
 - High welding current stability in spite of mains voltage fluctuations
 - Arc force, hot start and anti-stick devices
 - Thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections
- Complete with MMA welding accessories and plastic carry case.



1 PH 230V



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 815856	MAX ABSORBED CURRENT	27 A	D. USABLE ELECTRODES IN DC	1,6 - 3,2 mm
SINGLE PHASE MAINS VOLTAGE	230 V	MAX ABSORBED POWER	3,5 kW	PROTECTION DEGREE	IP21
MAINS FREQUENCY	50 / 60 Hz	MOTORGENERATOR MINIMUM POWER	5 kW	DIMENSIONS	38 x 42 x 17 cm
CURRENT RANGE	10 - 130 A	MAINS FUSE	16 A	WEIGHT	5,2 kg
%USE (20°C USE)	60% @ 125A %	EFFICIENCY	82 V	EAN CODE	800489778954 5
MAX CURRENT DC (EN 60974-1)	125 @ 7% A	POWER FACTOR (cosphi)	0,6	PIECES/PALLET	36 pz/pallet
MAX NO LOAD VOLTAGE	72 V				



FORCE 145 PLASTIC CARRY CASE

Included Accessories

CABLE 16 MMQ 1,8 M - PLUG ATLAS 25 - 124508

PLASTIC CARRY CASE - 322800



TOLEDO 250 WORK CLAMP 250A - 712030



SLAG REMOVER - 712139



DALLAS 300 ELECTRODE HOLDER 300A - 712260