TECNICA 188 MPGE



Overview

TECNICA 188 MPGE
cod. 816212
Inverter MMA electrode and TIG welding machine in direct current (DC) with scratch striking.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc.
Recommended for motorgenerators, this model grants high performance despite power supply instability, thanks to the MPGE multiprotections: control device of the wave form, filter against input peaks, stabilization ofoscillations.
Features:
- compact and light;
- high welding current stability in spite of mains voltage fluctuations;
- arc force, hot start and anti-stick devices;
- thermostatic, overvoltage, undervoltage, overcurrent protections.

Complete with MMA welding accessories and plastic carry case.

1 PH 230V

CE MARKING

EAC CERTIFICATION

Technical data

CODE 816212	DC CURRENT 95 A	MOTORGENERATOR MINIMUM POWER 6 kW
SINGLE PHASE MAINS VOLTAGE 230 V	MAX NO LOAD VOLTAGE 75 V	MAINS FUSE 16 A
MAINS FREQUENCY 50 / 60 Hz	MAX ABSORBED CURRENT 28 A	EFFICIENCY 86 V
CURRENT RANGE 10 - 150 A	ABSORBED CURRENT AT 60% - MAX 17 A	POWER FACTOR (cosphi) 0,7
%USE (20°C USE) 88% @ 150A %	MAX ABSORBED POWER 4,2 kW	D. USABLE ELECTRODES IN DC 1,6 - 4 mm
MAX CURRENT DC (EN 60974-1) 140 @ 25 % A	ABSORBED POWER AT 60% 2,6 kW	PROTECTION DEGREE IP23

TECNICA 188 MPGE

Included Accessories

CABLE TW05V-A 1X025 1.80M PLUG ATLAS - 124589

PLASTIC CARRY CASE - 322800



TOLEDO 250 WORK CLAMP 250A - 712030



DALLAS 300 ELECTRODE HOLDER 300A - 712260