



EURARC 422



Overview

EURARC 422

cod. 817017

MMA stick electrode welding machine in alternating current (AC).

Stepless regulation of welding current.

With thermostatic protection.

The model has double secondary voltage for use also with basic and rutile electrodes.



1 PH 230V



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 817017	AC CURRENT	170 A	PROTECTION DEGREE	IP22
SINGLE PHASE MAINS VOLTAGE	230 V	MAX NO LOAD VOLTAGE	52 - 73 V	DIMENSIONS	83 x 45,5 x 58 cm
DOUBLE PHASE MAINS VOLTAGE	400 V	MAX ABSORBED POWER	13 kW	WEIGHT	61 kg
MAINS FREQUENCY	50 / 60 Hz	ABSORBED POWER AT 60%	4,5 kW	EAN CODE	800489784789 4
CURRENT RANGE	70 - 350 A	POWER FACTOR (cosphi)	0,4	PIECES/PALLET	6 pz/pallet
MAX CURRENT (EN 60974-1)	215 @ 35% A	D. USABLE ELECTRODES IN AC	2 - 6 mm	PIECES/PALLET - B	3 pz/pallet-B
MAX CURRENT (EN 60974-1)	320 @ 15 % A				