



## TELMIG 281/2



### Overview

#### TELMIG 281/2

cod. 820099

MIG-MAG welding machine. Designed for continuous and spot welding with electronic regulation of spotwelding time. Flexibility of use with a wide range of materials such as steel, stainless steel, high strength steels and aluminium. With optional kit this model allows also sheet tempering. Complete with MIG-MAG welding accessories.



1 PH 230V



CE MARKING



EAC CERTIFICATION



COIL 15 kg

### Technical data

|                                |                                          |                         |                                          |                       |                                         |
|--------------------------------|------------------------------------------|-------------------------|------------------------------------------|-----------------------|-----------------------------------------|
| <b>CODE</b>                    | CODE 820099                              | <b>V<sub>0</sub> DC</b> | MAX NO LOAD VOLTAGE 34 V                 | <b>SS</b>             | INOX WELDING WIRE DIAMETER 0,8 - 1 mm   |
| <b>V<sub>1PH</sub></b>         | SINGLE PHASE MAINS VOLTAGE 230 V         | <b>P<sub>MAX</sub></b>  | MAX ABSORBED POWER 9,5 kW                | <b>AL</b>             | ALUMINIUM WELDING WIRE DIAM. 0,8 - 1 mm |
| <b>F</b>                       | MAINS FREQUENCY 50 / 60 Hz               | <b>P<sub>60%</sub></b>  | ABSORBED POWER AT 60% 5 kW               | <b>IP</b>             | PROTECTION DEGREE IP22                  |
| <b>A<sub>MIN</sub> MAX DC</b>  | CURRENT RANGE 40 - 270 A                 | <b>φ</b>                | POWER FACTOR (cosphi) 0,9                | <b>W<sup>H</sup>L</b> | DIMENSIONS 80 x 45 x 65,5 cm            |
| <b>A<sub>MAX</sub> 40°C DC</b> | MAX CURRENT DC (EN 60974-1) 235 @ 20 % A | <b>☼</b>                | ADJUSTMENT POSITIONS 8                   | <b>kg</b>             | WEIGHT 55 kg                            |
| <b>A<sub>60%</sub> 40°C DC</b> | DC CURRENT 150 A                         | <b>ST</b>               | STEEL WELDING WIRE DIAMETER 0,6 - 1,2 mm | <b>BAR CODE</b>       | EAN CODE 800489760679 8                 |

### Included Accessories

CABLE 25 MMQ 2 M - 123466



TOLEDO 300 WORK CLAMP - 712231



## TELMIG 281/2

SPACER - 322499



ARGON GAS BOTTLE IT ADAPTOR - 432036



GAS REGULATOR REFILLABLE BOTTLE - 722341

MT25 MIG TORCH 3M - 742183