



TELMIG 250/2



Overview

TELMIG 250/2

cod. 821061

MIG-MAG welding machine. Designed for continuous and spot welding with electronic regulation of spotwelding time. Flexibility of use with a wide range of materials such as steel, stainless steel, highstrength steels and aluminium. Complete with MIGMAG welding accessories.



3 PH 230V-400V



CE MARKING



EAC CERTIFICATION



COIL 15 kg

Technical data

CODE	CODE 821061	V₀ DC	MAX NO LOAD VOLTAGE 33 V	SS	INOX WELDING WIRE DIAMETER 0,8 - 1 mm
V_{3PH}	THREE PHASE MAINS VOLTAGE 230 / 400 V	P_{MAX}	MAX ABSORBED POWER 7 kW	AL	ALUMINIUM WELDING WIRE DIAM. 0,8 - 1 mm
F	MAINS FREQUENCY 50 / 60 Hz	P_{60%}	ABSORBED POWER AT 60% 3 kW	IP	PROTECTION DEGREE IP21
A_{MIN} / A_{MAX} DC	CURRENT RANGE 35 - 260 A	cosφ	POWER FACTOR (cosphi) 0,9	W_H / L	DIMENSIONS 80 x 45 x 65,5 cm
A_{MAX} 40°C DC	MAX CURRENT DC (EN 60974-1) 200 @ 20 % A	SUN	ADJUSTMENT POSITIONS 6	kg	WEIGHT 50 kg
A_{60%} 40°C DC	DC CURRENT 115 A	ST	STEEL WELDING WIRE DIAMETER 0,6 - 1 mm	BAR CODE	EAN CODE 800489759562 7

Included Accessories

CABLE 25 MMQ 2 M - 123466



TOLEDO 250 WORK CLAMP 250A - 712030



TELMIG 250/2

SPACER - 322499



ARGON GAS BOTTLE IT ADAPTOR - 432036



GAS REGULATOR REFILLABLE BOTTLE - 722341

MT15 MIG TORCH 3M (RED) - 742180