



MASTEMIG 300



Overview

MASTEMIG 300

cod. 827003

MIG-MAG/FLUX/BRAZING welding machine with removable wire feeder, fit for use in the industrial field.

Flexibility of use with a wide range of materials such as steel, stainless steel, high strength steels and aluminium.

Features:

- Very strong
- Numerous steps for regulation of arc voltage
- Regulation of spot welding time
- Two positions for reactance
- Thermostatic protection

Thanks to the extensions (optional) it is possible to increase the working range between wire feeder and power source up to 10 meters.

Complete with MIG-MAG welding accessories.



MIG-MAG FLUX



COIL 15 kg



EAC CERTIFICATION



3 PH 230V-400V



CE MARKING

Technical data



CODE 827003



MAX NO LOAD VOLTAGE 41,5 V



STEEL WELDING WIRE DIAMETER 0,6 - 1,2 mm



THREE PHASE MAINS VOLTAGE 230 / 400 V



MAX ABSORBED POWER 11,5 kW



INOX WELDING WIRE DIAMETER 0,6 - 1,2 mm



MAINS FREQUENCY 50 / 60 Hz



ABSORBED POWER AT 60% 6 kW



ALUMINIUM WELDING WIRE DIAM. 0,8 - 1,2 mm



CURRENT RANGE 40 - 300 A



MAINS FUSE 16 / 10 A



FLUX CORED WELDING WIRE DIAM. 1 - 1,2 mm



MAX CURRENT DC (EN 60974-1) 300 @ 25 % A



POWER FACTOR (cosphi) 0,9



BRAZING WIRE DIAM. 0,8 - 1,2 mm



MASTERMIG 300



DC CURRENT 200 A



ADJUSTMENT POSITIONS 12



PROTECTION DEGREE IP22

Included Accessories



ARGON GAS BOTTLE IT ADAPTOR - 432036



GAS REGULATOR 2 MANOMETERS 12 L\min - 722119

TORCH HOOK - 644444

MT25 MIG TORCH 3M - 742183

CABLE 25MMQ 3M-WORK CLAMP-ATLAS 50MMQ - 713192

FEED ROLL 4R 0,6FE-0,8/0,9FE "P-K" - 742576