

The NEOPULSE 220 C is a single-phase pulsed MIG/MAG generator with digital technology. Designed for the highest performance level using the latest technology, it features numerous synergic curves and exceptional arc quality/performance. Intuitive and highly functional, the digital interface allows for quick and easy modifications of the welding parameters. Fitted with an accurate and powerful 4 drive roll feeding system, the NEOPULSE 220 C offers manufacturers maximum productivity.

MULTI-PROCESS WELDING

- **MIG/MAG :**
 - steel and stainless steel wire: Ø 0.6 to 1.0 mm
 - aluminium wire: Ø 0.8 to 1.2 mm
 - CuSi and CuAl wire: Ø 0.8 to 1.0 mm
- **MMA DC / Pulse :** basic, rutile and cellulosic electrodes (up to Ø 5 mm).
- **TIG DC Lift / Pulse.**

SMART

- **SYNERGIC mode:** After selecting 2 criteria (material/gas combination and the wire diameter), NEOPULSE automatically works out the optimal welding conditions while still allowing you to adjust the settings (wire feed rate, voltage, current, arc length).

ACCURATE

- **Calibration** of the wire feed speed to adjust the displayed voltage measurement and refine the energy calculation.
- **Energie**, display and energy calculation after welding based on standards EN1011-1, ISO / TR 18491 and QW-409.
- **Portability :** load/backup user JOBS and machine configuration from a USB key.
- **Traceability :** trace / record all welding steps, cord by cord, during industrial manufacturing in line with standard EN ISO 3834.

OPTIMISED MIG/MAG SETTINGS

- **Welding processes:** Manual, Dynamic STD, Pulsed, Arc Module (variation of hot / cold current)
- **TACK modes:** SPOT and DELAY.
- **Trigger options supported:** 2T and 4T.
- **Precise control over the welding cycle :** CreepSpeed, Softstart, Hotstart, Upslope, Downslope, Crater Fill, Postgas, etc.

MAXIMUM PRODUCTIVITY

- **4 microprocessors** giving four times the processing power.
- **High productivity** thanks to high duty cycle (150 A @ 60%).
- **Compatible wire reels:** Ø 200 mm.
- **Powerful 4 roller wire-feeder** for efficient wire feeding.
- **Very high arc voltage** for easier ignition and exceptional arc dynamic.

INTUITIVE

- New user friendly interface focused on welders' navigation habits.
- Update of the machine and synergies using a USB key.
- Storage of 500 welding programs (can be saved on USB stick).
- Displays current/voltage during and after welding (WPS/PQR).
- Choice of the main parameter to display on the screen (wire speed, average welding current, etc.).
- Intelligent ventilation management to reduce power consumption, dust intake and noise.
- Compatible torch Push Pull (24 V).

ROBUST AND MOBILE

- Reinforced metal case & non slip rubber pads.
- IP23S case.
- 2 handles for easier mobility.



Supplied without accessories



3 levels of interface for the user:

- Easy: simplified features
- Expert: full display
- Advanced: full access to all parameters

50/60 Hz	A	A	Ø mm		200	300	Ø mm	Electronic Control	m/min	équipé d'origine / original equipment / originalausstattung / equipamiento de fabrica	MIG-MAG	MMA	TIG	U ₀	↕	kg	IP	Protected & compatible power generator (+/-15%)
230 V 1~	16	10 → 220	GAS	NO GAS	✓	-	1 → 5	⊕⊖	0.5 - 20	⊕	EN 60974-1 (40°C)	EN 60974-1 (40°C)	EN 60974-1 (40°C)	V	cm	27	IP 23S	7.5 kVA
			0.6	0.9						⊕	150A @ 60%	150A @ 60%	160A @ 60%	80	55 x 29 x 41			
			1.2	1.2						⊕	130A @ 100%	120A @ 100%	150A @ 100%					