

- Test torque wrenches, torque screwdrivers and other torque tools
- Clockwise operation
- Peak, track and first peak working modes
- Tolerance testing
- LED indicator for the target torque alarm: green LED light on when the value is within tolerance; red LED light on when the value is above the high tolerance
- Power off automatically in 2 minutes without any operations

SPECIFICATION

| Code | IST-04TT5 | IST-04TT28 | IST-04TT68 | IST-04TT350 | IST-04TT815 | IST-04TT1000 | IST-04TT2000 |
|--------------------------|-------------------|------------|------------|-------------|-------------|--------------|--------------|
| Туре | A | | | | В | | |
| Range | 0.5~5N.m | 2.8~28N.m | 6.8~68N.m | 35~350N.m | 81.5~815N.m | 100~1000N.m | 200~2000N.m |
| Accuracy | ±1% (clockwise) | | | | | | |
| Resolution | 0.001N.m | 0.01N.m | 0.01N.m | 0.1N.m | 0.1N.m | 1N.m | 1N.m |
| Unit | N.m, in.lb, ft.lb | , kg.cm | | | N.m, ft.lb | | |
| Square socket/hex driver | 1/4" | 3/8" | 3/8" | 1/2" | 27mm | 27mm | 27mm |
| Power supply | DC | | | | | | |
| Weight | 0.75kg | 0.75kg | 1.1kg | 1.1kg | 5.1kg | 5.1kg | 5.1kg |

STANDARD DELIVERY

| Main unit | 1 pc |
|---------------|------|
| AC/DC adapter | 1 pc |