Air Velocity Meyer

TM-412~TM-414 TM-412A~TM-414A

Features

- ♦ 45mm 4 plastics blade.
- ♦ Light air response 0.4m/s
- Rapid response temperature sensor
- · Air flow calculate function.
- Max/Min/Avg and data hold.
- Auto power off with disable function.
- Low battery indication.
- Data logging capacity: 99 records.
- · Memory recall function.
- · Backlight function.
- Absolute Pressure Sensor.
- Humidity Sensor
- DEW-POINT and WET-BULB temperature measuremen



Protection Holster(optional)

Specifications

Functions Cross table	Velocity	Flow	99 Record	Temperature	Humidity	Pressure
TM-412 (With Vane-02)	•	•	•	•		
TM413 (WithVane-03)	•	•	•	•	•	
TM-414 (WithVane-04)	•	•	•	•	•	•

Absolute Pressure

Unit	Range	Resolution	Accuracy
hPa	350~1100	0.1	±2hPa
mmHg	263~825	0.1	±1.5mmHg
inHg	10.3~32	0.1	±0.1inHg

Temperature

Unit	Range	Resolution	Accuracy
°C	-20~60	0.1	±1°C
°F	-4~140	0.1	±1.8°F

Air Flow Calculation

Unit	Range	Resolution	Accuracy
CMM	0~9999	1	1
CFM	0~9999	1	3=0

Humidity

Unit	Range	Resolution	Accuracy
%RH	20~80	0.1	±3.5%RH
%RH	<20,>80	0.1	±5%RH

Velocity

Unit	Range	Resolution	Accuracy
m/s	0.4~30	0.1	±3%+0.2
Km/hr (kph)	1.5~106	0.1	±3%+0.8
mph	0.9~66	0.1	±3%+0.4
Knots (kts)	0.8~58	0.1	±3%+0.4
ft/min (fpm)	79~5866	1	±3%+40
Beaufor	1~8	1	_