

# MANPOWER CLIMATE INCUBATOR

## MINC036



### Specifications

|                                   |              |              |              |              |              |              |
|-----------------------------------|--------------|--------------|--------------|--------------|--------------|--------------|
| Model                             | 160A         | 160B         | 160C         | 160D         | 280A         | 280B         |
| Work voltage (V)                  | AC220V 50HZ  |              |              |              |              |              |
| Range of temperature control (°C) | 0 ~ 50 °C    |              |              |              |              |              |
| Wave degree of temperature (°C)   | ±1.0 °C      |              |              |              |              |              |
| Humidity controlling scope (RH %) | 50 ~ 95      |              |              |              |              |              |
| Fluctuating degree (RH %)         | ± 7%RH       |              |              |              |              |              |
| Illumination (LX)                 | 0 ~ 4000     | 0 ~ 12000    | 0 ~ 22000    | 0 ~ 30000    | 0 ~ 4000     | 0 ~ 12000    |
| Temperature resolution            | 0.1          |              |              |              |              |              |
| Cubage (L)                        | 160          |              |              |              | 280          |              |
| Size of working room (mm)(L×W×H)  | 540×540×650  | 540×540×650  | 540×540×650  | 540×540×650  | 540×540×1050 | 540×540×1050 |
| Overall dimension (mm) (L×W×H)    | 600×600×1300 | 600×600×1300 | 600×600×1300 | 600×600×1300 | 600×600×1700 | 600×600×1700 |