

# COMBINED OSCILLATING INCUBATOR MINC045



## Specifications

|                                |                                     |          |                                      |             |   |          |
|--------------------------------|-------------------------------------|----------|--------------------------------------|-------------|---|----------|
| Model                          | 85A                                 | 85B      | 115A                                 | 115B        | 228A  | 228B     |
| Work voltage (V)               | AC220 + 10% /50 ~ 60Hz              |          |                                      |             |   |          |
| Timing scope:(min)             | 0 ~ 9999min                         |          |                                      |             |   |          |
| Marking control system         | LCD                                 |          |                                      |             |   |          |
| Oscillating frequency          | 30 ~ 350rpm                         |          |                                      | 30 ~ 300rpm |   |          |
| Oscillation frequency accuracy | ± 1rpm                              |          |                                      |             |   |          |
| Temperature control range      | RT +5 ~ 65(℃)                       | 4~ 65(℃) | RT +5 ~ 65(℃)                        | 4~ 65(℃)    | RT +5 ~ 65(℃)                                   | 4~ 65(℃) |
| Wave degree of temperature (℃) | ±0.3 ℃                              |          |                                      |             |   |          |
| Temperature resolution         | 0.1                                 |          |                                      |             |   |          |
| Roll plate size                | 400×370(mm)                         |          | 520×430(mm)                          |             | 850×530(mm)                                     |          |
| Standard capacity (mL×number)  | 100×20 or 250×16 or 500×9 or 1000×5 |          | 100×25 or 250×20 or 500×12 or 1000×6 |             | 100×45 or 250×28 or 500×28 or 1000×14 or 2000×9 |          |
| Power (KW)                     | 0.68                                | 0.8      | 0.48                                 | 0.7         | 1.2   | 1.5      |
| Outer size (mm) (L×W×H)        | 765×815×550                         |          | 885×735×550                          |             | 1270×900×600                                    |          |