DIGITAL ADHESION TESTER CODE SPT-AD21



- Pull-offtest
- Built-in rechargeable lithium battery, no need external power source
- Portable design, can be used anywhere
- Standard USB interface, can directly transmit the stored data to computer, no need to install software
- Conforms to GB/T 5210, ASTM D4541/D7234, ISO 4624/16276-1
- Store all test results, includes maximum pull-off force, pull-off rate, dolly size and time
- Built in real-time clock, all saved data have corresponding date and time
- Selectable four different sizes dolly for different resolution and testing range
- No need conversion, the instrument can calculates pull-off force according to the dolly size
- Get the testing results from LCD directly
- Two units MPa and psi for selection and can be converted automatically



Ø20mm Dolly(included)



Cutting tool(included)



Glue gun and glue(included)

SPECIFICATION

Range	0~20MPa	
Dolly Diameter	Ø20mm	
Resolution	0.01Mpa(1psi)	
Accuracy	±1% full scale	
Pull-offForce	0.7~20MPa	
Power	Built-in rechargeable lithium battery	
Dimension(LxWxH)	360x75x115mm	
Weight	3kg	

STANDARD DELIVERY

Main unit	1pc
Ø20mm dolly	20pcs
Cutting tool for Ø20mm dolly	1pc
Charger	1pc
USB cable	1pc
Glue gun	1pc
3M glue	1pc

OPTIONAL ACCESSORY

Ø10mm dolly	SPT-AD21-10	10pcs/package Pull-offforce: 2.8~80Mpa
Ø14mm dolly	SPT-AD21-14	10pcs/package Pull-offforce: 1.4~40Mpa
Ø20mm dolly	SPT-AD21-20	10pcs/package Pull-offforce: 0.7~20Mpa
Ø50mm dolly	SPT-AD21-50	10pcs/package Pull-offforce: 0.4~3.5Mpa
Cutting tool	SPT-AD21-CUTTER1	For Ø10mm, Ø14mm, Ø20mm dolly
Cutting tool	SPT-AD21-CUTTER2	For Ø50mm dolly
Glue	SPT-AD21-GLUE	3M DP420 epoxy glue/50ml