Г

Technical Data

• Accuracy of wire diameter: ±0.002 mm

3-Wire Units SERIES 313

 Attached to the measuring faces of both the spindle and anvil of the micrometer, enables measurement of pitch diameter of screw threads. • Determination of the pitch diameter: refer to "Quick Guide to Precision Measuring Instruments" on page B-68.



SPECIFICATIONS

Order No.		Pitch		
(One pair) (Support spindle dia.) 6.35 mm (0.25 in)	Wire dia. (mm)	Metric thread (mm)	Unified thread (threads per inch)	Whitworth thread (threads per inch)
952131	0.170	0.2, 0.25, 0.3	80	_
952132	0.195	0.35	72	_
952133	0.220	0.4	64	_
952134	0.250	0.45	56	60
952135	0.290	0.5	48	48
952136	0.335	0.6	44, 40	40
952137	0.390	0.7	36	36
952138	0.455	0.75, 0.8	32	32
952139	0.530	0.9	28	28, 26
952140	0.620	1.0	24	24, 22
952141	0.725	1.25	20	20, 19, 18
952142	0.895	1.5	18, 16	16
952143	1.100	1.75, 2.0	14, 13, 12	14, 12
952144	1.350	2.5	11, 10	11, 10
952145	1.650	3.0	9, 8	9, 8
952146	2.050	3.5	7	7
952147	2.550	4, 4.5	6	6
952148	3.200	5, 5.5, 6	5, 4.5	5, 4.5

3-Wire Units set

Order No.	Set	Wire dia. (mm)	Support spindle dia. (mm)
313-101	18	0.170 - 3.200	6.35

Note 1: Special-specification 3-wire units with a wire diameter other than those listed above (ø0.15 mm or more) can also be made to order.

Micrometer Oil

• Special lubricant for micrometers.





SPECIFICATIONS

Order No.	Product name	Remarks
207000	Micrometer oil	Grease (32 ml)



Note 2: Due to potential obstruction, the 3-wire unit cannot be used with screws having an external diameter exceeding \emptyset 50 mm.