

E100



NETWORK GNSS RECEIVER

■ Compact Design: Easy to Carry

Easily carry it in a variety of complex environments, benefiting from its lightweight and compact design.

■ RTK Assistant Technology: Uninterrupted Work

Work without interruption even when RTK corrections fail, powered by our RTK assistant technology.

■ Max 60° Tilt Survey: A Different Way of Working

- Quickly measure accurate points while standing or walking without leveling the pole.
- Concentrate on where the pole tip needs to go, which is especially useful during a stakeout.
- Easily start a survey in environments that are hard to reach, such as building corners and slopes.
- No longer worry about the movement of the pole when measuring, provided that the pole tip is stationary.

The eSurvey E100 is a network receiver produced by eSurvey GNSS. This entry-level GNSS solution handles multiple frequencies from multiple constellations, improving position accuracy. Thanks to its ultra-compact design and built-in RTK assistant function, the E100 is an ideal rover station receiver for a CORS system. The E100 is suitable for different applications such as car and machine control.

Specification

GNSS Performance		
Satellites tracking	GPS	L1CA, L2P(Y), L2C, L5
	BDS	B1I, B2I, B3I, B1C, B2a, B2b ¹
	GLONASS	L1, L2
	GALILEO	E1, E5a, E5b, E6 ¹
	QZSS	L1, L2, L5, L6 ¹
	L-Band	B2b PPP (Only for the Asian-Pacific region)
Channels	1408	
Cold start	< 30 seconds	
Warm start	< 20 seconds	
Hot start	< 5 seconds	
RTK signal initialization	< 5 seconds	
Initialization reliability	> 99.9%	
Update rate	20 Hz	
High precision static	<ul style="list-style-type: none"> H: 3 mm + 1 ppm RMS V: 5 mm + 1 ppm RMS 	
RTK	<ul style="list-style-type: none"> H: 8 mm + 1 ppm RMS V: 15 mm + 1 ppm RMS 	
Standard point positioning	<ul style="list-style-type: none"> H: 1.5 m RMS V: 2.5 m RMS 	
Code differential	<ul style="list-style-type: none"> H: 0.4 m RMS V: 0.8 m RMS 	
Correction data	RTCM V3.X, RTCM2, CMR	
Data output	GGA, ZDA, GSA, GSV, GST, VTG, RMC, GLL, Binary	

Power Supply	
Battery	Rechargeable Built-in Lithium-ion battery x 1 7.2V ~ 6900 mAh
Voltage	9 - 28V dc
Working time	<ul style="list-style-type: none"> RTK: 14 hours Static: 15 hours
Charging time	Typically 4 hours

1: It is not supported for now. It will be supported after firmware update in the future.

Internet Modem	
Supported band	Global 4G <ul style="list-style-type: none"> LTE FDD: B1, B2, B3, B4, B5, B7, B8, B12, B13, B18, B19, B20, B25, B26, B28 LTE TDD: B38, B39, B40, B41 UMTS: B1, B2, B4, B5, B6, B8, B19 GSM: B2, B3, B5, B8

System	
Operation system	Linux
Internal memory	8 GB
Bluetooth	BT5.0+EDR, BLE
Wi-Fi	802.11 a/b/g/n/ac
SIM card	√
5-pin port	Connect to external radio and external power
Type-C port	Charge and data transmission
Web UI	View status, update firmware, set up working mode, download data, etc.
Intelligent voice	Broadcast working mode and status
MEMS	Fast initialization, dynamic tilt survey up to 60°

Physical	
Dimension	Φ148 mm x H77 mm
Weight	900 g
Operating temperature	-30°C - +65°C
Storage temperature	-40°C - +80°C
Water / dust proof	IP67
Shock	<ul style="list-style-type: none"> Withstand topple over from a 2 m survey pole onto hard surfaces Survive a 1.2 m free drop
Vibration	Vibration resistant
Humidity	Up to 100%
Indicators	Satellites, datalink, battery, Bluetooth
Button	Power button, short press to voice broadcast working mode and status
Certificate	CE, FCC, NGS

