

UT32

8" Rugged Android Tablet

IP67 certificated, UT32 is designed for anyone who works in harsh environments. The battery handles whole day's work for different kinds of applications. UT32 is suitable for outdoor work such as survey, GIS, retail, logistics, monitoring.



High Performance CPU

Equipped with octa-core 2.2 GHz processor and Android 10.0 system, UT32 brings with smooth experience.

High Resolution Screen

The 8-inch screen with 1280 x 800 resolution makes UT32 a high-fidelity device. 400-nits brightness makes it Sunlight viewable.

Long-time Operation

The 8200 mAh rechargeable and replaceable battery ensures whole day's work without interruption. Quick charge 3.0 brings you fast charging experience.

GNSS Constellation Supported

Build-in GNSS module supports GPS, BDS, GLONASS and GALILEO. For a better signal acquisition, the external antenna is supported.

Large Memory Storage

UT32 has 64 GB internal storage to support large data access. It also supports SD card expansion up to 128 GB.

Powerful Extension Function

The pogo pin makes UT32 a powerful device for different kinds of applications. It is able to connect to external scanner and other modules as you want.

Rugged Design

UT32 is IP67 certificated as a rugged device. It survives a 1.2 m drop on concrete floor and passes the MIL-STD-810G certifications.

Product Specification

System			Support OTG and headphone
Processor	Qualcomm MSM8953 Pro	Pogo pin	14 pins
	Octa-Core, 2.2GHz		
OS	Android 10.0	Power Supply	
RAM	4 GB	Rechargea	Rechargeable and replaceable Lithium
ROM	64 GB		ion battery, 3.8 V, 8200 mAh
GMS	Support	Working	Up to 15 hours ¹
Screen		Charge	Qualcomm quick charge 3.0
Screen Size	8"	Safety Lock	With battery safety lock
Resolution	1280 x 800		
Density	320 dpi	Sensor	
Brightness	400 nits	NFC	Yes
Touch Panel	Capacitive	Speaker	Yes
		Microphone	Yes
Camera		Light	Yes
Rear	13 MP	Proximity	Yes
Front	5 MP	Magnetometer	Yes
Flash Light	Support	— Gyroscope	Yes
Auto Focus	Support	Barometer	Yes
		Accelerometer	Yes
GNSS		Gravity	Yes
Tracking	GPS/BDS/GLONASS/GALILEO	Compass	Yes
SBAS	Support		
Accuracy	Single: 1 ~ 3 m	Physical	
	SBAS: 0.6 m	Dimension	235 x 146 x 14.5 mm
External Antenna	Support, Female MMCX	Weight	660 g with battery
		vv Cigiit	505 g Without battery
Communication		Operating Temperature	-20°C ~ +60°C
GSM	GSM/WCDMA/LTE	Storage Temperature	-40°C ~ +70°C
	1 x Nano SIM	Water/Dust Proof	IP67
Call	Support	MIL-STD	MIL-STD-810G
SMS	Support	Shock	Survive a 1.2 m drop on concrete floor
WIFI	802.11 a/b/g/n/ac	Humidity	95%
Bluetooth	4.1	Buttons	Menu, home, return, volume +/-,
SD Card	Support, up to 128 GB		power, 2 x FN
USB	1 x USB Type-C	Certificate	FCC, IC, CE, RoHS, REACH, WEEE
	1 , ,		



 $^{1. \} The \ actually \ working \ time \ depends \ on \ the \ temperature \ and \ the \ running \ software.$