Surface Dial Thermometer

Description

A range of surface mount stainless steel bimetal dial thermometers for temperature measurement of pipes and surfaces.

These reliable, robust and compact design surface thermometers have a 63mm stainless steel dial and are available with two contact types: a spring option for heating and water pipes between 3/8" and 1 ½" diameters and a magnetic mount option for ferrous surfaces, such as radiators.

There are five temperature ranges available: -30 to +60 °C, 0 to 120 °C, 0 to 160 °C, 0 to 250 °C and 0 to 400 °C.



Features

- Accuracy Class 2.0 (BS EN13190)
- Magnetic or Spring Mount
- Stainless Steel Case (IP40)
- Dual Temperature Scale C or F

Application

- Heating and Water Pipes
- Ferrous Vessels
- Radiators

Specification

Product	Surface Dial Thermometer
Pipe Size	3/8" and 1 ½"
Accuracy	Class 2 (BS EN13190)
	-30/+60 °C, 0/120 °C
Temp Ranges	0/160°C, 0/250 °C
	0/400°C
Scale	°C outer black, °F inner Red
Material	Stainless Steel
IP rating	IP40
Dial Size	63mm
Part Number	ISBIM





Sterling Sensors UK Ltd

Fitmec Works : Hawksley Street : Oldham United Kingdom : OL8 4PQ

T: +44 (0) 161 620 0410 F: +44 (0) 161 627 0507 E: sales@sterlingsensors.co.uk W: sterlingsensors.co.uk