KERN **ABP 200-5DAM**

Premium analytical balance with the latest Single-Cell Generation for extremely rapid, stable weighing resultsÂ- now also as a version with automatic sliding doors



Measuring system	
Adjustment options:	Internal calibration (auto) Internal calibration (manual)
Eccentric loading at 1/3 [Max]:	0,100 mg
Linearity:	0,100 mg | 0,200 mg
Minimum weight (USP):	100 mg
Readability [d]:	0,010 mg | 0,100 mg
Repeatability:	0,050 mg | 0,100 mg
Resolution:	10.200.000 2.200.000
Stabilisation time under laboratory conditions:	8 s | 2 s
Tare range:	220 g
Warm up time:	8 h | 8 h
Weighing capacity [Max]:	102 g | 220 g
Weighing units:	ct g mg

Display	
Display digit height (large):	1,200 cm

Technical data about verification	
Minimum load [Min]:	1 mg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	I
Verification value [e]:	1 mg | 1 mg

Counting	
Counting resolution:	220000
Mininum piece weight at piece counting (Laboratory:	1 mg
Mininum piece weight at piece counting (Normal):	10 mg
Reference weight:	yes

Functions	
Capacity display:	yes
Counting function:	yes
Function to save totals:	yes
Percentage determination:	yes
Standby function:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	30 °C
Minimum ambient temperature:	10 °C

Power supply	
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH AUS US UK EURO

Services (optional)	
DAkkS Certificate:	963-101
Verification:	965-201

Category	
Brand:	KERN
Category:	Balances
Product Group:	Analytical balance

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	382 x 585 x 535 mm
Gross weight:	12,300 kg
Net weight:	7,900 kg
Shipping method:	Parcel service

KERN **ABP 200-5DAM**

Premium analytical balance with the latest Single-Cell Generation for extremely rapid, stable weighing resultsÂ- now also as a version with automatic sliding doors

Construction

Dimensions draft shield (WxDxH):	213 x 156 x 225 mm
Dimensions housing (WxDxH):	595 x 380 x 540 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Weighing space (WxDxH):	166 x 156 x 220 mm
Weighing surface (d):	91

Piktogramme

STANDARD



OPTION



FACTORY

