## KERN **PWS8000-1**



High-resolution precision balance made of stainless steel with IP protection



Measuring system				
Adjustment options:	External calibration			
Eccentric loading at 1/3 [Max]:	300 mg			
Linearity:	100 mg			
Minimum weight (USP):	200 g			
Number of weighing ranges:	1			
Readability [d]:	100 mg			
Recommended adjusting weight:	2 kg (F1); 5 kg (F1)			
Repeatability:	100 mg			
Resolution:	82000			
Stabilisation time under laboratory conditions:	3 s			
Tare range:	3,200 kg			
Warm up time:	2 h			
Weighing capacity [Max]:	8,200 kg			
Weighing units:	ct g kg			
Display				
Display digit height (large):	1,650 cm			
Counting				
Counting resolution:	82000			
Mininum piece weight at piece	100 mg			

o o an ang rooona ao n	02000
Mininum piece weight at piece counting (Laboratory:	100 mg
Mininum piece weight at piece counting (Normal):	1 g
Reference weight:	yes

Functions	
Capacity display:	yes
Counting function:	yes
Percentage determination:	yes
Weighing with tolerance range:	yes
Environmental conditions	
	00.0/
Maximum humidity:	80 %
Maximum operating temperature:	30 °C 10 °C
Minimum ambient temperature:	10 C
Power supply	
Battery:	4x1.5 V AA
Input voltage:	100 V - 240V AC 50/60Hz 0.3A
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH AUS US UK EURO
Operating time:	200 h
Services (optional)	
	000.400
DAkkS Certificate:	963-128
Category	
Brand:	KERN
Category:	Balances
Product Group:	<b>B</b> 11 1 1
	Precision balance
Packaging & shipping	Precision balance
Packaging & shipping Delivery:	Precision balance
Delivery:	24 h
Delivery: Dimensions packaging (WxDxH):	24 h 325 x 405 x 230 mm
Delivery: Dimensions packaging (WxDxH): Gross weight:	24 h 325 x 405 x 230 mm 2,870 kg
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	24 h 325 x 405 x 230 mm 2,870 kg 1,520 kg
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	24 h 325 x 405 x 230 mm 2,870 kg 1,520 kg
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	24 h 325 x 405 x 230 mm 2,870 kg 1,520 kg Parcel service
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material:	24 h 325 x 405 x 230 mm 2,870 kg 1,520 kg Parcel service stainless steel
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Level indicator:	24 h 325 x 405 x 230 mm 2,870 kg 1,520 kg Parcel service stainless steel yes
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Level indicator: Material weighing plate: Overall dimensions mounted	24 h 325 x 405 x 230 mm 2,870 kg 1,520 kg Parcel service stainless steel yes stainless steel

## KERN **PWS8000-1**



High-resolution precision balance made of stainless steel with IP protection

## Piktogramme

## STANDARD

CAL EXT	• 6884 •	GLP		%	-√+ ⊙	666	C H	((( <b>Ų</b> )))
CAL EXT	RS 232	PRINTER	PCS	PERCENT	TOL	IP 65	MULTI	T-FORK

1 DAY

OPTION

