



Shanghai Yoke Instrument Co., Ltd.

Add: No. 228, Qingling Road, Fengxian, Shanghai, 201414, China

Mobile/Wechat/Skype/WhatsApp: +86 15542693398

E-mail: sarah@yoke-fac.com

Contact person: Sarah Wang



www.yoke-fac.com

About Us

Yoke Instrument was founded in 2007. we are a specialized manufacturer of laboratory analytical instruments based in Shanghai. Main products: Spectrophotometer, GC, pH/Conductivity/DO Meter, Ion Meter, Turbidity Meter, Colorimeter, COD, Moisture Analyzer, Balance and biological microscope, etc.

Using advanced production equipment from Japan, our products are manufactured to CE standards. And we inspect 100 percent of products before shipping. OEM/ODM orders are welcomed. and our senior R&D staff will meet your requests quickly. we are constantly striving to innovate- a thirst which has aided us in garnering nine patents in China.

With reliable quality, favorable price and sincere service, Yoke has successfully established business cooperation with customers from more than 80 countries and have good reputation. We will further promote ourselves and enhance customer satisfaction to create a win-win situation between Yoke and customers.

Contents

Spectrophotometer

X Series Xenon Lamp Spectrophotometer
T Series PMT Spectrophotometer
M Series PC Controlled Spectrophotometer
K Series Touch Screen Spectrophotometer
K Series Color Screen Spectrophotometer
U Series Touch Screen Spectrophotometer
N Series Color Screen Spectrophotometer
1900 Series Double Beam Spectrophotometer
1800 Series Single Beam Spectrophotometer
1700 Series Single Beam Spectrophotometer
1600 Series Single Beam Spectrophotometer
2000 Series Single Beam Spectrophotometer
1200 Basic Spectrophotometer
1000 Basic Spectrophotometer
Accessories

Water Quality Instrument

P9 Series Tablet pH/EC/DO Meter
P8 Series Touch Screen pH/EC/DO/Ion Meter
P7 Series Benchtop pH/EC/DO/Ion Meter
P6 Series Portable pH/EC/DO/Ion Meter
P5/P3 Series Pen type pH/EC Meter
Mini Magnetic Stirrer
Turbidity Meter
Colorimeter

Balance

Moisture Analyzer
SY Series Touch Screen Balance
YK Series 0.1mg/1mg Balance
FA/JA Series 0.1/1mg Balance
YP Series 10mg/100mg/1g Balance

Microscope

Biological Microscope

X Series Flashing Xenon Lamp Spectrophotometer



- High quality flashing xenon lamp is from Hamamatsu, which can start to test directly without preheating. The lamp can be used at least 3-year.
- Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, multi-wavelength test, etc
- In-house massive memory is capable of saving up to 1024M for test data & working curves.
- Supports USB storage. The USB port can be used for data transfer, which is easily exported to Excel for further processing, analysis and storage.
- Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
- Extensive accessories are optional, such as auto 8-cell holder, film holder, peltier/sipper system, 21 CFR compliant software, built-in thermal printer, etc.

Model	X8000	X8001	X8001S	X9000	X9001	X9001S
Optical System	Double Beam, Grating 1200 lines/mm					
Wavelength Range	190-1100 nm					
Spectral Bandwidth	2nm	1nm	0.5/1/2/4/5	2nm	1nm	0.5/1/2/4/5
Wavelength Accuracy	±0.1nm@656.1nm, ±0.3nm@all					
Wavelength Repeatability	≤0.1nm					
Photometric Accuracy	0.2%T(0~100%T), ±0.002A(0-0.5A), ±0.004A(0.5-1A)					
Photometric Repeatability	≤0.15%T (0-100%T), 0.001A(0-0.5A), 0.002A(0.5-1A)					
Photometric Range	0-200%T, -0.3~3A, 0-9999C (0-9999F)					
Stray Light	≤0.03%T@220nm, 360nm					
Stability	±0.0005A/h@500nm			±0.0003A/h @500 nm		
Baseline Flatness	±0.0002A	±0.001A		±0.0002A	±0.001A	
Noise	0.0005A@500nm					
Work Mode	T, A, C, E					
Scanning Speed	Hi, Med, Low (Max. 3000nm/min)					
Wavelength Setting	Auto					
Display	7" TFT Color Screen			10.1" TFT Colored Capacitive Touch Screen		
Light Source	Imported Xenon Lamp					
Detector	Imported Silicon Photodiode					
Cuvette Holder	10mm single hole cell holder					
Output	USB drive, USB host, RS232					
Power	AC 220V/50Hz or AC 110V/60Hz					
Shipping Size	810*660*390mm		880*690*520mm	810*660*390mm		880*690*520mm
Gross Weight	27kg		45kg	27kg		45kg
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2, Power cord, User's Manual , PC software					

T Series PMT Spectrophotometer



- The use of photomultiplier tube as a detector offers exceptional sensitivity.
- Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, multi-wavelength test, etc
- In-house massive memory is capable of saving up to 1024M for test data & working curves.
- Supports USB storage. The USB port can be used for data transfer, which is easily exported to Excel for further processing, analysis and storage.
- Socket type deuterium and tungsten lamp can make lamps switching without optics debugging and easy to be replaced.
- Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
- Extensive accessories are optional, such as auto 8-cell holder, film holder, peltier/sipper system, 21 CFR compliant software, built-in thermal printer, etc.

Model	T8000	T8001	T8001S	T9000	T9001	T9001S
Optical System	Double Beam, Grating 1200 lines/mm					
Wavelength Range	190-1100 nm					
Spectral Bandwidth	2nm	1nm	0.5/1/2/4/5	2nm	1nm	0.5/1/2/4/5
Wavelength Accuracy	±0.1nm@656.1nm, ±0.3nm@all					
Wavelength Repeatability	<=0.1nm					
Photometric Accuracy	0.2%T(0~100%T), ±0.002A(0-0.5A), ±0.004A(0.5-1A)					
Photometric Repeatability	≤0.15%T (0-100%T), 0.001A(0-0.5A), 0.002A(0.5-1A)					
Photometric Range	0-200%T, -4~4A, 0-9999C (0-9999F)					
Stray Light	<=0.03%T@220nm, 360nm					
Stability	±0.0005A/h@500nm			±0.0003A/h @500 nm		
Baseline Flatness	±0.0002A	±0.001A		±0.0002A	±0.001A	
Noise	0.0005A@500nm					
Work Mode	T, A, C, E					
Scanning Speed	Hi, Med, Low (Max. 3000nm/min)					
Wavelength Setting	Auto					
Display	7" TFT Color Screen			10.1" TFT Colored Capacitive Touch Screen		
Light Source	Imported Deuterium & Tungsten lamp					
Detector	Imported Photomultiplier Tube					
Cuvette Holder	10mm single hole cell holder					
Output	USB drive, USB host, RS232					
Power	AC 220V/50Hz or AC 110V/60Hz					
Shipping Size	810*660*390mm		880*690*520m	810*660*390mm		880*690*520m
Gross Weight	27kg		45kg	27kg		45kg
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2, Power cord, User's Manual , PC software					

M Series PC Controlled Spectrophotometer



- PC controlled design without display screen and keyboard, and easy to operate on a computer.
- Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, multi-wavelength test, etc
- In-house massive memory is capable of saving up to 1024M for test data & working curves.
- Supports USB storage. The USB port can be used for data transfer, which is easily exported to Excel for further processing, analysis and storage.
- Socket type deuterium and tungsten lamp can make lamps switching without optics debugging and easy to be replaced.
- Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
- Extensive accessories are optional, such as auto 8-cell holder, film holder, peltier/sipper system, 21 CFR compliant software, built-in thermal printer, etc.

Model	M4000	M4001	M4001S	M5000	M5001	M5001S
Optical System	Single Beam, Grating 1200 lines/mm			Double Beam, Grating 1200 lines/mm		
Wavelength Range	190-1100 nm					
Spectral Bandwidth	2nm	1nm	0.5/1/2/4/5	2nm	1nm	0.5/1/2/4/5
Wavelength Accuracy	±0.1nm@656.1nm, ±0.3nm@all					
Wavelength Repeatability	<=0.1nm					
Photometric Accuracy	0.2%T(0~100%T), ±0.002A(0-0.5A), ±0.004A(0.5-1A)					
Photometric Repeatability	≤0.15%T (0-100%T), 0.001A(0-0.5A), 0.002A(0.5-1A)					
Photometric Range	0-200%T, -0.3~3A, 0-9999C (0-9999F)					
Stray Light	<=0.03%T@220nm, 360nm					
Stability	±0.0005A/h@500nm			±0.0003A/h @500 nm		
Baseline Flatness	±0.0002A	±0.001A		±0.0002A	±0.001A	
Noise	0.0005A@500nm					
Work Mode	T, A, C, E					
Scanning Speed	Hi, Med, Low (Max. 3000nm/min)					
Wavelength Setting	Auto					
Display	No Screen					
Light Source	Imported Deuterium &Tungsten lamp					
Detector	Imported Silicon Photodiode					
Cuvette Holder	10mm manual 4-cell holder			10mm single hole cell holder		
Output	USB drive, USB host, RS232					
Power	AC 220V/50Hz or AC 110V/60Hz					
Shipping Size	810*660*390mm					880*690*520mm
Gross Weight	27kg					45kg
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2, Power cord, User's Manual , PC software					

K Series Touch Screen Spectrophotometer



- 10.1 inches high resolution TFT colored capacitive touch screen and windows graphic interface.
- Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, multi-wavelength test, etc
- In-house massive memory is capable of saving up to 1024M for test data & working curves.
- Supports USB & SD card storage. The USB port can be used for data transfer, which is easily exported to Excel for further processing, analysis and storage.
- Socket type deuterium and tungsten lamp can make lamps switching without optics debugging and easy to be replaced.
- Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
- Extensive accessories are optional, such as auto 8-cell holder, film holder, peltier/sipper system, 21 CFR compliant software, built-in thermal printer, etc.

Model	K7000	K7001	K7001S	K9000	K9001	K9001S
Optical System	Single Beam, Grating 1200 lines/mm			Double Beam, Grating 1200 lines/mm		
Wavelength Range	190-1100 nm					
Spectral Bandwidth	2nm	1nm	0.5/1/2/4/5	2nm	1nm	0.5/1/2/4/5
Wavelength Accuracy	±0.1nm@656.1nm, ±0.3nm@all					
Wavelength Repeatability	<=0.1nm					
Photometric Accuracy	0.2%T(0~100%T), ±0.002A(0-0.5A), ±0.004A(0.5-1A)					
Photometric Repeatability	≤0.15%T (0-100%T), 0.001A(0-0.5A), 0.002A(0.5-1A)					
Photometric Range	0-200%T, -0.3~3A, 0-9999C (0-9999F)					
Stray Light	<=0.03%T@220nm, 360nm					
Stability	±0.0005A/h@500nm			±0.0003A/h @500 nm		
Baseline Flatness	±0.002A	±0.001A		±0.002A	±0.001A	
Noise	0.0005A@500nm					
Work Mode	T, A, C, E					
Scanning Speed	Hi, Med, Low (Max. 3000nm/min)					
Wavelength Setting	Auto					
Display	10.1" TFT Colored Capacitive Touch Screen					
Light Source	Imported Deuterium &Tungsten lamp					
Detector	Imported Silicon Photodiode					
Cuvette Holder	10mm manual 4-cell holder			10mm single hole cell holder		
Output	USB drive, USB host, RS232					
Power	AC 220V/50Hz or AC 110V/60Hz					
Shipping Size	810*660*390mm					880*690*520mm
Gross Weight	27kg					45kg
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2, Power cord, User's Manual , PC software					

K Series Color Screen Spectrophotometer



Windows Graphic Interface

- 7 inches TFT color screen and windows graphic interface.
- Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, multi-wavelength test, etc
- In-house massive memory is capable of saving up to 1024M for test data & working curves.
- Supports USB storage. The USB port can be used for data transfer, which is easily exported to Excel for further processing, analysis and storage.
- Socket type deuterium and tungsten lamp can make lamps switching without optics debugging and easy to be replaced.
- Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
- Extensive accessories are optional, such as auto 8-cell holder, film holder, peltier/sipper system, 21 CFR compliant software, built-in thermal printer, etc.

Model	K6000	K6001	K6001S	K8000	K8001	K8001S
Optical System	Single Beam, Grating 1200 lines/mm			Double Beam, Grating 1200 lines/mm		
Wavelength Range	190-1100 nm					
Spectral Bandwidth	2nm	1nm	0.5/1/2/4/5	2nm	1nm	0.5/1/2/4/5
Wavelength Accuracy	±0.1nm@656.1nm, ±0.3nm@all					
Wavelength Repeatability	≤0.1nm					
Photometric Accuracy	0.2%T(0~100%T), ±0.002A(0-0.5A), ±0.004A(0.5-1A)					
Photometric Repeatability	≤0.15%T (0-100%T), 0.001A(0-0.5A), 0.002A(0.5-1A)					
Photometric Range	0-200%T, -0.3~3A, 0-9999C (0-9999F)					
Stray Light	≤0.03%T@220nm, 360nm					
Stability	±0.0005A/h@500nm			±0.0003A/h @500 nm		
Baseline Flatness	±0.002A	±0.001A		±0.002A	±0.001A	
Noise	0.0005A@500nm					
Work Mode	T, A, C, E					
Scanning Speed	Hi, Med, Low (Max. 3000nm/min)					
Wavelength Setting	Auto					
Display	7" TFT Color Screen					
Light Source	Imported Deuterium & Tungsten lamp					
Detector	Imported Silicon Photodiode					
Cuvette Holder	10mm manual 4-cell holder			10mm single hole cell holder		
Output	USB drive, USB host, RS232					
Power	AC 220V/50Hz or AC 110V/60Hz					
Shipping Size	810*660*390mm					880*690*520mm
Gross Weight	27kg					45kg
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2, Power cord, User's Manual , PC software					

U Series Touch Screen Spectrophotometer



- 8 inches high resolution capacitive color touch screen and windows graphic interface.
- Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, multi-wavelength test, etc
- In-house massive memory is capable of saving up to 1024M for test data & working curves.
- Supports USB & SD card storage. The USB port can be used for data transfer, which is easily exported to Excel for further processing, analysis and storage.
- Socket type deuterium and tungsten lamp can make lamps switching without optics debugging and easy to be replaced.
- Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
- Extensive accessories are optional, such as auto 8-cell holder, film holder, tube rack, peltier/sipper system, 21 CFR compliant software, etc.

Model	U3200	U3100	U3100S	U5200	U5100	U5100S
Optical System	Single Beam, Grating 1200 lines/mm			Double Beam, Grating 1200 lines/mm		
Wavelength Range	190-1100 nm					
Spectral Bandwidth	2nm	1nm	0.5/1/2/4/5	2nm	1nm	0.5/1/2/4/5
Wavelength Accuracy	±0.1nm@656.1nm, ±0.3nm@all					
Wavelength Repeatability	<=0.1nm					
Photometric Accuracy	0.2%T(0~100%T), ±0.002A(0-0.5A), ±0.004A(0.5-1A)					
Photometric Repeatability	≤0.15%T (0-100%T), 0.001A(0-0.5A), 0.002A(0.5-1A)					
Photometric Range	0-200%T, -0.3~3A, 0-9999C					
Stray Light	<=0.03%T@220nm, 360nm					
Stability	±0.0005A/h@500nm			±0.0003A/h @500 nm		
Baseline Flatness	±0.002A	±0.001A		±0.002A	±0.001A	
Noise	0.0005A@500nm					
Work Mode	T, A, C, E					
Scanning Speed	Hi, Med, Low (Max. 3000nm/min)					
Wavelength Setting	Auto					
Display	8" TFT Colored Capacitive Touch Screen					
Light Source	Imported Deuterium &Tungsten lamp					
Detector	Imported Silicon Photodiode					
Cuvette Holder	10mm manual 4-cell holder			10mm single hole cell holder		
Output	USB drive, USB host, RS232					
Power	AC 220V/50Hz or AC 110V/60Hz					
Shipping Size	810*660*390mm					880*690*520mm
Gross Weight	27kg					45kg
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2, Power cord, User's Manual , PC software					

N Series Color Screen Spectrophotometer



- 7 inches TFT color screen and windows graphic interface.
- Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, multi-wavelength test, etc
- In-house massive memory is capable of saving up to 1024M for test data & working curves.
- Supports USB storage. The USB port can be used for data transfer, which is easily exported to Excel for further processing, analysis and storage.
- Socket type deuterium and tungsten lamp can make lamps switching without optics debugging and easy to be replaced.
- Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
- Extensive accessories are optional, such as auto 8-cell holder, film holder, tube rack, peltier/sipper system, 21 CFR compliant software, etc.

Model	N5000	N5000Plus	N5000S	N6000	N6000Plus	N6000S
Optical System	Single Beam, Grating 1200 lines/mm			Double Beam, Grating 1200 lines/mm		
Wavelength Range	190-1100 nm					
Spectral Bandwidth	2nm	1nm	0.5/1/2/4/5	2nm	1nm	0.5/1/2/4/5
Wavelength Accuracy	±0.1nm@656.1nm, ±0.3nm@all					
Wavelength Repeatability	≤0.1nm					
Photometric Accuracy	0.2%T(0~100%T), ±0.002A(0-0.5A), ±0.004A(0.5-1A)					
Photometric Repeatability	≤0.15%T (0-100%T), 0.001A(0-0.5A), 0.002A(0.5-1A)					
Photometric Range	0-200%T, -0.3~3A, 0-9999C					
Stray Light	≤0.03%T@220nm, 360nm					
Stability	±0.0005A/h@500nm			±0.0003A/h @500 nm		
Baseline Flatness	±0.002A	±0.001A		±0.002A	±0.001A	
Noise	0.0005A@500nm					
Work Mode	T, A, C, E					
Scanning Speed	Hi, Med, Low (Max. 3000nm/min)					
Wavelength Setting	Auto					
Display	7" TFT Color Screen					
Light Source	Imported Deuterium & Tungsten lamp					
Detector	Imported Silicon Photodiode					
Cuvette Holder	10mm manual 4-cell holder			10mm single hole cell holder		
Output	USB drive, USB host, RS232					
Power	AC 220V/50Hz or AC 110V/60Hz					
Shipping Size	810*660*390mm					880*690*520mm
Gross Weight	27kg					45kg
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2, Power cord, User's Manual , PC software					

1900 series Double Beam Spectrophotometer



- Large 320*240 dots highlighted LCD.
- Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, multi-wavelength test, etc
- The real double beam metering system, with advanced circuit measurement and control system, make the instrument with high reliability and low noise.
- The USB port can be used for data transfer and storage.
- Socket type deuterium and tungsten lamp can make lamps switching without optics debugging and easy to be replaced.
- Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
- Extensive accessories are optional, such as auto 8-cell holder, film holder, tube rack, peltier/sipper system, 21 CFR compliant software, etc.

Model	UV1900	UV1901	UV1901S
Optical System	Double Beam, Grating 1200 lines/mm		
Wavelength Range	190-1100 nm		
Spectral Bandwidth	2nm	1 nm	0.5/1/2/4/5 nm
Wavelength Accuracy	±0.1nm@656.1nm, ±0.3nm@all		
Wavelength Repeatability	0.1nm		
Photometric Accuracy	±0.3%T(0~100%T)		
Photometric Repeatability	0.1%T(0~100%T)		
Photometric Range	0-200%T, -0.3~3A, 0-9999C		
Stray light	0.05%T@220nm,360nm		
Stability	±0.0003A/h @500 nm		
Baseline Flatness	±0.0002A	±0.001A	
Noise	0.0005A@500nm		
Work Mode	T, A, C, E		
Scanning Speed	Hi, Med, Low (Max. 3000nm/min)		
Wavelength Setting	Auto		
Display	320*240 LCD		
Light Source	Imported Deuterium &Tungsten lamp		
Detector	Imported Silicon Photodiode		
Cuvette Holder	10mm single hole cell holder		
Output	USB, RS232		
Power	AC 220V/50Hz or AC 110V/60Hz		
Shipping Size	810*660*390mm		880*690*520mm
Gross Weight	27kg		45kg
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2, Power cord, User's Manual , PC software		

1800 Series Single Beam Spectrophotometer



- Large 320*240 dots highlighted LCD.
- Powerful functions like Photometric measurement, Quantitative measurement, Kinetics, Spectrum scan, DNA\Protein test, multi-wavelength test, etc
- The newly designed excellent optical system and high performance holographic blazed grating ensure the low stray light of the instrument.
- The USB port can be used for data transfer and storage.
- Socket type deuterium and tungsten lamp can make lamps switching without optics debugging and easy to be replaced.
- Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
- Extensive accessories are optional, such as auto 8-cell holder, film holder, tube rack, peltier/sipper system, 21 CFR compliant software, etc.

Model	UV1800	UV1801	UV1801S	V1800
Optical System	Single Beam, Grating 1200 lines/mm			
Wavelength Range	190-1100 nm			320-1100nm
Spectral Bandwidth	2nm	1nm	0.5/1/2/4/5nm	2nm
Wavelength Accuracy	0.5nm	±0.1nm@656.1nm, ±0.3nm@all		
Wavelength Repeatability	0.2 nm	0.1nm		0.2 nm
Photometric Accuracy	±0.5%T	±0.3%T		±0.5%T
Photometric Repeatability	0.1%T(0~100%T)			
Photometric Range	0-200%T, -0.3~3A, 0-9999C			
Stray Light	0.05%T@220nm,360nm			
Stability	±0.0005A/h@500nm			
Baseline Flatness	±0.002 A			
Noise	±0.001 A			
Work Mode	T, A, C, E			
Scanning Speed	Hi, Med, Low (Max. 3000nm/min)			
Wavelength setting	Auto			
Display	320*240 LCD			
Light Source	Imported Deuterium & Tungsten lamp			Imported Tungsten lamp
Detector	Imported Silicon Photodiode			
Cuvette Holder	10mm manual 4-cell holder			
Output	USB, RS232			
Power	AC 220V/50Hz; AC 110V/60Hz			
Shipping Size	810*660*390mm			
Gross Weight	27kg			
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2 (UV) , Power cord, User's Manual , PC software			

1700 Series Single Beam Spectrophotometer



Features:

- Unique optical system, 1200 lines/mm grating and imported receiver to ensure its sound performance.
- The instrument has basic functions of photometric analysis and quantitative analysis. With PC software, it expands the applications, such as spectral scanning, kinetics, DNA/protein analysis, multi-wavelength test, etc. PC software included.
- Adopts 51 microcomputer system, and can store 200 test data and 100 standard curves.
- Socket type deuterium and tungsten lamp can make lamps switching without optics debugging and easy to be replaced.
- Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
- Extensive accessories are optional, such as 50/100mm manual 4-cell holder, auto 8-cell holder, film holder, 21 CFR compliant software, etc.

Model	UV1700	UV1710	UV1720	V1700	V1710
Optical System	Single Beam, Grating 1200 lines/mm				
Wavelength Range	190-1100nm			330-1100nm	340-1050nm
Spectral Bandwidth	2 nm				4nm
Wavelength Accuracy	±0.3 nm	±0.5 nm	1nm	±0.5 nm	1nm
Wavelength Repeatability	<=0.1 nm	<=0.2 nm		<=0.1 nm	<=0.2 nm
Photometric Accuracy	0.3%T	0.5%T		0.3%T	0.5%T
Photometric Repeatability	0.2%T				
Photometric Range	0-200%T, -0.3~3A, 0-9999C				
Stray light	0.05%T	0.1%T	0.15%T	0.05%T	0.15%T
Stability	±0.0001A/h @500nm	±0.0002A/h @500nm		±0.0001A/h @500nm	±0.0002A/h @500nm
Baseline Flatness	±0.002 A				
Noise	±0.001 A				
Work Mode	T, A, C, E				
Wavelength Setting	Auto				
Display	128*64 LCD				
Light Source	Imported Deuterium & Tungsten lamp			Imported Tungsten lamp	
Detector	Imported Silicon Photodiode				
Cuvette Holder	10mm manual 4-cell holder				
Output	USB, RS232				
Power	AC 220V/50Hz; AC 110V/60Hz				
Shipping Size	700*580*340mm				
Gross Weight	20kg				
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2 (UV) , Power cord, User's Manual , PC software				

1600 Series Single Beam Scanning Spectrophotometer



- Unique optical system, 1200 lines/mm grating and imported receiver to ensure its sound performance.
- The instrument has basic functions of photometric analysis and quantitative analysis. With PC software, it expands the applications, such as spectral scanning, kinetics, DNA/protein analysis, multi-wavelength test, etc. PC software is optional.
- Adopts 51 microcomputer system, and can store 200 test data and 100 standard curves;
- Socket type deuterium and tungsten lamp can make lamps switching without optics debugging and easy to be replaced.
- Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
- Extensive accessories are optional, such as 50/100mm manual 4-cell holder, auto 8-cell holder, film holder, PC software, 21 CFR compliant software, etc.

Model	UV1600	UV1610
Optical System	Single Beam, Grating 1200 lines/mm	
Wavelength Range	190-1100nm	
Spectral Bandwidth	2 nm	4 nm
Wavelength Accuracy	1nm	
Wavelength Repeatability	<=0.5nm	
Photometric Accuracy	0.5%T	
Photometric Repeatability	0.3%T	
Photometric Range	0-200%T, -0.3~3A, 0-9999C	
Stray light	0.3%T	
Stability	±0.002A/h @500nm	
Baseline Flatness	±0.002 A	
Noise	±0.001 A	
Work Mode	T, A, C, E	
Wavelength Setting	Auto	
Display	128*64 LCD	
Light Source	Deuterium & Tungsten lamp	
Detector	Silicon Photodiode	
Cuvette Holder	10mm manual 4-cell holder	
Output	USB, RS232	
Power	AC 220V/50Hz; AC 110V/60Hz	
Shipping Size	700*580*340mm	
Gross Weight	20kg	
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2 (UV) , Power cord, User's Manual	

2000 Series Single Beam Spectrophotometer



Features:

1. 128* 64mm dot matrix LCD can display wavelength. Minimum wavelength display 0.5 nm.
2. Can make test of Quantitative and Kinetics with professional PC software.
3. Adjust automatically 0%A and 100%T.
4. Store 200 measuring data and 50 standard curve.
5. Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
6. Automatic control of the switching of deuterium and tungsten lamp, automatic wavelength calibration, manual wavelength setting.
7. PC software is optional.

Specificaions:

Model	V2000	UV2000	UV2000Pro
Optical System	Single Beam, Grating 1200 lines/mm		
Wavelength Range	320-1100nm	190-1100nm	
Spectral Bandwidth	4nm		2nm
Wavelength Accuracy	2 nm	1.5nm	
Wavelength Repeatability	1nm		
Photometric Accuracy	0.5%T		
Photometric Repeatability	0.2%T		
Stray light	0.1%T @500nm		
Stability	0.002 A@500nm		
Wavelength Setting	Manual		
Work Mode	T, A, C		
Display	128* 64mm dot matrix LCD		
Light Source	Tungsten lamp	Deuterium & Tungsten lamp	
Detector	Silicon Photodiode		
Cuvette Holder	10mm manual 4-cell holder		
Output	USB, RS232		
Power	AC 220V/50Hz; AC 110V/60Hz		
Shipping Size	520*450*320mm		
Gross Weight	10kg		
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2 (UV) , Power cord, User's Manual		

1200 Series Basic Spectrophotometer



Features:

1. 70* 40mm blue-lit LCD can display T, A, C, K, B.
2. Can make test of Quantitative and Kinetics with professional PC software.
3. Adjust automatically 0%A and 100%T.
4. Store 50 groups of measuring data and 10 groups of K & B value.
5. Large sample chamber can accommodate 5-100mm cuvettes of all kinds.
6. Automatic control of the switching of deuterium and tungsten lamp, manual wavelength setting.
7. PC software is optional.

Specifikaions:

Model	V1200	UV1200	UV1200Pro
Optical System	Single Beam, Grating 1200 lines/mm		
Wavelength Range	320-1100nm	190-1100nm	
Spectral Bandwidth	4nm		2nm
Wavelength Accuracy	2 nm		
Wavelength Repeatability	1nm		
Photometric Accuracy	0.5%T		
Photometric Repeatability	0.2%T		
Stray light	0.15%T @500nm		
Stability	0.002 A@500nm		
Wavelength Setting	Manual		
Work Mode	T, A, C		
Display	70 * 40mm blue-lit LCD		
Light Source	Tungsten lamp	Deuterium & Tungsten lamp	
Detector	Silicon Photodiode		
Cuvette Holder	10mm manual 4-cell holder		
Output	USB, RS232		
Power	AC 220V/50Hz; AC 110V/60Hz		
Shipping Size	520*450*320mm		
Gross Weight	10kg		
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2 (UV) , Power cord, User's Manual		

1000 Series Basic Spectrophotometer



1000 series is a basic spectrophotometer, which is widely used in education in universities and colleges, food & beverage production and quality control, agricultural monitoring, etc. It is an ideal choice for routine analysis and gernal experiments. Measured values can be transferred to PC via RS232 port for further analysis. PC software is optional.

Specificaions:

Model	V1000(V721)	V1100(V722)	UV1100(UV752)
Optical System	Single Beam, Grating 1200 lines/mm		
Wavelength Range	340-1020 nm	330-1020 nm	195-1020 nm
Spectral Bandwidth	6 nm	5 nm	
Wavelength Accuracy	±3 nm	±2nm	
Wavelength Repeatability	1nm		
Photometric Accuracy	±1%T	±0.5%T	
Photometric Repeatability	0.5%T	0.2%T	
Stray light	0.5%T	0.3%T	
Stability	0.004A	0.002A	
Wavelength Setting	Manual		
Work Mode	T, A, C		
Display	4 LCD		
Light Source	Tungsten lamp		Deuterium &Tungsten lamp
Detector	Silicon Photodiode		
Cuvette Holder	10mm manual 4-cell holder		
Output	RS232		
Power	AC 220V/50Hz or AC 110V/60Hz		
Shipping Size	520*450*320mm		
Gross Weight	10kg		
Standard Accessories	10mm glass cuvette x 4, 10mm quartz cuvette x 2 (UV) , Power cord, User's Manual		

Accessories



Single hole film holder



Auto 8-cell holder



single hole cell holder-10mm



Manual 4-position film holder



Integrating Sphere



Manual 4-cell holder-100mm



Adjustable XY micro cell holder



Tube rack



Peltier/Sipper system

P9 Series pH/EC/DO Meter

· pH · mV · Cond. · Res · TDS · Sal · DO · Temp.



General Features:

- 5-inch LCD screen with 150° viewing angle for clear reading out of 5-meter.
- Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, automatic power-off and low voltage alarm, etc.
- Two USB interfaces for PC connection, battery charging, and data transfer.
- 3.5mm electrode interface makes it very easy for electrode connection.
- Auto recognition of different electrodes. The electrode with built-in chip can automatically stores and retrieve calibration data after connecting with meter.
- Can store 300 sets of data including readings, date and time.
- Rechargeable battery can last for 30 hours. Auto power off when no operation in 10 minutes.

Features:

● pH Mode:

- Auto recognition of 15 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.

● Conductivity Mode:

- Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5 μ S/cm ~ 200mS/cm.
- Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
- Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.

● DO Mode:

- It has functions of ATC, manual salinity compensation and manual pressure compensation.
- Polarographic DO electrode, short polarization time (3-5 minutes).

P911 pH Meter



1. 5-inch LCD screen with 150° viewing angle for clear reading out of 5-meter.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, automatic power-off and low voltage alarm, etc.
3. Two USB interfaces for PC connection, battery charging, and data transfer.
4. 3.5mm electrode interface makes it very easy for electrode connection.
5. Automatic recognition of different electrodes. The electrode with built-in chip can automatically stores and retrieve calibration data after connecting with meter.
6. Auto recognition of different electrodes. The electrode with built-in chip can automatically stores and retrieve calibration data after connecting with meter.
7. Can store 300 sets of data including readings, date and time.
8. Rechargeable battery can last for 30 hours. Auto power off when no operation in 10 minutes.
9. Auto recognition of 15 buffers with three kinds of options: European & USA, NIST and China. Support 1, 2, 3 point calibration

pH	Measuring range	(-2 ~ 19.999)pH
	Resolution	0.1/0.01pH
	Accuracy	±0.02 pH
	Input current	≤2×10 ⁻¹² A
	Input impedance	≥1×10 ¹² Ω
	Stability	±0.002 pH/3h
	Temp. compensation	(0 ~ 100)°C, auto/manual
mV	Measuring range	±1999.9mV
	Resolution	0.1mV
	Accuracy	±0.03% FS
Temp.	Measuring range	(-10 ~ 110)°C
	Resolution	0.1°C
	Accuracy	5 ~ 60°C: ±0.4°C Others: ±0.8°C
Other	Display	5-Inch white backlit LCD screen
	Data storage	300 sets
	Power	DC 5V/1A
	Output	Micro USB & Standard USB
	Ambient Temp.	5 ~ 45 °C
	Ambient Humidity	≤85%
	IP Grade	IP54
	Dimension/N.W.	190×130×15mm / 280g
	Shipping Size/G.W.	470×430×100mm / 2.5kg
Meter Kits	1) Electrode holder	
	2) pH combination electrode	
	3) Temperature probe.	
	4) pH buffer solution	
	5) Power adapter	
	6) manual	

P912 Conductivity Meter



1. 5-inch LCD screen with 150° viewing angle for clear reading out of 5-meter.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, automatic power-off and low voltage alarm, etc.
3. Two USB interfaces for PC connection, battery charging, and data transfer.
4. 3.5mm electrode interface makes it very easy for electrode connection.
5. Automatic recognition of different electrodes. The electrode with built-in chip can automatically stores and retrieve calibration data after connecting with meter.
6. Auto recognition of different electrodes. The electrode with built-in chip can automatically stores and retrieve calibration data after connecting with meter.
7. Can store 300 sets of data including readings, date and time.
8. Rechargeable battery can last for 30 hours. Auto power off when no operation in 10 minutes.
9. Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5 μ S/cm ~ 200mS/cm.
10. Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
11. Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.

Conductivity	Measuring range	Conductivity:
		(0.00~20.00) μ S/cm, (20.0~200.0) μ S/cm
		(200~2000) μ S/cm, (2.00~20.00)mS/cm
		(20.0~200.0)mS/cm,
		(200~2000)mS/cm (K=10)
		TDS: (0~100) g/L
		Salinity: (0 ~ 100)ppt
		Resistivity: (0 ~ 100)M Ω -cm
	Resolution	0.01/0.1/1 μ S/cm; 0.01/0.1mS/cm
Temperature	Accuracy	Meter: \pm 1.50% FS; Electrode: \pm 1.0% FS
	Temp. compensation	(0 ~ 50) $^{\circ}$ C , auto
	Electrode constant	0.1 / 1 / 10 cm ⁻¹
	Measuring range	(-10 ~ 110) $^{\circ}$ C
Other Technical Parameters	Resolution	0.1 $^{\circ}$ C
	Accuracy	5 ~ 60 $^{\circ}$ C : \pm 0.4 $^{\circ}$ C Others: \pm 0.8 $^{\circ}$ C
	Display	5-Inch white backlit LCD screen
	Data storage	300 sets
	Power	DC 5V/1A
	Output	Micro USB & Standard USB
	Ambient Temp.	5 ~ 45 $^{\circ}$ C
	Ambient Humidity	\leq 85%
	IP Grade	IP54
	Dimension/N.W.	190x130x15mm / 280g
	Shipping Size/G.W.	470x430x100mm /2.5kg
Meter Kits	1) Electrode holder	
	2) Cond. electrode (K=1)	
	3) temperature probe.	
	4) Power adapter	
	5) manual	

P913 pH/Conductivity Meter



1. 5-inch LCD screen with 150° viewing angle for clear reading out of 5-meter.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, automatic power-off and low voltage alarm, etc.
3. Two USB interfaces for PC connection, battery charging, and data transfer.
4. 3.5mm electrode interface makes it very easy for electrode connection.
5. Automatic recognition of different electrodes. The electrode with built-in chip can automatically stores and retrieve calibration data after connecting with meter.
6. Auto recognition of different electrodes. The electrode with built-in chip can automatically stores and retrieve calibration data after connecting with meter.
7. Can store 300 sets of data including readings, date and time.
8. Rechargeable battery can last for 30 hours. Auto power off when no operation in 10 minutes.
9. Auto recognition of 15 buffers with three kinds of options: European & USA, NIST and China. Support 1, 2, 3 point calibration
10. Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement
11. Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
12. Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.

pH	Measuring range	(-2 ~ 19.999)pH
	Resolution	0.1/0.01pH
	Accuracy	±0.02 pH
	Input current	≤2×10 ⁻¹² A
	Input impedance	≥1×10 ¹² Ω
	Stability	±0.002 pH/3h
	Temp. compensation	(0 ~ 100)°C, auto/manual
mV	Measuring range	±1999.9mV
	Resolution	0.1mV
	Accuracy	±0.03% FS
Conductivity	Measuring range	Conductivity:
		(0.00~20.00)μS/cm, (20.0~200.0)μS/cm
		(200~2000)μS/cm, (2.00~20.00)mS/cm
		(20.0~200.0)mS/cm,
		(200~2000)mS/cm (K=10)
		TDS: (0~100) g/L
		Salinity: (0 ~ 100)ppt
		Resistivity: (0 ~ 100)MΩ·cm
	Resolution	0.01/0.1/1μS/cm; 0.01/0.1mS/cm
	Accuracy	Meter: ±1.50% FS; Electrode: ±1.0% FS
	Temp. compensation	(0 ~ 50)°C, auto
	Electrode constant	0.1 / 1 / 10 cm ⁻¹
Temperature	Measuring range	(-10 ~ 110)°C
	Resolution	0.1°C
	Accuracy	5 ~ 60°C: ±0.4°C Others: ±0.8°C
Other Technical Parameters	Display	5-Inch white backlit LCD screen
	Data storage	300 sets
	Power	DC 5V/1A
	Output	Micro USB & Standard USB
	Ambient Temp.	5 ~ 45 °C
	Ambient Humidity	≤85%
	IP Grade	IP54
	Dimension/N.W.	190×130×15mm / 280g
	Shipping Size/G.W.	470x430x100mm /2.5kg
Meter Kits	1) Electrode holder	
	2) pH combination electrode	
	3) Cond. electrode (K=1)	
	4) Temperature probe.	
	5) pH buffer solution	
	6) Power adapter	
	7) manual	

P914 DO Meter



1. 5-inch LCD screen with 150° viewing angle for clear reading out of 5-meter.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, automatic power-off and low voltage alarm, etc.
- Two USB interfaces for PC connection, battery charging, and data transfer.
4. 3.5mm electrode interface makes it very easy for electrode connection.
5. Automatic recognition of different electrodes. The electrode with built-in chip can automatically stores and retrieve calibration data after connecting with meter.
6. Auto recognition of different electrodes. The electrode with built-in chip can automatically stores and retrieve calibration data after connecting with meter.
7. Can store 300 sets of data including readings, date and time.
8. Rechargeable battery can last for 30 hours. Auto power off when no operation in 10 minutes.
9. It has functions of ATC, manual salinity compensation and manual pressure compensation.
10. Polarographic DO electrode, short polarization time (3-5 minutes).

DO	Measuring range	(0.000 ~ 90)mg/L (ppm)
	Resolution	0.01/0.1
	Accuracy	(0 ~ 100) ppt
	Response time	≤30s (25℃, 90% response)
	Temp compensation	(0 ~ 50)℃ , auto
	Salinity compensation	(0.0 ~ 50.0)g/L, manual
	Pressure compensation	(80 ~ 105)kPa, manual
	Display parameters	Conc., Saturation, Temp.
	Electrode type	Polarographic
Temp.	Measuring range	(-10 ~ 110)℃
	Resolution	0.1℃
	Accuracy	5 ~ 60℃:±0.4℃ Others: ±0.8℃
Other	Display	5-Inch white backlit LCD screen
	Data storage	300 sets
	Power	DC 5V/1A
	Output	Micro USB & Standard USB
	Ambient Temp.	5 ~ 45 ℃
	Ambient Humidity	≤85%
	IP Grade	IP54
	Dimension/N.W.	190×130×15mm / 280g
	Shipping Size/G.W.	470x430x100mm /2.5kg
Meter Kits	1) Electrode holder	
	2)DO electrode	
	3) temperature probe.	
	4) DO filling solution	
	5) Membrane cap	
	6) Cathode polishing paper	
	7) Power adapter	
	8)manual	

P8 Series pH/EC/DO/Ion Meter

· pH · mV · ISE · Cond. · Res · TDS · Sal · DO · Temp.



General Features:

- 7-inch colored capacitive touch screen with high resolution (1024*600) and high sensitivity.
- Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
- It supports wireless bluetooth printing and PC connection. Real-time data transfer to mobile phone via bluetooth is optional.
- Smart electrode status display to ensure accurate use.
- Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.

Features:

• pH Mode:

- Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.

• Conductivity Mode:

- Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5μS/cm ~ 200mS/cm.

- Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.

- Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.

• DO Mode:

- It has functions of ATC, auto salinity compensation and auto pressure compensation.

- Polarographic DO electrode, short polarization time (3-5 minutes).

• ISE Mode:

- Can test electric potential, pH, pX, ORP, ion concentration and temperature.

- Can switch 6 kinds of concentration units: μg/L, mg/L, g/L, mol/L, mmol/L, PX.

- Auto recognition of buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3, 4, 5 point calibration.

Model	Description	Application
P811	pH meter	General laboratory pH meter, which can be used in most of the areas related to water quality analysis.
P812	Conductivity meter	Used to measure the conductivity value of conventional aqueous solutions, especially in education and scientific research.
P813	pH/Conductivity meter	Suitable for high-precision pH/conductivity measurement in scientific research, quality control, biotechnology, fine chemicals, etc.
P814	DO meter	Applicable to aquaculture, water source monitoring, sewage treatment and environmental monitoring, etc., also widely used in education and scientific research.
P815	pH/DO meter	Suitable for biotechnology, aquaculture, power plants and environmental protection industries, especially in education and research.
P816	Conductivity/DO meter	Widely used in biotechnology, aquaculture, power plants and environmental protection industries.
P817	pH/Conductivity/DO meter	Suitable for the fields of petroleum, chemical, pharmacy, power plants and environmental protection, also widely used in education and scientific research.
P818-F	Fluoride ion meter	Test and analysis of the fluoride in drinking water, surface water, sea water, living sewage and industrial wastewater and the fluorine ion in mineral, organic, and biological materials.
P818-Na	Sodium ion meter	Suitable for measurement of sodium ion and pH value in natural water, boiler water and industrial drainage, especially for the quality monitoring of high purity water in power plant.
P818-Cl	Chloride ion meter	Measure chloride ion and pH value in drinking water, food and sewage.
P818-Ca	Calcium ion meter	Test calcium ion and pH value of water solutions. Widely used in the analysis and research of water quality, biochemistry and biomedicine.
P818-Br	Bromide ion meter	Test bromide ion and pH value in drinking water, food and sewage.
P818-NO	Nitrate ion meter	Test nitrate ion and pH value in drinking water, food and sewage.
P818-K	Potassium ion meter	Measure potassium ion and pH value in drinking water, food and sewage.
P818-NH	Ammonia Ion Meter	Test ammonia & nitrogen and pH value in drinking water, food and sewage.
P818-Cu	Copper ion meter	Test copper ion and pH value in food, beverage, electroplating industry and sewage.
P818-I	Iodide ion meter	Test iodide ion and pH value in drinking water, food and sewage.

P811 Touch Screen pH Meter



1. 7-inch colored capacitive touch screen with high resolution (1024*600) and sensitivity.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
6. Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.

pH	Measuring range	(-1.999 ~ 19.999)pH
	Resolution	0.1/0.01/0.001 pH
	Accuracy	Electrode: ± 0.002 pH, Meter: ± 0.01 pH
	Auto calibration	1, 2, 3 point
	Buffer	Europe & USA, NIST, China standards
	Input current	$\leq 1 \times 10^{-12}$ A
	Input impedance	$\geq 3 \times 10^{12} \Omega$
	Stability	± 0.002 pH/3h
	Temp. compensation	(0 ~ 100) °C, auto or manual
mV	Measuring range	-1999.9mV ~ 0 ~ 1999.9mV
	Resolution	0.1 mV
	Accuracy	$\pm 0.03\%$ FS
Temp.	Range	(-10 ~ 110) °C
	Resolution	0.1 °C
	Accuracy	5 ~ 60 °C: ± 0.4 °C Others: ± 0.8 °C
Other	Display	7-inch colored capacitive touch screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	15 ~ 30 °C
	Ambient Humidity	$\leq 85\%$
	IP grade	IP54
	Dimensions/N.W.	215×170×37mm/600g
	Shipping Size/G.W.	470×430×72mm/3kg
Meter Kits	1) Electrode holder	
	2) pH combination electrode	
	3) temperature probe.	
	4) pH buffer solution	
	5) Power adapter	
	6) manual	

P812 Touch Screen Conductivity Meter



1. 7-inch colored capacitive touch screen with high resolution (1024*600) and sensitivity.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
6. Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5 μ S/cm ~ 200mS/cm.
7. Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
8. Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.

Cond.	Measuring range	Conductivity:
		(0.00~20.00) μ S/cm, (20.0~200.0) μ S/cm
		(200~2000) μ S/cm, (2.00~20.00)mS/cm
		(20.0~200.0)mS/cm,
		(200~2000)mS/cm (K=10)
		TDS:(0 ~ 100)g/L
		Salinity:(0 ~ 100)ppt
		Resistivity:(0 ~ 100)M Ω ·cm
	Resolution	0.01/0.1/1 μ S/cm; 0.01/0.1mS/cm
	Accuracy	Electrode: \pm 0.5% FS, Meter: \pm 0.8% FS
Temp.	Temp. compensation range	(0 ~ 50)°C, auto
	Electrode constant	0.1/0.5/1/5/10/50/100 cm ⁻¹
	Reference Temp.	25°C、20°C、18°C
Other	Range	(-10 ~ 110)°C
	Resolution	0.1°C
	Accuracy	5 ~ 60°C : \pm 0.4°C Others: \pm 0.8°C
	Display	7-inch colored capacitive touch screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	15 ~ 30 °C
	Ambient Humidity	\leq 85%
Meter Kits	IP grade	IP54
	Dimensions/N.W.	215×170×37mm/600g
	Shipping Size/G.W.	470x430x72mm/3kg
	1) Electrode holder	
	2) Cond electrode (K=1)	
	3) temperature probe.	
	4) Power adapter	
	5) manual	

P813 Touch Screen pH/Conductivity Meter



1. 7-inch colored capacitive touch screen with high resolution (1024*600) and sensitivity.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
6. Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.
7. Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5 μ S/cm ~ 200mS/cm.
8. Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
9. Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.

pH	Measuring range	(-1.999 ~ 19.999)pH
	Resolution	0.1/0.01/0.001 pH
	Accuracy	Electrode: ± 0.002 pH, Meter: ± 0.01 pH
	Auto calibration	1, 2, 3 point
	Buffer	Europe & USA, NIST, China standards
	Input current	$\leq 1 \times 10^{-12}$ A
	Input impedance	$\geq 3 \times 10^{12}$ Ω
	Stability	± 0.002 pH/3h
	Temp. compensation	(0 ~ 100) $^{\circ}$ C, auto or manual
mV	Measuring range	-1999.9mV ~ 0 ~ 1999.9mV
	Resolution	0.1 mV
	Accuracy	$\pm 0.03\%$ FS
Cond.	Measuring range	Conductivity:
		(0.00~20.00) μ S/cm, (20.0~200.0) μ S/cm
		(200~2000) μ S/cm, (2.00~20.00)mS/cm
		(20.0~200.0)mS/cm,
		(200~2000)mS/cm (K=10)
		TDS:(0 ~ 100)g/L
		Salinity:(0 ~ 100)ppt
		Resistivity:(0 ~ 100)M Ω ·cm
	Resolution	0.01/0.1/1 μ S/cm; 0.01/0.1mS/cm
	Accuracy	Electrode: $\pm 0.5\%$ FS, Meter: $\pm 0.8\%$ FS
	Temp. compensation range	(0 ~ 50) $^{\circ}$ C, auto
	Electrode constant	0.1/0.5/1/5/10/50/100 cm $^{-1}$
	Reference Temp.	25 $^{\circ}$ C、20 $^{\circ}$ C、18 $^{\circ}$ C
Temp.	Range	(-10 ~ 110) $^{\circ}$ C
	Resolution	0.1 $^{\circ}$ C
	Accuracy	5 ~ 60 $^{\circ}$ C: $\pm 0.4^{\circ}$ C Others: $\pm 0.8^{\circ}$ C
Other	Display	7-inch colored capacitive touch screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	15 ~ 30 $^{\circ}$ C
	Ambient Humidity	$\leq 85\%$
	IP grade	IP54
	Dimensions/N.W.	215x170x37mm/600g
	Shipping Size/G.W.	470x430x72mm/3kg
Meter Kits	1) Electrode holder	
	2) pH combination electrode	
	3) Cond electrode (K=1)	
	4) temperature probe.	
	5) pH buffer solution	
	6) Power adapter	
	7) manual	

P814 Touch Screen DO Meter



1. 7-inch colored capacitive touch screen with high resolution (1024*600) and sensitivity.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
6. It has functions of ATC, auto salinity compensation and auto pressure compensation.
7. Polarographic DO electrode, short polarization time (3-5 minutes).

DO	Measuring range	(0 ~ 20.00) mg/L(ppm) (0 ~ 200.0)%
	Resolution	0.1/0.01 mg/L(ppm) 1/0.1 %
	Accuracy	Electrode: ± 0.10 mg/L, Meter: ± 0.40 mg/L
	Response time	≤ 30 s (25°C, 90% response)
	Residual current	≤ 0.1 mg/L
	Temp compensation	(0 ~ 45)°C, auto
	Salinity compensation	(0 ~ 45) ppt, auto
	Pressure compensation	(80 ~ 105) kPa, auto
	Auto calibration	Air saturated by water; water saturated by air
	Electrode type	Polarographic
Temp.	Range	(-10 ~ 110)°C
	Resolution	0.1°C
	Accuracy	5 ~ 60°C: ± 0.4 °C Others: ± 0.8 °C
Other	Display	7-inch colored capacitive touch screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	15 ~ 30 °C
	Ambient Humidity	$\leq 85\%$
	IP grade	IP54
	Dimensions/N.W.	215×170×37mm/600g
	Shipping Size/G.W.	470×430×72mm/3kg
Meter Kits	1) Electrode holder	
	2) DO electrode	
	3) temperature probe.	
	4) DO filling solution	
	5) Membrane cap	
	6) Cathode polishing paper	
	7) Power adapter	
	8) manual	

P815 Touch Screen pH/DO Meter



1. 7-inch colored capacitive touch screen with high resolution (1024*600) and sensitivity.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
6. Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.
7. It has functions of ATC, auto salinity compensation and auto pressure compensation.
8. Polarographic DO electrode, short polarization time (3-5 minutes).

pH	Measuring range	(-1.999 ~ 19.999)pH
	Resolution	0.1/0.01/0.001 pH
	Accuracy	Electrode: ± 0.002 pH, Meter: ± 0.01 pH
	Auto calibration	1, 2, 3 point
	Buffer	Europe & USA, NIST, China standards
	Input current	$\leq 1 \times 10^{-12}$ A
	Input impedance	$\geq 3 \times 10^{12}$ Ω
	Stability	± 0.002 pH/3h
	Temp. compensation	(0 ~ 100)°C, auto or manual
mV	Measuring range	-1999.9mV ~ 0 ~ 1999.9mV
	Resolution	0.1 mV
	Accuracy	$\pm 0.03\%$ FS
DO	Measuring range	(0 ~ 20.00) mg/L(ppm) (0 ~ 200.0)%
	Resolution	0.1/0.01 mg/L(ppm) 1/0.1 %
	Accuracy	Electrode: ± 0.10 mg/L, Meter: ± 0.40 mg/L
	Response time	≤ 30 s (25°C, 90%response)
	Residual current	≤ 0.1 mg/L
	Temp compensation	(0 ~ 45)°C, auto
	Salinity compensation	(0 ~ 45) ppt, auto
	Pressure compensation	(80 ~ 105) kPa, auto
	Auto calibration	Air saturated by water; water saturated by air
Temp.	Electrode type	Polarographic
	Range	(-10 ~ 110)°C
	Resolution	0.1°C
Other	Accuracy	5 ~ 60°C: ± 0.4 °C Others: ± 0.8 °C
	Display	7-inch colored capacitive touch screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	15 ~ 30 °C
	Ambient Humidity	$\leq 85\%$
	IP grade	IP54
	Dimensions/N.W.	215×170×37mm/600g
Meter Kits	Shipping Size/G.W.	470x430x72mm/3kg
	1) Electrode holder	
	2) pH combination electrode	
	3) DO electrode	
	4) temperature probe.	
	5) pH buffer solution	
	6) DO filling solution	
	7) Membrane cap	
	8) Cathode polishing paper	
	9) Power adapter	
	10) manual	

P816 Touch Screen Conductivity/DO Meter



1. 7-inch colored capacitive touch screen with high resolution (1024*600) and sensitivity.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
6. Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of $0.5\mu\text{S}/\text{cm} \sim 200\text{mS}/\text{cm}$.
7. Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
8. Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.
9. It has functions of ATC, auto salinity compensation and auto pressure compensation.
10. Polarographic DO electrode, short polarization time (3-5 minutes).

Cond.	Measuring range	Conductivity:
		(0.00~20.00) $\mu\text{S}/\text{cm}$, (20.0~200.0) $\mu\text{S}/\text{cm}$
		(200~2000) $\mu\text{S}/\text{cm}$, (2.00~20.00)mS/cm
		(20.0~200.0)mS/cm,
		(200~2000)mS/cm (K=10)
		TDS:(0 ~ 100)g/L
		Salinity:(0 ~ 100)ppt
		Resistivity:(0 ~ 100)M Ω ·cm
	Resolution	0.01/0.1/1 $\mu\text{S}/\text{cm}$; 0.01/0.1mS/cm
	Accuracy	Electrode: $\pm 0.5\%$ FS, Meter: $\pm 0.8\%$ FS
DO	Temp. compensation range	(0 ~ 50) $^{\circ}\text{C}$, auto
	Electrode constant	0.1/0.5/1/5/10/50/100 cm^{-1}
	Reference Temp.	25 $^{\circ}\text{C}$ 、20 $^{\circ}\text{C}$ 、18 $^{\circ}\text{C}$
	Measuring range	(0 ~ 20.00) mg/L(ppm) (0 ~ 200.0)%
	Resolution	0.1/0.01 mg/L(ppm) 1/0.1 %
	Accuracy	Electrode: ± 0.10 mg/L, Meter: ± 0.40 mg/L
	Response time	$\leq 30\text{s}$ (25 $^{\circ}\text{C}$, 90%response)
	Residual current	≤ 0.1 mg/L
	Temp compensation	(0 ~ 45) $^{\circ}\text{C}$, auto
	Salinity compensation	(0 ~ 45) ppt, auto
Temp.	Pressure compensation	(80 ~ 105) kPa, auto
	Auto calibration	Air saturated by water; water saturated by air
	Electrode type	Polarographic
Other	Range	(-10 ~ 110) $^{\circ}\text{C}$
	Resolution	0.1 $^{\circ}\text{C}$
	Accuracy	5 ~ 60 $^{\circ}\text{C}$: $\pm 0.4^{\circ}\text{C}$ Others: $\pm 0.8^{\circ}\text{C}$
Other	Display	7-inch colored capacitive touch screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	15 ~ 30 $^{\circ}\text{C}$
	Ambient Humidity	$\leq 85\%$
	IP grade	IP54
	Dimensions/N.W.	215×170×37mm/600g
	Shipping Size/G.W.	470×430×72mm/3kg
Meter Kits	1) Electrode holder	
	2) Cond electrode (K=1)	
	3) DO electrode	
	4) temperature probe.	
	5) DO filling solution	
	6) Membrane cap	
	7) Cathode polishing paper	
	8) Power adapter	
	9) manual	

P817 Touch Screen pH/Conductivity & DO Meter



1. 7-inch colored capacitive touch screen with high resolution (1024*600) and sensitivity.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
6. Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.
7. Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5 μ S/cm ~ 200mS/cm.
8. Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
9. Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.
10. It has functions of ATC, auto salinity compensation and auto pressure compensation.
11. Polarographic DO electrode, short polarization time (3-5 minutes).

pH	Measuring range	(-1.999 ~ 19.999)pH
	Resolution	0.1/0.01/0.001 pH
	Accuracy	Electrode: ± 0.002 pH, Meter: ± 0.01 pH
	Auto calibration	1, 2, 3 point
	Buffer	Europe & USA, NIST, China standards
	Input current	$\leq 1 \times 10^{-12}$ A
	Input impedance	$\geq 3 \times 10^{12} \Omega$
	Stability	± 0.002 pH/3h
	Temp. compensation	(0 ~ 100) $^{\circ}$ C, auto or manual
mV	Measuring range	-1999.9mV ~ 0 ~ 1999.9mV
	Resolution	0.1 mV
	Accuracy	$\pm 0.03\%$ FS
Cond.	Measuring range	Conductivity:
		(0.00~20.00) μ S/cm, (20.0~200.0) μ S/cm
		(200~2000) μ S/cm, (2.00~20.00)mS/cm
		(20.0~200.0)mS/cm,
		(200~2000)mS/cm (K=10)
		TDS:(0 ~ 100)g/L
		Salinity:(0 ~ 100)ppt
		Resistivity:(0 ~ 100)M Ω -cm
	Resolution	0.01/0.1/1 μ S/cm; 0.01/0.1mS/cm
	Accuracy	Electrode: $\pm 0.5\%$ FS, Meter: $\pm 0.8\%$ FS
	Temp. compensation range	(0 ~ 50) $^{\circ}$ C, auto
	Electrode constant	0.1/0.5/1/5/10/50/100 cm $^{-1}$
	Reference Temp.	25 $^{\circ}$ C、20 $^{\circ}$ C、18 $^{\circ}$ C
DO	Measuring range	(0 ~ 20.00) mg/L(ppm) (0 ~ 200.0)%
	Resolution	0.1/0.01 mg/L(ppm) 1/0.1 %
	Accuracy	Electrode: ± 0.10 mg/L, Meter: ± 0.40 mg/L
	Response time	≤ 30 s (25 $^{\circ}$ C, 90%response)
	Residual current	≤ 0.1 mg/L
	Temp compensation	(0 ~ 45) $^{\circ}$ C, auto
	Salinity compensation	(0 ~ 45) ppt, auto
	Pressure compensation	(80 ~ 105) kPa, auto
	Auto calibration	Air saturated by water; water saturated by air
	Electrode type	Polarographic

Temp.	Range	(-10 ~ 110)℃
	Resolution	0.1℃
	Accuracy	5 ~ 60℃:±0.4℃ Others: ±0.8℃
Other	Display	7-inch colored capacitive touch screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	15 ~ 30 ℃
	Ambient Humidity	≤85%
	IP grade	IP54
	Dimensions/N.W.	215×170×37mm/600g
	Shipping Size/G.W.	470x430x72mm/3kg
Meter Kits	1) Electrode holder	
	2) pH composite electrode	
	3) Conductivity electrode	
	4) DO electrode	
	5) Temperature probe	
	6) pH buffer solution	
	7) DO filling solution	
	8) Membrane cap	
	9) Cathode polishing paper	
	10) Power adapter	
	11)manual	

P7 Series pH/EC/DO/Ion Meter

· pH · mV · ISE · Cond. · Res · TDS · Sal · DO · Temp.



General Features:

- 6.5-inch LED screen with concise and friendly-use interface.
- Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
- It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
- Smart electrode status display to ensure accurate use.
- Omron long lasting and light touch key can be used more than 100,000 times.
- Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.

Features:

● pH Mode:

- Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.

● Conductivity Mode:

- Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5μS/cm ~ 200mS/cm.
- Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
- Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.

● DO Mode:

- It has functions of ATC, auto salinity compensation and auto pressure compensation.
- Polarographic DO electrode, short polarization time (3-5 minutes).

● ISE Mode:

- Can test electric potential, pH, pX, ORP, ion concentration and temperature.
- Can switch 6 kinds of concentration units: μg/L, mg/L, g/L, mol/L, mmol/L, PX.
- Auto recognition of buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3, 4, 5 point calibration.

Model	Description	Application
P711	pH meter	General laboratory pH meter, which can be used in most of the areas related to water quality analysis.
P712	Conductivity meter	Used to measure the conductivity value of conventional aqueous solutions, especially in education and scientific research.
P713	pH/Conductivity meter	Suitable for high-precision pH/conductivity measurement in scientific research, quality control, biotechnology, fine chemicals, etc.
P714	DO meter	Applicable to aquaculture, water source monitoring, sewage treatment and environmental monitoring, etc., also widely used in education and scientific research.
P715	pH/DO meter	Suitable for biotechnology, aquaculture, power plants and environmental protection industries, especially in education and research.
P716	Conductivity/DO meter	Widely used in biotechnology, aquaculture, power plants and environmental protection industries.
P717	pH/Conductivity/DO meter	Suitable for the fields of petroleum, chemical, pharmacy, power plants and environmental protection, also widely used in education and scientific research.
P718-F	Fluoride ion meter	Test and analysis of the fluoride in drinking water, surface water, sea water, living sewage and industrial wastewater and the fluorine ion in mineral, organic, and biological materials.
P718-Na	Sodium ion meter	Suitable for measurement of sodium ion and pH value in natural water, boiler water and industrial drainage, especially for the quality monitoring of high purity water in power plant.
P718-Cl	Chloride ion meter	Measure chloride ion and pH value in drinking water, food and sewage.
P718-Ca	Calcium ion meter	Test calcium ion and pH value of water solutions. Widely used in the analysis and research of water quality, biochemistry and biomedicine.
P718-Br	Bromide ion meter	Test bromide ion and pH value in drinking water, food and sewage.
P718-NO	Nitrate ion meter	Test nitrate ion and pH value in drinking water, food and sewage.
P718-K	Potassium ion meter	Measure potassium ion and pH value in drinking water, food and sewage.
P718-NH	Ammonia Ion Meter	Test ammonia & nitrogen and pH value in drinking water, food and sewage.
P718-Cu	Copper ion meter	Test copper ion and pH value in food, beverage, electroplating industry and sewage.
P718-I	Iodide ion meter	Test iodide ion and pH value in drinking water, food and sewage.

P711 pH Meter



1. 6.5-inch LED screen with concise and friendly-use interface.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Omron long lasting and light touch key can be used more than 100,000 times.
6. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
7. Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.

pH	Measuring range	(-2.00 ~ 18.00)pH
	Resolution	0.01 pH
	Accuracy	Electrode:±0.01 pH, Meter:±0.02 pH
	Auto calibration	1, 2, 3 point
	Buffer	Europe & USA, NIST, China standards
	Input current	$\leq 2 \times 10^{-12}$ A
	Input impedance	$\geq 1 \times 10^{12}$ Ω
	Stability	±0.02 pH/3h
	Temp. compensation	(0 ~ 100)°C, auto or manual
mV ORP	Measuring range	±1999.9mV
	Resolution	0.1 mV
	Accuracy	±0.03% FS
Temp.	Measuring range	(0 ~ 100)°C
	Resolution	0.1°C
	Accuracy	5 ~ 60°C:±0.4°C Others: ±0.8°C
Other	Display	6.5-inch LED screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	5 ~ 35 °C
	Ambient Humidity	≤85%
	IP grade	IP54
	Dimensions/N.W.	215×170×37mm/600g
	Shipping Size/G.W.	470x430x72mm/3kg
Meter Kits	1) Electrode holder	
	2) pH combination electrode	
	3) temperature probe.	
	4) pH buffer solution	
	5) Power adapter	
	6) manual	

P712 Conductivity Meter



1. 6.5-inch LED screen with concise and friendly-use interface.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Omron long lasting and light touch key can be used more than 100,000 times.
6. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
7. Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5 μ S/cm ~ 200mS/cm.
8. Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
9. Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.

Cond.	Measuring range	Conductivity:
		(0.00~20.00) μ S/cm, (20.0~200.0) μ S/cm
		(200~2000) μ S/cm, (2.00~20.00)mS/cm
		(20.0~200.0)mS/cm,
		(200~2000)mS/cm (K=10)
		TDS:(0 ~ 100)g/L
		Salinity:(0 ~ 100)ppt
		Resistivity:(0 ~ 100)M Ω ·cm
	Resolution	0.01/0.1/1 μ S/cm; 0.01/0.1mS/cm
	Accuracy	Electrode: \pm 0.5% FS, Meter: \pm 0.8% FS
Temp.	Temp. compensation	(0 ~ 50) $^{\circ}$ C, auto
	Electrode constant	0.1 / 1 / 10 cm ⁻¹
	Reference Temp.	25 $^{\circ}$ C、20 $^{\circ}$ C、18 $^{\circ}$ C
Temp.	Measuring range	(0 ~ 100) $^{\circ}$ C
	Resolution	0.1 $^{\circ}$ C
	Accuracy	5 ~ 60 $^{\circ}$ C: \pm 0.4 $^{\circ}$ C Others: \pm 0.8 $^{\circ}$ C
Other	Display	6.5-inch LED screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	5 ~ 35 $^{\circ}$ C
	Ambient Humidity	\leq 85%
	IP grade	IP54
	Dimensions/N.W.	215×170×37mm/600g
	Shipping Size/G.W.	470×430×72mm/3kg
Meter Kits	1) Electrode holder	
	2) Cond electrode (K=1)	
	3) temperature probe.	
	4) Power adapter	
	5) manual	

P713 pH/Conductivity Meter



1. 6.5-inch LED screen with concise and friendly-use interface.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Omron long lasting and light touch key can be used more than 100,000 times.
6. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
7. Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.
8. Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of $0.5\mu\text{S}/\text{cm} \sim 200\text{mS}/\text{cm}$.
9. Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision
10. Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.

pH	Measuring range	(-2.00 ~ 18.00)pH
	Resolution	0.01 pH
	Accuracy	Electrode: ± 0.01 pH, Meter: ± 0.02 pH
	Auto calibration	1, 2, 3 point
	Buffer	Europe & USA, NIST, China standards
	Input current	$\leq 2 \times 10^{-12}$ A
	Input impedance	$\geq 1 \times 10^{12} \Omega$
	Stability	± 0.02 pH/3h
	Temp. compensation	(0 ~ 100)°C, auto or manual
mV ORP	Measuring range	± 1999.9 mV
	Resolution	0.1 mV
	Accuracy	$\pm 0.03\%$ FS
Cond.	Measuring range	Conductivity:
		(0.00~20.00) $\mu\text{S}/\text{cm}$, (20.0~200.0) $\mu\text{S}/\text{cm}$
		(200~2000) $\mu\text{S}/\text{cm}$, (2.00~20.00)mS/cm
		(20.0~200.0)mS/cm,
		(200~2000)mS/cm (K=10)
		TDS: (0 ~ 100)g/L
		Salinity: (0 ~ 100)ppt
		Resistivity: (0 ~ 100)M Ω ·cm
	Resolution	0.01/0.1/1 $\mu\text{S}/\text{cm}$; 0.01/0.1mS/cm
	Accuracy	Electrode: $\pm 0.5\%$ FS, Meter: $\pm 0.8\%$ FS
	Temp. compensation	(0 ~ 50)°C, auto
Temp.	Electrode constant	0.1 / 1 / 10 cm^{-1}
	Reference Temp.	25°C、20°C、18°C
	Measuring range	(0 ~ 100)°C
	Resolution	0.1°C
Other	Accuracy	5 ~ 60°C: $\pm 0.4^\circ\text{C}$ Others: $\pm 0.8^\circ\text{C}$
	Display	6.5-inch LED screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	5 ~ 35 °C
	Ambient Humidity	$\leq 85\%$
	IP grade	IP54
	Dimensions/N.W.	215×170×37mm/600g
Meter Kits	Shipping Size/G.W.	470x430x72mm/3kg
	1) Electrode holder	
	2) pH combination electrode	
	3) Cond electrode (K=1)	
	4) temperature probe.	
	5) pH buffer solution	
	6) Power adapter	
	7) manual	

P714 DO Meter



1. 6.5-inch LED screen with concise and friendly-use interface.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Omron long lasting and light touch key can be used more than 100,000 times.
6. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
7. It has functions of ATC, auto salinity compensation and auto pressure compensation.
8. Polarographic DO electrode, short polarization time (3-5 mintues).

DO	Measuring range	(0-20.00)mg/L(ppm), (0-200.0)%
	Resolution	0.1/0.01 mg/L(ppm), 1/0.1 %
	Accuracy	Electrode: ± 0.10 mg/L, Meter: ± 0.40 mg/L
	Response time	$\leq 30s$ (25°C, 90%response)
	Residual current	≤ 0.1 mg/L
	Temp compensation	(0 ~ 45)°C, auto
	Salinity compensation	(0 ~ 45) ppt, auto
	Pressure compensation	(80 ~ 105) kPa, auto
	Auto calibration	Air saturated by water, water saturated by air
	Electrode type	Polarographic
Temp.	Measuring range	(0 ~ 100)°C
	Resolution	0.1°C
	Accuracy	5 ~ 60°C: $\pm 0.4^\circ\text{C}$ Others: $\pm 0.8^\circ\text{C}$
Other	Display	6.5-inch LED screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	5 ~ 35 °C
	Ambient Humidity	$\leq 85\%$
	IP grade	IP54
	Dimensions/N.W.	215×170×37mm/600g
	Shipping Size/G.W.	470×430×72mm/3kg
Meter Kits	1) Electrode holder	
	2) DO electrode	
	3) temperature probe.	
	4) DO filling solution	
	5) Membrane cap	
	6) Cathode polishing paper	
	7) Power adapter	
	8) manual	

P715 pH/DO Meter



1. 6.5-inch LED screen with concise and friendly-use interface.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Omron long lasting and light touch key can be used more than 100,000 times.
6. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
7. Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.
8. It has functions of ATC, auto salinity compensation and auto pressure compensation.
9. Polarographic DO electrode, short polarization time (3-5 minutes).

pH	Measuring range	(-2.00 ~ 18.00)pH
	Resolution	0.01 pH
	Accuracy	Electrode:±0.01 pH, Meter:±0.02 pH
	Auto calibration	1, 2, 3 point
	Buffer	Europe & USA, NIST, China standards
	Input current	$\leq 2 \times 10^{-12}$ A
	Input impedance	$\geq 1 \times 10^{12}$ Ω
	Stability	±0.02 pH/3h
	Temp. compensation	(0 ~ 100)°C, auto or manual
mV ORP	Measuring range	±1999.9mV
	Resolution	0.1 mV
	Accuracy	±0.03% FS
DO	Measuring range	(0-20.00)mg/L(ppm), (0-200.0)%
	Resolution	0.1/0.01 mg/L(ppm), 1/0.1 %
	Accuracy	Electrode: ±0.10 mg/L, Meter: ±0.40 mg/L
	Response time	≤30s (25 °C, 90%response)
	Residual current	≤0.1 mg/L
	Temp compensation	(0 ~ 45)°C, auto
	Salinity compensation	(0 ~ 45) ppt, auto
	Pressure compensation	(80 ~ 105) kPa, auto
	Auto calibration	Air saturated by water, water saturated by air
Temp.	Electrode type	Polarographic
	Measuring range	(0 ~ 100)°C
	Resolution	0.1 °C
Other	Accuracy	5 ~ 60°C:±0.4 °C Others: ±0.8 °C
	Display	6.5-inch LED screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	5 ~ 35 °C
	Ambient Humidity	≤85%
	IP grade	IP54
	Dimensions/N.W.	215×170×37mm/600g
Meter Kits	Shipping Size/G.W.	470x430x72mm/3kg
	1) Electrode holder	
	2) pH combination electrode	
	3) DO electrode	
	4) temperature probe.	
	5) pH buffer solution	
	6) DO filling solution	
	7) Membrane cap	
	8) Cathode polishing paper	
	9) Power adapter	
	10) manual	

P716 Conductivity/DO Meter



1. 6.5-inch LED screen with concise and friendly-use interface.
2. Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
3. It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
4. Smart electrode status display to ensure accurate use.
5. Omron long lasting and light touch key can be used more than 100,000 times.
6. Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
7. Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5 μ S/cm ~ 200mS/cm.
8. Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
9. Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.
10. It has functions of ATC, auto salinity compensation and auto pressure compensation.
11. Polarographic DO electrode, short polarization time (3-5 minutes).

Cond.	Measuring range	Conductivity:
		(0.00~20.00) μ S/cm, (20.0~200.0) μ S/cm
		(200~2000) μ S/cm, (2.00~20.00)mS/cm
		(20.0~200.0)mS/cm,
		(200~2000)mS/cm (K=10)
		TDS:(0 ~ 100)g/L
		Salinity:(0 ~ 100)ppt
		Resistivity:(0 ~ 100)M Ω ·cm
	Resolution	0.01/0.1/1 μ S/cm; 0.01/0.1mS/cm
	Accuracy	Electrode: \pm 0.5% FS, Meter: \pm 0.8% FS
DO	Temp. compensation	(0 ~ 50) $^{\circ}$ C, auto
	Electrode constant	0.1 / 1 / 10 cm $^{-1}$
	Reference Temp.	25 $^{\circ}$ C、20 $^{\circ}$ C、18 $^{\circ}$ C
	Measuring range	(0-20.00)mg/L(ppm), (0-200.0)%
	Resolution	0.1/0.01 mg/L(ppm), 1/0.1 %
	Accuracy	Electrode: \pm 0.10 mg/L, Meter: \pm 0.40 mg/L
	Response time	\leq 30s (25 $^{\circ}$ C, 90%response)
	Residual current	\leq 0.1 mg/L
	Temp compensation	(0 ~ 45) $^{\circ}$ C, auto
	Salinity compensation	(0 ~ 45) ppt, auto
Temp.	Pressure compensation	(80 ~ 105) kPa, auto
	Auto calibration	Air saturated by water, water saturated by air
	Electrode type	Polarographic
Other	Measuring range	(0 ~ 100) $^{\circ}$ C
	Resolution	0.1 $^{\circ}$ C
	Accuracy	5 ~ 60 $^{\circ}$ C: \pm 0.4 $^{\circ}$ C Others: \pm 0.8 $^{\circ}$ C
Meter Kits	Display	6.5-inch LED screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	5 ~ 35 $^{\circ}$ C
	Ambient Humidity	\leq 85%
	IP grade	IP54
	Dimensions/N.W.	215 \times 170 \times 37mm/600g
	Shipping Size/G.W.	470 \times 430 \times 72mm/3kg
Meter Kits	1) Electrode holder	
	2) Cond electrode (K=1)	
	3) DO electrode	
	4) temperature probe.	
	5) DO filling solution	
	6) Membrane cap	
	7) Cathode polishing paper	
	8) Power adapter	
	9) manual	

P717 pH/Conductivity/DO Meter



- 6.5-inch LED screen with concise and friendly-use interface.
- Built-in microprocessor chip has Intelligent functions such as automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis information, etc.
- It supports wireless bluetooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
- Smart electrode status display to ensure accurate use.
- Omron long lasting and light touch key can be used more than 100,000 times.
- Can store 1000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.
- Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.
- Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5 μ S/cm ~ 200mS/cm.
- Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
- Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.
- It has functions of ATC, auto salinity compensation and auto pressure compensation.
- Polarographic DO electrode, short polarization time (3-5 minutes).

pH	Measuring range	(-2.00 ~ 18.00)pH
	Resolution	0.01 pH
	Accuracy	Electrode:±0.01 pH, Meter:±0.02 pH
	Auto calibration	1, 2, 3 point
	Buffer	Europe & USA, NIST, China standards
	Input current	≤2×10 ⁻¹² A
	Input impedance	≥1×10 ¹² Ω
	Stability	±0.02 pH/3h
	Temp. compensation	(0 ~ 100)°C, auto or manual
mV ORP	Measuring range	±1999.9mV
	Resolution	0.1 mV
	Accuracy	±0.03% FS
Cond.	Measuring range	Conductivity: (0.00~20.00) μ S/cm, (20.0~200.0) μ S/cm (200~2000) μ S/cm, (2.00~20.00)mS/cm (20.0~200.0)mS/cm, (200~2000)mS/cm (K=10) TDS:(0 ~ 100)g/L Salinity:(0 ~ 100)ppt Resistivity:(0 ~ 100)MΩ·cm
	Resolution	0.01/0.1/1 μ S/cm; 0.01/0.1mS/cm
	Accuracy	Electrode: ±0.5% FS, Meter: ±0.8% FS
	Temp. compensation	(0 ~ 50)°C, auto
	Electrode constant	0.1 / 1 / 10 cm ⁻¹
	Reference Temp.	25°C、20°C、18°C
DO	Measuring range	(0-20.00)mg/L(ppm), (0-200.0)%
	Resolution	0.1/0.01 mg/L(ppm), 1/0.1 %
	Accuracy	Electrode: ±0.10 mg/L, Meter: ±0.40 mg/L
	Response time	≤30s (25°C, 90%response)
	Residual current	≤0.1 mg/L
	Temp compensation	(0 ~ 45)°C, auto
	Salinity compensation	(0 ~ 45) ppt, auto
	Pressure compensation	(80 ~ 105) kPa, auto
	Auto calibration	Air saturated by water, water saturated by air
	Electrode type	Polarographic
Temp.	Measuring range	(0 ~ 100)°C
	Resolution	0.1°C
	Accuracy	5 ~ 60°C:±0.4°C Others: ±0.8°C
Other	Display	6.5-inch LED screen
	Data storage	1000 sets
	Power	12V/1A
	Output	USB, Bluetooth
	Ambient Temp.	5 ~ 35 °C
	Ambient Humidity	≤85%
	IP grade	IP54
	Dimensions/N.W.	215×170×37mm/600g
	Shipping Size/G.W.	470×430×72mm/3kg
Meter Kits	1) Electrode holder	
	2) pH composite electrode	
	3) Conductivity electrode	
	4) DO electrode	
	5) Temperature probe	
	6) pH buffer solution	
	7) DO filling solution	
	8) Membrane cap	
	9) Cathode polishing paper	
	10) Power adapter	
	11) manual	

P6 Series pH/EC/DO/Ion Meter

· pH · mV · ISE · Cond. · Res · TDS · Sal · DO · Temp.

General Features:



- Large LCD screen with controllable white backlight.
- Built-in microprocessor chip has Intelligent functions such as auto calibration, ATC, data storage, function settings, auto diagnosis, auto power off, and undervoltage prompt, etc.

Features:

• pH Mode:

- Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.

• Conductivity Mode:

- Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5μS/cm ~ 200mS/cm.
- Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
- Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.

• DO Mode:

- It has functions of ATC, auto salinity compensation and manual pressure compensation.
- Polarographic DO electrode, short polarization time (3-5 minutes).

• ISE Mode:

- Can test electric potential, pH, pX, ORP, ion concentration and temperature.
- Can switch 6 kinds of concentration units: μg/L, mg/L, g/L, mol/L, mmol/L, PX.
- Auto recognition of buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3, 4, 5 point calibration.

Model	Description	Application
P611	pH meter	General laboratory pH meter, which can be used in most of the areas related to water quality analysis.
P612	Conductivity meter	Used to measure the conductivity value of conventional aqueous solutions, especially in education and scientific research.
P613	pH/Conductivity meter	Suitable for high-precision pH/conductivity measurement in scientific research, quality control, biotechnology, fine chemicals, etc.
P614	DO meter	Applicable to aquaculture, water source monitoring, sewage treatment and environmental monitoring, etc., also widely used in education and scientific research.
P615	pH/DO meter	Suitable for biotechnology, aquaculture, power plants and environmental protection industries, especially in education and research.
P616	Conductivity/DO meter	Widely used in biotechnology, aquaculture, power plants and environmental protection industries.
P618-F	Fluoride ion meter	Test and analysis of the fluoride in drinking water, surface water, sea water, living sewage and industrial wastewater and the fluorine ion in mineral, organic, and biological materials.
P618-Na	Sodium ion meter	Suitable for measurement of sodium ion and pH value in natural water, boiler water and industrial drainage, especially for the quality monitoring of high purity water in power plant.
P618-Cl	Chloride ion meter	Measure chloride ion and pH value in drinking water, food and sewage.
P618-Ca	Calcium ion meter	Test calcium ion and pH value of water solutions. Widely used in the analysis and research of water quality, biochemistry and biomedicine.
P618-Br	Bromide ion meter	Test bromide ion and pH value in drinking water, food and sewage.
P618-NO	Nitrate ion meter	Test nitrate ion and pH value in drinking water, food and sewage.
P618-K	Potassium ion meter	Measure potassium ion and pH value in drinking water, food and sewage.
P618-NH	Ammonia Ion Meter	Test ammonia & nitrogen and pH value in drinking water, food and sewage.
P618-Cu	Copper ion meter	Test copper ion and pH value in food, beverage, electroplating industry and sewage.
P618-I	Iodide ion meter	Test iodide ion and pH value in drinking water, food and sewage.

P611 pH Meter



1. Large LCD screen with controllable white backlight.
2. Built-in microprocessor chip has Intelligent functions such as auto calibration, ATC, data storage, function settings, auto diagnosis, auto power off, and undervoltage prompt, etc.
3. Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.

pH	Measuring range	(-2.00~19.99)pH
	Resolution	0.1/0.01 pH
	Accuracy	Meter:±0.01pH; Overall: ±0.02pH
	Input impedance	$\geq 1 \times 10^{12} \Omega$
	Stability	±0.01 pH/3h
	Temp. compensation	(0~100)°C (Auto/manual)
mV	Measuring range	±1999.9mV
	Resolution	1mV
	Accuracy	±0.1% FS
Temp.	Measuring range	(0 ~ 100)°C
	Resolution	0.1 °C
	Accuracy	5 ~ 60°C:±0.4°C Others: ±0.8°C
Other	Data storage	200 sets
	Power	Two AA batteries (1.5V x2)
	Ambient Temp.	5 ~ 35 °C
	Ambient humidity	≤85%
	IP grade	IP57 Dustproof and waterproof
	Dimensions/N.W.	(65×120×31)mm/180g
	Shipping size/G.W.	(460×300×55)mm/1Kg
Meter Kits	1) pH meter	
	2) pH composite electrode	
	3) Temperature electrode	
	4) pH buffer solution	
	5) Backup AA battery	
	6) manual	

P612 Conductivity Meter



1. Large LCD screen with controllable white backlight.
2. Built-in microprocessor chip has Intelligent functions such as auto calibration, ATC, data storage, function settings, auto diagnosis, auto power off, and undervoltage prompt, etc.
3. Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5 μ S/cm ~ 200mS/cm.
4. Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
5. Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.

Cond.	Measuring range	Conductivity:
		(0.00~19.99) μ S/cm
		(20.0~199.9) μ S/cm
		(200~1999)S/cm
		(2.00~19.99)mS/cm
		(20.0~199.9)mS/cm
		TDS:(0~100)g/L
		Salinity:(0~100)ppt
		Resistivity:(0~100)M Ω ·cm
	Resolution	0.01/0.1/1 μ S/cm; 0.01/0.1 mS/cm
Temp.	Accuracy	$\pm 1.0\%$ FS, Overall: $\pm 1.5\%$ FS
	Temp. compensation	(0~100) $^{\circ}$ C (Auto/manual)
	Electrode constant	0.1 / 1 / 10 cm ⁻¹
	Measuring range	(0 ~ 100) $^{\circ}$ C
Other	Resolution	0.1 $^{\circ}$ C
	Accuracy	5 ~ 60 $^{\circ}$ C : $\pm 0.4^{\circ}$ C Others: $\pm 0.8^{\circ}$ C
	Data storage	200 sets
	Power	Two AA batteries (1.5V x2)
	Ambient Temp.	5 ~ 35 $^{\circ}$ C
	Ambient humidity	$\leq 85\%$
	IP grade	IP57 Dustproof and waterproof
Meter Kits	Dimensions/N.W.	(65 \times 120 \times 31)mm/180g
	Shipping size/G.W.	(460 \times 300 \times 55)mm/1Kg
	1) Electrode holder	
	2) Cond electrode (K=1)	
	3) temperature probe.	
	4) Backup AA battery	
	5) manual	

P613 pH/Conductivity Meter



1. Large LCD screen with controllable white backlight.
2. Built-in microprocessor chip has Intelligent functions such as auto calibration, ATC, data storage, function settings, auto diagnosis, auto power off, and undervoltage prompt, etc.
3. Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.
4. Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5 μ S/cm ~ 200mS/cm.
5. Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
6. Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.

pH	Measuring range	(-2.00~19.99)pH
	Resolution	0.1/0.01 pH
	Accuracy	Meter: ± 0.01 pH; Overall: ± 0.02 pH
	Input impedance	$\geq 1 \times 10^{12} \Omega$
	Stability	± 0.01 pH/3h
	Temp. compensation	(0~100) $^{\circ}$ C (Auto/manual)
mV	Measuring range	± 1999.9 mV
	Resolution	1mV
	Accuracy	$\pm 0.1\%$ FS
Cond.	Measuring range	Conductivity:
		(0.00~19.99) μ S/cm
		(20.0~199.9) μ S/cm
		(200~1999)S/cm
		(2.00~19.99)mS/cm
		(20.0~199.9)mS/cm
		TDS: (0~100)g/L
		Salinity: (0~100)ppt
		Resistivity: (0~100)M Ω ·cm
	Resolution	0.01/0.1/1 μ S/cm; 0.01/0.1 mS/cm
	Accuracy	$\pm 1.0\%$ FS, Overall: $\pm 1.5\%$ FS
	Temp. compensation	(0~100) $^{\circ}$ C (Auto/manual)
	Electrode constant	0.1 / 1 / 10 cm ⁻¹
Temp.	Measuring range	(0 ~ 100) $^{\circ}$ C
	Resolution	0.1 $^{\circ}$ C
	Accuracy	5 ~ 60 $^{\circ}$ C: $\pm 0.4^{\circ}$ C Others: $\pm 0.8^{\circ}$ C
Other	Data storage	200 sets
	Power	Two AA batteries (1.5V x2)
	Ambient Temp.	5 ~ 35 $^{\circ}$ C
	Ambient humidity	$\leq 85\%$
	IP grade	IP57 Dustproof and waterproof
	Dimensions/N.W.	(65 \times 120 \times 31)mm/180g
	Shipping size/G.W.	(460 \times 300 \times 55)mm/1Kg
Meter Kits	1) Electrode holder	
	2) pH combination electrode	
	3) Cond electrode (K=1)	
	4) temperature probe.	
	5) pH buffer solution	
	6) Backup AA battery	
	7) manual	

P614 DO Meter



1. Large LCD screen with controllable white backlight.
2. Built-in microprocessor chip has Intelligent functions such as auto calibration, ATC, data storage, function settings, auto diagnosis, auto power off, and undervoltage prompt, etc.
3. It has functions of ATC, auto salinity compensation and manual pressure compensation.
4. Polarographic DO electrode, short polarization time (3-5 minutes).

DO	Measuring range	(0 ~ 20.00) mg/L(ppm), (0 ~ 200.0)%
	Resolution	0.1/0.01 mg/L(ppm), 1/0.1 %
	Accuracy	Electrode: ± 0.10 mg/L, Instrument: ± 0.40 mg/L
	Response time	$\leq 30s$ (25°C, 90% response)
	Residual current	≤ 0.1 mg/L
	Temp. compensation	(0 ~ 45)°C (auto)
	Salinity compensation	(0 ~ 45) ppt (auto)
	Pressure compensation	(66 ~ 200) kPa (manual)
	Auto calibration	Air saturated by water, water saturated by air
	Electrode type	Polarographic
Temp.	Measuring range	(0 ~ 100)°C
	Resolution	0.1°C
	Accuracy	5 ~ 60°C: ± 0.4 °C Others: ± 0.8 °C
Other	Data storage	200 sets
	Power	Two AA batteries (1.5V x2)
	Ambient Temp.	5 ~ 35 °C
	Ambient humidity	$\leq 85\%$
	IP grade	IP57 Dustproof and waterproof
	Dimensions/N.W.	(65×120×31)mm/180g
	Shipping size/G.W.	(460×300×55)mm/1Kg
Meter Kits	1) Electrode holder	
	2) DO electrode	
	3) temperature probe.	
	4) DO filling solution	
	5) Membrane cap	
	6) Cathode polishing paper	
	7) Backup AA battery	
	8) manual	

P615 pH/DO Meter



1. Large LCD screen with controllable white backlight.
2. Built-in microprocessor chip has Intelligent functions such as auto calibration, ATC, data storage, function settings, auto diagnosis, auto power off, and undervoltage prompt, etc.
3. Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST and China. Support 1, 2, 3 point calibration.
4. It has functions of ATC, auto salinity compensation and manual pressure compensation.
5. Polarographic DO electrode, short polarization time (3-5 minutes).

pH	Measuring range	(-2.00~19.99)pH
	Resolution	0.1/0.01 pH
	Accuracy	Meter:±0.01pH; Overall: ±0.02pH
	Input impedance	≥1×10 ¹² Ω
	Stability	±0.01 pH/3h
	Temp. compensation	(0~100)°C (Auto/manual)
mV	Measuring range	±1999.9mV
	Resolution	1mV
	Accuracy	±0.1% FS
DO	Measuring range	(0 ~ 20.00) mg/L(ppm), (0 ~ 200.0)%
	Resolution	0.1/0.01 mg/L(ppm), 1/0.1 %
	Accuracy	Electrode: ±0.10 mg/L, Instrument: ±0.40 mg/L
	Response time	≤30s (25 °C, 90%response)
	Residual current	≤0.1 mg/L
	Temp. compensation	(0 ~ 45) °C (auto)
	Salinity compensation	(0 ~ 45) ppt (auto)
	Pressure compensation	(66 ~ 200) kPa (manual)
	Auto calibration	Air saturated by water, water saturated by air
	Electrode type	Polarographic
Temp.	Measuring range	(0 ~ 100) °C
	Resolution	0.1 °C
	Accuracy	5 ~ 60 °C:±0.4 °C Others: ±0.8 °C
Other	Data storage	200 sets
	Power	Two AA batteries (1.5V x2)
	Ambient Temp.	5 ~ 35 °C
	Ambient humidity	≤85%
	IP grade	IP57 Dustproof and waterproof
	Dimensions/N.W.	(65×120×31)mm/180g
	Shipping size/G.W.	(460×300×55)mm/1Kg
Meter Kits	1) Electrode holder	
	2) pH combination electrode	
	3) DO electrode	
	4) temperature probe.	
	5) pH buffer solution	
	6) DO filling solution	
	7) Membrane cap	
	8) Cathode polishing paper	
	9) Backup AA battery	
	10) manual	

P616 Conductivity/DO Meter



1. Large LCD screen with controllable white backlight.
2. Built-in microprocessor chip has Intelligent functions such as auto calibration, ATC, data storage, function settings, auto diagnosis, auto power off, and undervoltage prompt, etc.
3. Adopt advanced conductivity measurement technology, with conductivity electrode (K=1), it can meet measuring accuracy requirement for range of 0.5 μ S/cm ~ 200mS/cm.
4. Can switch among conductivity, TDS, salinity and resistivity. Multinomial calculation for TDS and salinity to ensure the conversion precision of the full scale.
5. Auto recognition of 8 conductivity standard solution with 2 kinds of options: Europe & USA, and China.
6. It has functions of ATC, auto salinity compensation and manual pressure compensation.
- 7 Polarographic DO electrode, short polarization time (3-5 mintues).

Cond.	Measuring range	Conductivity:
		(0.00~19.99) μ S/cm
		(20.0~199.9) μ S/cm
		(200~1999)S/cm
		(2.00~19.99)mS/cm
		(20.0~199.9)mS/cm
		TDS:(0~100)g/L
		Salinity:(0~100)ppt
		Resistivity:(0~100)M Ω ·cm
	Resolution	0.01/0.1/ 1μ S/cm; 0.01/0.1 mS/cm
DO	Accuracy	$\pm 1.0\%$ FS, Overall: $\pm 1.5\%$ FS
	Temp. compensation	(0~100) $^{\circ}$ C (Auto/manual)
	Electrode constant	0.1 / 1 / 10 cm $^{-1}$
	Measuring range	(0 ~ 20.00) mg/L(ppm), (0 ~ 200.0)%
	Resolution	0.1/0.01 mg/L(ppm), 1/0.1 %
	Accuracy	Electrode: ± 0.10 mg/L, Instrument: ± 0.40 mg/L
	Response time	≤ 30 s (25 $^{\circ}$ C, 90%response)
	Residual current	≤ 0.1 mg/L
	Temp. compensation	(0 ~ 45) $^{\circ}$ C (auto)
	Salinity compensation	(0 ~ 45) ppt (auto)
Temp.	Pressure compensation	(66 ~ 200) kPa (manual)
	Auto calibration	Air saturated by water, water saturated by air
	Electrode type	Polarographic
	Measuring range	(0 ~ 100) $^{\circ}$ C
Other	Resolution	0.1 $^{\circ}$ C
	Accuracy	5 ~ 60 $^{\circ}$ C: $\pm 0.4^{\circ}$ C Others: $\pm 0.8^{\circ}$ C
	Data storage	200 sets
	Power	Two AA batteries (1.5V x2)
	Ambient Temp.	5 ~ 35 $^{\circ}$ C
	Ambient humidity	$\leq 85\%$
	IP grade	IP57 Dustproof and waterproof
	Dimensions/N.W.	(65 \times 120 \times 31)mm/180g
Meter Kits	Shipping size/G.W.	(460 \times 300 \times 55)mm/1Kg
	1) Electrode holder	
	2) Cond electrode (K=1)	
	3) DO electrode	
	4) temperature probe.	
	5) DO filling solution	
	6) Membrane cap	
	7) Cathode polishing paper	
	8) Power adapter	
	9) manual	

PHS-3C Benchtop pH Meter



Features:

1. 1/2LED display.
2. It has the function of manual temperature compensation, 1 or 2 point calibration.
3. It is equipped with pH combined electrode and buffer.

Specifications:

1. Measuring range
pH: (0.00~14.00)pH
mV: (-1999 ~1999)mV
2. Resolution
pH: 0.01pH
mV: 1mV
3. Basic Error
pH: $\pm 0.01\text{pH} \pm 1 \text{ bit}$
mV: $\pm 1\text{mV} \pm 1 \text{ bit}$
4. Input impedance: $\geq 1 \times 10^{12} \Omega$
5. Stability: $\pm 0.01 \text{ pH/3h}$
6. Range of temperature compensation: (0.0~60.0) $^{\circ}\text{C}$ Manual
7. Power supply: 220V/110V
8. Dimension: 320×220×90mm
9. Net Weight: 1.5kg
10. Shipping Size: 330x260x280mm/2kg

Included Accessories:

1. E-201-9 Combined Electrode
2. Multi-function Electrode Holder
3. Fuse BGXP $\Phi 5 \times 20$ 0.5A
4. Buffer Solution
5. Universal Adapter

DDS-11A Benchtop Conductivity Meter



Features:

1. With 3 1/2 LED, display is clear and precision is high.
2. Electrode constant compensation.
3. Manual temperature compensation.
4. It is equipped with DJS-1C platinum black probe.

Specifications:

1.Measuring range: The measuring range is (0~2×10⁵) uS/cm. The instrument has five ranges and can be changed through band switch by manual (by electrode with constant).

Range	Measuring range	Resolution
2 uS/cm	0.001~2 uS/cm	0.001 uS/cm
20 uS/cm	0.01~20 uS/cm	0.01uS/cm
200 uS/cm	0.1~200 uS/cm	0.1uS/cm
2 mS/cm	0.001~2.mS/cm	0.001mS/cm
20 mS/cm	0.01~20 mS/cm	0.01mS/cm

NOTE: To measure high conductivity, a larger constant electrode is commonly used. If the conductivity is over 10000 uS/cm, the electrode with constant of 10 cm⁻¹ is used and the measuring range is extended to 2×10⁵ uS/cm.

2. Accuracy of the electronic unit : ±1.0%(FS) ±1bit
- 3.Accuracy of the meter: ±1.5%(FS) ±1bit
4. Range of Temperature compensation: 5-35℃
- 5.Normal operation conditions:
 - (1) Ambient temperature: (5-35)℃
 - (2) Relative humidity: not more than 85%
 - (3) Power source: 220V/110V
 - (4) Without any notable vibration.
 - (5)No strong electromagnetic interference to surrounding except the geomagnetic field.

Included Accessories:

- 1.DJS-1C Platinum-black Probe
- 2.Multi-function Electrode Holder
3. Fuse BGXP Φ5*20 0.5A
- 4.Universal Adapter

PHS-3E Benchtop pH Meter



Features:

1. Large screen, LCD display, dual parameter.
2. Automatic buffer recognition and 2-point calibration.
3. Manual and auto temperature compensation.
4. Simultaneous measurement or display of pH value, temperature and mV(ORP).
5. It is equipped with pH combined electrode, temperature sensor and buffer.

Specifications:

Specifications:

Accuracy: 0.01

1. Measuring range

pH: -2 ~ 18.00pH

mV: (-1999 ~ 1999) mV

Temperature: (0 ~ 99.9)°C Auto/manual

2. Resolution

pH: 0.01pH

mV: 1mV

Temperature: 0.1°C

3. Basic Error

pH: $\pm 0.01\text{pH} \pm 1 \text{ bit}$

mV: $\pm 0.1\% \text{ FS}$

Temperature: $\pm 0.3^\circ\text{C} \pm 1 \text{ bit}$

4. Input impedance: $\geq 1 \times 10^{12} \Omega$

5. Stability: $\pm 0.01 \text{ pH/3h}$

6. Temperature compensation range: (0 ~ 99.9)°C Auto/manual

7. Power supply: 220V/110V

8. Dimension: 320×220×90mm

9. Net Weight: 1.5kg

10. Shipping Size: 330x260x280mm/2kg

Included Accessories:

1. E-201-9 Combined Electrode
2. T-818-B-6 Temperature Electrode
3. Multi-function Electrode Holder
4. Fuse BGXP $\Phi 5 \times 20$ 0.5A
5. Buffer Solution
6. Universal Adapter

DDS-11A Benchtop Conductivity Meter



Features:

1. Large screen and LCD segmented display.
2. It functions as auto and manual temperature compensation.
3. If matched with the titanium alloy sensor of 0.01cm-1 and sealed measuring reservoir, it can test high purity water.
4. It is equipped with DJS-1C platinum black probe and T-818-B-6 temperature sensor.

Specifications:

1. Measuring range: Conductivity: 0.00 μ S/cm-100 μ S/cm; TDS: 0-1000 mg/L; Temperature: 0.0-60.0 °C
2. Accuracy: Conductivity: $\pm 0.5\%$ FS; T D S: $\pm 1.0\%$ FS; Temperature: $\pm 0.3^{\circ}\text{C} \pm 1$ bit
3. Stability: ($\pm 0.33\%$ FS ± 1 digital)/3h
4. Temperature compensation range: Manual/Auto (0.0-40.0) $^{\circ}\text{C}$
5. Temperature compensation coefficient: 2%
6. Power supply: 220V / 110V
7. Dimension: 300 \times 200 \times 72mm
8. Net Weight: 1.5kg

Conductance Constant and corresponding Conductivity measuring range

Electrode constant (K) (cm^{-1})	0.01	0.1	1	10
Measuring range ($\mu\text{S}/\text{cm}$)	0.0 \sim 2.0	0.2 \sim 20.0	2 \sim 1 $\times 10^4$	1 $\times 10^4 \sim$ 1 $\times 10^5$

Included Accessories:

- 1.DJS-1C Platinum-black Probe
- 2.T-818-B-6 Temperature Sensor
- 3.Multi-function Electrode Holder
4. Fuse BGXP $\Phi 5 \times 20$ 0.5A
- 3.Universal Adapter

Pen Type pH/Conductivity Meter

P3 Series

- Mini design with size 148×29×14mm.
- Intelligent Functions: auto calibration, auto power-off, low voltage alarm, etc.
- Reliable structure design: meets IP57, Replaceable electrodes.



Model	P301	P311	P312
Description	pH Meter		Conductivity Meter
Measuring Range	-1.00~15.00pH		Conductivity (0 ~ 10)mS/cm: (0~99.9)μS/cm, (100~999)μS/cm, (1.00~10.00)mS/cm.
Resolution	0.01pH		0.1/1μS/cm; 0.01mS/cm
Accuracy	±0.2pH	±0.05pH	±3%FS
Temp. Compensation	0 ~ 60℃		
Calibration	1-3 Point (pH4.00/7.00/9.18)		1 Point (1413μS/cm)
Power	Lithium batteries (CR2032) x 2		
Humidity	85%		
IP grade	IP57		
Shipping size/G.W.	168×96×28mm/180g		
Standard Accessories	Replaceable batteries		Replaceable batteries
	Manual		Manual
	pH buffer solution		

P5 Series

- Intelligent Functions: auto calibration, ATC, auto power-off, low voltage alarm, etc.
- Rechargeable Lithium batteries (3000mA) can last for more than 400 hours with USB charging mode.
- Reliable structure design: meets IP57, Replaceable electrodes.



Model	P501	P511	P512
Description	pH Meter		Conductivity Meter
Measuring Range	-1.00~15.00pH		0~1999mg/L
Resolution	0.1pH; ±0.1℃	0.01pH; ±0.1℃	10mg/L
Accuracy	±0.1pH; ±1.0℃		±2%FS
Temp. Compensation	0 ~ 60℃ (Auto)		
Calibration	1-3 Point (pH4.00/7.00/9.18)		1 Point (1413μS/cm)
Power	3000mA Lithium batteries x 2		
Humidity	85%		
IP grade	IP57		
Shipping size/G.W.	168×96×28mm/220g		
Standard Accessories	Replaceable batteries		Replaceable batteries
	Manual		Manual
	pH buffer solution		

R100 Mini Magnetic Stirrer(without heating)



- LED display screen, which displays speed, mode, timing, etc.
- With smart chip, the speed can be set and saved, 2-modes of rotation and timing function available.
- Five different speeds are available.
- Two rotation options of forward/reverse mode and one-way mode.
- ABS plastic outer shell and anti-slip foot pads ensure stirring stability.
- Equipped with strut and electrode clip, which is used as stirred electrode stand.
- Laboratory routine use, can be carried in the field and on the spot, as well as in the incubator.
- Waterproof design.

Speed range	Five-speed
Maximum stirring capacity	1000ml
Working diameter	100mm
Maximum operating current	150mA
Maximum power consumption	1.5W
Size of the electrode clip mount	Φ16mm (2 holes), Φ13mm (1 hole)
Electrode holder’s Landing distance	0~100mm
Power	DC12V
Dimensions/N.W.	160 x 120 x 65mm /600g
Shipping Size/G.W.	220 x 230 x 120mm /1kg
Standard Accessories	Strut, Electrode clip, Stir bead x 2pcs, Adapter, Manual

Turbidity Meter



Benchtop



Portable

- 4.3 inch colored TFT screen with friendly UI.
- Contain 200 curves and customize high precision test curve according to measurement ranges. Users can set up different piecewise curve and coefficient subject to different concentrations which will literally improve measurement precision.
- ARM9 main control chip makes operations easy, response quick and big storage up to 500M.
- Adopt special and high precision light filter system to ensure the instruments' stability and accuracy.
- Cold light source, narrowband interference, with long lifetime up to 100,000 hours.
- Benchtop Type: Data transfer to PC via USB interface and optional bluetooth transmission.
- Portable Type: Advanced power management system can show the battery status in real time and be charged via USB port on PC or vehicle.

Model	BT-2000D	BT-2000S	BT-2000H	PT-2000S	PT-2000H
Type	Benchtop			Portable	
Description	Drinking Water Turbidity	Smart Turbidity	High-precision Turbidity	Smart Turbidity	High-precision Turbidity
Minimum readout (NTU)	0.001	0.01	0.001, 0.01	0.01	0.001
Measuring range (NTU)	0-10	0-10			
	0-100	0-100			
	—	0-1000			
	—	0-4000			
Basic error	±5%FS	±5%FS	±2%FS	±5%FS	±3%FS
Repeatability	≤0.5%				
Zero Drift	±0.5%F.S	—	—	±0.5%FS	±0.5%FS
Applications	Drinking water and low turbidity solutions, with wider cuvette	Industrial waste water and river water	Industrial waste water and river water	Drinking water, surface water and circulating water	Factory condensate water, Domestic sewage
Power	220V/110V			Lithium battery 3.7V/5200mA	
Output	USB, RS232			Micro USB	
Dimensions/N.W.	290×365×120 mm / 3.7kg			210×105×65mm/500g	
Shipping size/G.W.	485×383×250mm / 5kg			300×240×90mm/1kg	
Standard Accessories	1cm glass cuvette - A set of 4 pcs			Cuvette cup x 2 pcs	
	5cm glass cuvette - A set of 2 pcs			Charger	
	Power cord			Suitcase	
	Manual			Manual	

Colorimeter



Benchtop



Portable

- 4.3 inch colored TFT screen with friendly UI.
- Contain 200 curves and customize high precision test curve according to measurement ranges. Users can set up different piecewise curve and coefficient subject to different concentrations which will literally improve measurement precision.
- ARM9 main control chip makes operations easy, response quick and big storage up to 500M.
- Adopt special and high precision light filter system to ensure the instruments' stability and accuracy.
- Cold light source, narrowband interference, with long lifetime up to 100,000 hours.
- Benchtop Type: Data transfer to PC via USB interface and optional bluetooth transmission.
- Portable Type: Advanced power management system can show the battery status in real time and be charged via USB port on PC or vehicle.

Model	BC-2000D	BC-2000S	BC-2000H	BC-2000B	PC-2000H
Type	Benchtop				Portable
Description	Drinking Water Colorimeter	Smart Colorimeter	High-precision Colorimeter	Beer Colorimeter	High-precision Colorimeter
Minimum readout (PCU)	0.001	0.1	0.001, 0.01	0.001EBC	0.001
Measuring range (PCU)	0～50	0-500	0-500	0-30EBC	0-500, 0-100
Basic error	±5%FS	±5%FS	±5%FS	2-5 EBC, ≤±0.1 EBC	±3%FS
				5-10 EBC, ≤±0.2 EBC	
				10-30 EBC, ≤ ±0.5 EBC	
Repeatability	≤0.5%				
Zero Drift	±0.5%FS				
Applications	Drinking water and low chroma solutions, with wider cuvette	Industrial waste water and river water	Industrial waste water and river water	Beer chroma measurements	Industrial waste water, river water, drinking water, domestic sewage
Power	220V/110V				Lithium battery3.7V/5200mA
Output	USB, RS232				Micro USB
Dimensions/N.W.	290×365×120 mm / 3.7kg				210×105×65mm/500g
Shipping size/G.W.	485x383x250mm / 5kg				300x240x90mm/1kg
Standard Accessories	1cm quartz cuvette - A set of 2 pcs				Cuvette cup x2 pcs
	3cm quartz cuvette - A set of 2 pcs				Charger
	Power cord				Suitcase
	Manual				Manual

SY Series 0.1/1mg Touch Screen Balance



- 5.7 inch color touch screen and convenient graphic menu.
- With powerful software SUPERTEX1.0, SY balance have functions, such as weighing, parts counting, percent weighing, check weighing, animal weighing, totalization, density weighing, formula weighing, target weighing, etc.
- Multi-users management, can store 5000 sets of test data, can display the sensor temperature and automatic temperature compensation in real time to ensure the accuracy of the instrument.
- Excellent wireless sensing operation function, can set the operation of automatic correction and peeling function, to avoid contamination of the instrument by chemical reagent operation.
- Electromagnetic balance sensor
- External/ Internal calibration
- RS232C and USB output interface.

Model	Maximum Capacity	Readability	Pan Size	Dimension/N.W.	Shipping Size/G.W.	Calibration
SY104	100g	0.1mg	Φ90mm	230*393*350mm/8kg	520*380*500mm/10kg	External
SY204	200g	0.1mg				External
SY304	300g	0.1mg				External
SY103	100g	1mg				External
SY203	200g	1mg				External
SY303	300g	1mg				External
SY503	500g	1mg				External
SY104C	100g	0.1mg				Internal
SY204C	200g	0.1mg				Internal
SY304C	300g	0.1mg				Internal
SY103C	100g	1mg				Internal
SY203C	200g	1mg				Internal
SY303C	300g	1mg				Internal
SY503C	500g	1mg				Internal
Standard Accessories	Calibration Weight (for external calibration balance), Adapter, Manual, Dust cover					

YK Series 0.1/1mg Balance



- Large blue backlighting 120*55 mm LCD screen.
- Powerful functions like basic weighing, piece counting, whole automatic taring, checkweighing, percentage ,multi-units conversion and animal weighing, etc.
- With the sensor technology of German STL software, it supports muti-point calibration and has more stable performance.
- The windshield of all around antistatic coating can effectively shield the electrostatic interference.
- Electromagnetic balance sensor
- External/ Internal calibration
- The built-in RS232 standard interface can connect to printer or computer.
- Units: g, mg, ct, oz, ozt.

Model	Weighing Range	Readability	Pan Size	Dimension/N.W.	Shipping Size/G.W.	Calibration
YK1004B	0-100g	0.1mg	Φ80mm	360*220*350mm/8kg	520*380*500mm/10kg	External
YK1104B	0-110g					
YK1204B	0-120g					
YK2004B	0-200g					
YK2104B	0-210g					
YK2204B	0-220g					
YK1004C	0-100g					Internal
YK1104C	0-110g					
YK1204C	0-120g					
YK2004C	0-200g					
YK2104C	0-210g					
YK2204C	0-220g					
YK1003N	0-100g	1mg	Φ80mm	360*220*350mm/8kg	520*380*500mm/10kg	External
YK1203N	0-120g					
YK2003N	0-200g					
YK2603N	0-260g					
YK3003N	0-300g					
YK5003N	0-500g					
YK1003C	0-100g					Internal
YK1203C	0-120g					
YK2003C	0-200g					
YK2603C	0-260g					
YK3003C	0-300g					
YK5003C	0-500g					
Standard Accessories	Calibration Weight (for external calibration balance), Adapter, Manual, Dust cover					

FA/JA Series 0.1/1mg Balance



- Large blue backlighting 120*55 mm LCD screen.
- Powerful functions like basic weighing, piece counting, whole automatic taring, checkweighing, percentage ,multi-units conversion and animal weighing, etc.
- With the sensor technology of German STL software, it supports multi-point calibration and has more stable performance.
- The windshield of all around antistatic coating can effectively shield the electrostatic interference.
- Electromagnetic balance sensor
- External/ Internal calibration
- 4-level shockproof
- Counting function
- The built-in RS232 standard interface can connect to printer or computer.
- Units: g, mg, ct, oz, ozt.

Model	Weighing Range	Readability	Pan Size	Dimension/N.W.	Shipping Size/G.W.	Calibration
FA1004B	0-100g	0.1mg	Φ80mm	350*215*340mm/8KG	520*380*500mm/10kg	External
FA1204B	0-120g					
FA2004B	0-200g					
FA2104B	0-210g					
FA2204B	0-220g					
FA1004C	0-100g					Internal
FA1204C	0-120g					
FA2004C	0-200g					
FA2104C	0-210g					
FA2204C	0-220g					
JA1003N	0-100g	1mg	Φ80mm	350*215*340mm/8KG	520*380*500mm/10kg	External
JA1203N	0-120g					
JA2003N	0-200g					
JA2603N	0-260g					
JA3003N	0-300g					
JA5003N	0-500g					
JA1003C	0-100g					Internal
JA2003C	0-200g					
Standard Accessories	Calibration Weight (for external calibration balance), Adapter, Manual, Dust cover					

YP Series Electronic Balance



Round Pan



Rectangular Pan

- The new design promotes the reaction speed and fixed-point speed.
- The unique metal base and mechanical construction ensure a high stability and increase the anti-interference performance.
- It has various functions such as: multi-units conversion, parts counting, animal weighing, etc.
- RS232C output interface.

Model	Weighing Range	Readability	Pan Size	Dimension/N.W.	Shipping Size/G.W.	Power
YP1002	0~100g	10mg	Φ130mm	280*200*60mm/ 1.8kg	320*280*150mm/ 2.5kg	communication & direct current
YP2002	0~200g	10mg				
YP3002	0~300g	10mg				
YP4002	0~400g	10mg				
YP5002	0~500g	10mg				
YP6002	0~600g	10mg				
YP10002	0~1000g	10mg				
YP20002	0~2000g	10mg				
YP30002	0~3000g	10mg				
YP2001	0~200g	100mg				
YP3001	0~300g	100mg				
YP4001	0~400g	100mg				
YP5001	0~500g	100mg				
YP6001	0~600g	100mg				
YP8001	0~800g	100mg				
YP10001	0~1000g	100mg				
YP20001	0~2000g	100mg				
YP30001	0~3000g	100mg				
YP40001	0~4000g	100mg				
YP50001	0~5000g	100mg				
YP60001	0~6000g	100mg				
YP80001	0~8000g	100mg				
YP100001	0-10000g	0.1g	255*190mm	320*220*100mm/ 2.5kg	360*300*185mm/ 3.3kg	
YP200001	0-20000g	0.1g	Φ130mm	280*200*60mm/ 1.8kg	320*280*150mm/ 2.5kg	
YP1000	0~1000g	1g				
YP2000	0~2000g	1g				
YP3000	0~3000g	1g				
YP5000	0-5000g	1g				
YP6000	0-6000g	1g				
YP8000	0-8000g	1g				
YP10000	0-10000g	1g	255*190mm			
YP15000	0-15000g	1g				
YP20000	0-20000g	1g				
YP30000	0-30000g	1g				
Standard Accessories	Calibration Weight (optional), Adapter, Manual, Dust cover					

Moisture Analyzer



- The Large, high-resolution, bright dot matrix LCD display make operation easy and comfortable in the dark place.
- One-button operation makes testing easier.
- The high precision heat insulation type sensor makes the temperature for data acquisition reliable.
- The use of halogen lamp for heating and drying makes heating rapidly and test time shorter.
- In the process of test, the dry state can be directly confirmed to speculate the finish time.
- With auto peeling function, it can measure immediately and continuously, and also measure accurately through the zero drift correction.
- Installed with RS232C interface inside, the products can be directly connected to computer or printer(blue-teeth).
- The Halogen drying method moisture analyzer can test the free water content of chemical raw materials, grain, mineral, biological product, food, pharmaceutical raw materials, paper, textile raw materials, etc.

Model	DSH-10A	DSH-50A-1	DSH-50A-5	DSH-50A-10	DSH-100A-1	DSH-100A-5	DSH-100A-10
Weighing Range	10g	50g	50g	50g	100g	100g	100g
Readability	10mg	1mg	5mg	10mg	1mg	5mg	10mg
Repeatability (3g samples)	0.005	0.002	0.003	0.005	0.002	0.003	0.005
Minimum Sample Amount	0.5g						
Advised Sample Amount	3-5g						
Heat up time	1-99minutes, 1 minute interval						
Temperature Program	Standard						
Terminal Control	Timing, Automatic						
Heating Temperature Range	50-180°C						
Display Content	Moisture%, Solid%, Weight, Time, Data etc						
Heating Source	Halogen Lamp						
Pan Size	100mm						
Dimension/N.W.	265x160x150mm/5kg						
Shipping size/G.W.	530x380x340mm/6kg						
Standard Accessories	Calibration Weight, Power Cable, Manual						

Kindly note:The above repeatability is based on 3g sample.More sample weight,better repeatability results.

Biological Microscope

Natural light source biological microscope XSP-1CA

Traditional models, stable quality and high cost performance. the light bar turntable.



Monocular tube: monocular 45° tilt, 360° rotatable

Magnification: 40 times - 640 times

Objective Mirror Converter: Three-Pole Converter

Eyepiece: 16X

Achromatic objective lens: 4X, 10X, 40X

Observation head: monocular observation head

Stage: tablet square platform

Focusing: coarse focus adjustment

Condenser: turntable

Light source: natural light source

Mirrors: flat and concave mirrors

Binocular biological microscope XSP-2CA

Used to observe and study biological sections, biological cells, bacteria, and living tissue culture, fluid precipitation, etc., while observing other transparent or translucent objects as well as objects such as powders and fine particles. Suitable for research experiments in biology, bacteriology, medicinal chemistry, etc.



Achromatic objectives: 4X, 10X, 40X (spring), 100X (spring oil)

Flat field eyepiece: large field of view eyepiece WF10X, (WF16X optional)

Flat field eyepiece: large field of view eyepiece WF10X, (WF16X optional)

Total magnification: 40X-1600X

Observation head: hinged binocular head

Objective Mirror Converter: Four-Pole Converter

Stage: Double-layer movable platform: 115x125mm Actual range 15*75mm

Condenser: Condenser NA=1.25 with variable diaphragm

Light source: electric light source (LED or halogen)

Focusing: Coaxial coarse and fine adjustment, focusing range 20mm

Power supply: 220V or 110V AC input, 6V DC regulated output

Monocular biological microscope XSP-3CA

Widely recognized at all levels in various application fields for its reliable stability and superior cost performance. Can be used in biological, medical, agricultural and animal husbandry, textile fiber, medicinal chemical microparticles and other observational research.



Flat field eyepiece: large field of view eyepiece WF10X, (WF16X optional)

Achromatic objectives: 4X, 10X, 40X (spring), 100X (spring, oil)

Total magnification: 40X-1600X

Monocular viewing head: 45° tilt 360° rotation

Converter: Four-hole converter

Coarse and fine adjustment focus range: Coaxial coarse and fine adjustment, focusing range 20mm

Stage: Double mechanical movable platform: 115x125mm Actual range 15*75mm

Mechanical barrel length: 160mm

Condenser: Condenser NA=1.25 with variable diaphragm

Lighting: Electric light source (LED or halogen)

Power supply: 220V or 110V AC input, 6V DC regulated output

Binocular biological microscope XSP-8CA

Used to observe and study biological sections, biological cells, bacteria, and living tissue culture, fluid precipitation, etc., while observing other transparent or translucent objects as well as objects such as powders and fine particles. Suitable for research experiments in biology, bacteriology, medicinal chemistry, etc.



- Achromatic objectives: 4X, 10X, 40X (spring), 100X (spring, oil)
- Flat field eyepiece: large field of view eyepiece WF10X, (WF16X optional)
- Total magnification: 40X-1600X
- Observation head: hinged binocular head
- Objective Mirror Converter: Four-Pole Converter
- Stage: Double-layer movable platform: 115x125mm Actual range 15*75mm
- Condenser: Condenser NA=1.25 with variable diaphragm
- Light source: electric light source (LED or halogen)
- Focusing: Coaxial coarse and fine adjustment, focusing range 20mm
- Power supply: 220V or 110V AC input, 6V DC regulated output

Trinocular Biological Microscope XSP-10CA

Used to observe and study biological sections, biological cells, bacteria, and living tissue culture, fluid precipitation, etc., while observing other transparent or translucent objects as well as objects such as powders and fine particles. Suitable for industries or individuals who require microscopic observation experiments such as laboratory/school/aquaculture/medical institutions/clinical research.



- Achromatic objectives: 4X, 10X, 40X (spring), 100X (spring, oil)
- Flat field eyepiece: large field of view eyepiece WF10X, (WF16X optional)
- Total magnification: 40X-1600X
- Observation head: hinged trinocular head
- Objective Mirror Converter: Four-Pole Converter
- Stage: Double-layer movable platform: 115x125mm Actual range 15*75mm
- Condenser: Condenser NA=1.25 with variable diaphragm
- Light source: electric light source (LED or halogen)
- Focusing: Coaxial coarse and fine adjustment, focusing range 20mm
- Power supply: 220V or 110V AC input, 6V DC regulated output
- Electronic eyepiece: 200W/500W pixels

MODEL	XSP-1CA	XSP-2CA	XSP-3CA	XSP-8CA	XSP-10CA
Tube	Monocular	Binocular	Monocular	Binocular	Trinocular
Condensor/Light Bar	Abbe condenser variable iris diaphragm and filter				
Eyepiece	Huygens eyepiece H5X,H10X,H6X	Wide-angle eyepiece WF10X,Huygens eyepiece H16X			
Achromatic Objective	4x,10X,40X(S)	4X,10X,40X(S),100X(S)			
Lighting	Halogen lamp 6V/20W				
Power Source	Nature light	Electric light	Electric light	Electric light	Electric light
Shipping size	370x240x210mm	425x300x250mm	400x280x210mm	425x300x250mm	
G.W.	1.6kg	4kg	2.7kg	4kg	