

PCE Americas Inc.
711 Commerce Way
Suite 8
Jupiter
FL-33458
USA
From outside US: +1
Tel: (561) 320-9162
Fax: (561) 320-9176
info@poe-americas.com

PCE Instruments UK Ltd.
 Units 12/13
 Southpoint Business Park
 Ensign way
 Hampshire / Southampton
 United Kingdom, SO31 4RF
 From outside UK: +44
 Tel: (0) 2380 98703 0
 Fax: (0) 2380 98703 9
 info@poe-instruments.com

www.pce-instruments.com/english www.pce-instruments.com

## Force Gauge for for businesses / weighing range up to max. 15.000 kg / with remote control

Force Gauge with a high weight range up to 15 t. The resolution of the Force Gauge is 10 kg. The housing of the Force Gauge has an IP 67 protection. The digit height is 40 mm and thanks to the display high contrast is easy to read. The remote control is included in the shipment. It can control the Force Gauge at a maximum distance of 8 m. Some features of the Force Gauge are the addition of several weights, controlled weights with imit value definition, percentage weighing, piece counting and indication of the maximum weight.

It is especially suitable for warehouses, retail, food and transport sectors, although of course it can be used in other fields. Because of its small size, it allows very efficient use in lifting systems or lifting devices such as cranes. The Force Gauge is sent with accumulator, charger and remote control (including battery).

- Display with red LEDs , 40 mm height
- Protection IP 67, protection against water and dust
- rechargeable battery with hermetic protection ( aprox. life of 60 h in use)
- Peak value
- Addition function
- weighing percentage
- Piece counting function
   Remote control

## **Technical Specifications**

	Maximum	Minimum load weight	Reading capacity	Repeatability	Verification value
	weight range [kg]	[kg]	[kg]	n . 1	[kg]
PCE-MCWHU15	15000	200	10	[kg] ±0.03% of	10
				weight range	

Protection IP 67 (protection against water and dust)

Tare function yes, in all the range

Response time <10 s
Units of measurement kg / lb

Functions Addition, percentage, piece counting function, pick value, freeze the valuein display (HOLD)

Display with red LEDs, 40 mm hight

Enclosure very robust construction of lacquered iron plate (galvanized)

Power rechargeable battery 6 V - 10 A / (prox. life of 60 h ) / automatic switch off

Time to recharge aprox. 12 hours

Auto shut-off programmable of 1 to 255 minutes, or desactivated

Remote control Regulable for automatic tare or remote control of 4 keys

Operating temperature -10 ... +40 °C

Weight 86 kg

## **Delivery contents**