



## 1 - ELECTRICAL SPECIFICATIONS

Accuracy indicated as  $\pm$  [%rdg + (no. dgts \* resolution)] at 23°C  $\pm$  5°C, <75%HR

### DC Voltage

Range [V]	Resolution [V]	Accuracy
10.0 ÷ 265.0	0.1	$\pm(0.7\% \text{ rdg} + 0.4V)$

Voltage values <10.0V are zeroed

### AC TRMS Voltage – Phase to Neutral

Range [V]	Frequency [Hz]	Resolution [V]	Accuracy
10.0 ÷ 265.0	42.5 ÷ 65.0	0.1	$\pm(0.5\% \text{ rdg} + 0.2V)$

Max Crest Factor =1.5, Voltage values <10.0V are zeroed

### AC TRMS Voltage – Phase to Phase

Range [V]	Frequency [Hz]	Resolution [V]	Accuracy
50.0 ÷ 460	42.5 ÷ 65.0	0.1	$\pm(1.0\% \text{ rdg} + 0.2V)$

Max Crest Factor =1.5, Voltage values <10.0V are zeroed

### DC TRMS Current by external clamp transducer – STD clamps

Range [mV]	Resolution [mV]	Accuracy	Overload protection
5.0 ÷ 219.9	1	$\pm(0.7\% \text{ rdg} + 1mV)$	10V
220.0 ÷ 999.9		$\pm 0.7\% \text{ rdg}$	

Current values correspondent to a voltage < 5mV are zeroed

### AC TRMS Current by external clamp transducer – STD clamps

Range [mV]	Frequency [Hz]	Resolution [mV]	Accuracy	Overload protection
5.0 ÷ 219.9	42.5 ÷ 65.0	1	$\pm(0.5\% \text{ rdg} + 0.6mV)$	10V
220.0 ÷ 999.9			$\pm 0.5\% \text{ rdg}$	

Current values correspondent to a voltage < 5mV are zeroed

### AC TRMS Current by external clamp transducer – Flex (100A AC range – 85uV/A)

Range [mV]	Frequency [Hz]	Resolution	Accuracy	Overload protection
0.085 ÷ 8.50	42.5 ÷ 65.0	8.5 $\mu$ V	$\pm(0.5\% \text{ rdg} + 0.007mV)$	10V

Max Crest Factor =1.5, Current values <1A are zeroed

### AC TRMS Current by external clamp transducer – Flex (1000A AC range – 85uV/A)

Range [mV]	Frequency [Hz]	Resolution	Accuracy	Overload protection
0.425 ÷ 85.0	42.5 ÷ 65.0	85 $\mu$ V	$\pm(0.5\% \text{ rdg} + 0.15mV)$	10V

Max Crest Factor =1.5, Current values <5A are zeroed

### Frequency

Range [Hz]	Resolution [Hz]	Accuracy
42.5 ÷ 65.0	0.1	$\pm(0.2\% \text{ rdg} + 0.1Hz)$

### DC Power – (Vmeas>200V)

Clamp FS [A]	Range [W] [Wh]	Resolution [W] [Wh]	Accuracy
1 < FS $\leq$ 10	0.000k ÷ 9.999k	0.001k	$\pm(1.0\% \text{ rdg} + 5W)$
	10.00k ÷ 99.99k	0.01k	$\pm(1.0\% \text{ rdg} + 50W)$
10 < FS $\leq$ 200	0.00k ÷ 99.99k	0.01k	$\pm(1.0\% \text{ rdg} + 50W)$
	100.0k ÷ 999.9k	0.1k	$\pm(1.0\% \text{ rdg} + 500W)$
200 < FS $\leq$ 1000	0.0k ÷ 999.9k	0.1k	$\pm(1.0\% \text{ rdg} + 0.5kW)$
	1000k ÷ 9999k	1k	$\pm(1.0\% \text{ rdg} + 5kW)$

Vmeas = Voltage in which the power is measured

**Power/Energy – (V<sub>meas</sub>>200V, Pf=1)**

Clamp FS [A]	Range [W] [Wh]	Resolution [W] [Wh]	Accuracy
1 < FS ≤ 10	0.000k ÷ 9.999k	0.001k	±(0.7%rdg + 3W/Wh)
	10.00k ÷ 99.99k	0.01k	±(0.7%rdg+30W/Wh)
10 < FS ≤ 200	0.00k ÷ 99.99k	0.01k	±(0.7%rdg+30W/Wh)
	100.0k ÷ 999.9k	0.1k	±(0.7%rdg+300W/Wh)
200 < FS ≤ 1000	0.0k ÷ 999.9k	0.1k	±(0.7%rdg+0.3kW/kWh)
	1000k ÷ 9999k	1k	±(0.7%rdg+3kW/kWh)

V<sub>meas</sub> = Voltage in which the power is measured

**Power factor (Cosφ)**

Range (cosφ)	Resolution	Accuracy (°)
0.20 ÷ 0.50	0.01	0.6
0.50 ÷ 0.80		0.7
0.80 ÷ 1.00		1.0

**Voltage/Current harmonics (Real time values available only)**

Range	Maximum resolution	Base accuracy
DC ÷ 25 <sup>th</sup>	0.3V / 0.1% FS clamp	±(5.0% rdg + 2dgt)
26 <sup>th</sup> ÷ 33 <sup>th</sup>		±(10% rdg + 2dgt)
34 <sup>th</sup> ÷ 49 <sup>th</sup>		±(15% rdg + 2dgt)

Harmonics will be zeroed:

- DC harmonics: DC value <0.5% 1st Harmonic value or if DC value < 0.5% FS clamp
- 1st Harmonic: 1st Harmonic value <0.5% FS clamp
- 2nd ÷ 49th Harmonics: 2nd ÷ 49th values <0.5% 1st Harmonic value or <0.5% FS clamp



## 2. GENERAL SPECIFICATIONS

### ELECTRICAL SYSTEMS

- Single Phase,
- 3 Phase without Neutral
- 3 Phase with Neutral

### CHANNELS RECORDED SIMULTANEOUSLY

- Phase to Neutral and Phase to Phase voltages
- Phase currents
- THD% voltages and currents
- Phase and total active and reactive power
- Phase and total power factor and  $\text{Cos}\phi$
- Phase and total active and reactive energy
- Number of recorded parameters: 44 (fixed)
- Integration Period: 5, 10, 30s, 1, 2, 5, 10, 15, 60min.
- Recording autonomy: > 230 days with integrated period of 15 minutes
- Memory capacity: 8Mbyte

### POWER SUPPLY:

Internal power supply: Rechargeable battery, battery life approx. 1 hour  
External power supply: By mean Red/Yellow plugs, 100V ÷ 415V, 50/60Hz  
45mA@100V, 30mA@230V, 20mA@415V

### COMMUNICATION INTERFACE

PC (Windows), Tablet/Smartphone(iOS, Android): USB (PC only) / WiFi

### MECHANICAL FEATURES:

Dimensions (L x W x H): 245 x 210 x 110mm  
Weight: 1.5kg

### WORKING ENVIRONMENTAL CONDITIONS:

Reference temperature:  $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$   
Working temperature:  $0^{\circ} \div 40^{\circ}\text{C}$   
Allowed relative humidity: <80%HR  
Storage temperature:  $-10 \div 60^{\circ}\text{C}$   
Storage humidity: <80%HR

### POWER/ENERGY MEASUREMENTS REFERENCE GUIDELINES:

Features of voltage supplied by public utilities: EN50160 (only voltage and THDV%)

### GENERAL REFERENCE GUIDELINES:

Safety of measuring instruments: IEC/EN61010-1  
Insulation: double insulation  
Pollution degree: 2  
Encapsulation: IP65 (case board closed)  
Measurement category: CAT IV 300VAC to ground, max 460V between Inputs  
Max height of use: 2000m

**This instrument complies with the prescriptions of the European directive on low voltage 2006/95/EEC (LVD) and EMC directive 2004/108/EEC**