

Regulated DC Power Supplies

PA10-5B (10V/5A)	PA80-1B (80V/1A)
PA18-1.2B (18V/1.2A)	PA120-0.6B (120V/0.6A)
PA18-2B (18V/2A)	PA160-0.4B (160V/0.4A)
PA18-3B (18V/3A)	PA250-0.25B (250V/0.25A)
PA18-5B (18V/5A)	PA250-0.42B (250V/0.42A)
PA36-1.2B (36V/1.2A)	PA350-0.2B (350V/0.2A)
PA36-2B (36V/2A)	PA600-0.1B (600V/0.1A)
PA36-3B (36V/3A)	

PA-B Series

Remote Sensing



GP-IB
OPTION

- Low ripple, low noise
- Digital display of voltage and current at the same time
- Series/parallel operation
- Floating output/voltage remote sensing terminal
- External analog control

- Monitor output
 - EIA rack size
 - Option: GP-IB Adapter (GP-600B and OP-18-PAB)
 - PA18-1.2B/PA18-2B/PA36-1.2B:without handle.
- With handle model:PA18-1.2BVT/PA18-2BVT/PA36-1.2BVT

Specifications

Model	Output (Voltage,Current)	Ripple		Line regulation		Load regulation		Dimensions W×H×D(mm)	Max. dimensions W×H×D(mm)	Power consumption W/VA(approx.)	Weight kg (approx.)
		CV mVrms	CC mA rms	CV mV	CC mA	CV mV	CC mA				
PA10-5B	0V-10V, 0A-5A	0.5	5	1	2	5	5	104×124×350	106.2×144.3×368.3	120W/150VA	6.6
PA18-1.2B	0V-18V, 0A-1.2A	0.5	1	1	2	2	5	104×124×270	106.2×144.3×288.3	50W/60VA	4.7
PA18-2B	0V-18V, 0A-2A	0.5	1	1	2	2.5	5	104×124×270	106.2×144.3×288.3	75W/100VA	4.7
PA18-3B	0V-18V, 0A-3A	0.5	1	1	2	3	5	104×124×350	106.2×144.3×368.3	110W/140VA	6.6
PA18-5B	0V-18V, 0A-5A	0.5	5	1	2	5	5	104×124×350	106.2×144.3×368.3	165W/210VA	6.6
PA36-1.2B	0V-36V, 0A-1.2A	0.5	1	2	2	2	5	104×124×270	106.2×144.3×288.3	80W/105VA	4.7
PA36-2B	0V-36V, 0A-2A	0.5	2	2	2	3	5	104×124×350	106.2×144.3×368.3	130W/165VA	6.6
PA36-3B	0V-36V, 0A-3A	0.5	2	2	2	4	5	104×124×350	106.2×144.3×368.3	170W/220VA	6.6
PA80-1B	0V-80V, 0A-1A	1	2	5	2	5	5	104×124×350	106.2×144.3×368.3	140W/170VA	6.6
PA120-0.6B	0V-120V, 0A-0.6A	1.2	1	7	1	7	5	104×124×350	106.2×144.3×368.3	115W/155VA	6.6
PA160-0.4B	0V-160V, 0A-0.4A	1.6	1	8	1	8	5	104×124×350	106.2×144.3×368.3	100W/150VA	6.6
PA250-0.25B	0V-250V, 0A-0.25A	2.5	1	15	0.5	15	5	104×124×350	106.2×144.3×368.3	105W/140VA	6.6
PA250-0.42B	0V-250V, 0A-0.42A	2.5	1	15	1	15	5	104×124×350	106.2×144.3×368.3	150W/220VA	6.6
PA350-0.2B	0V-350V, 0A-0.2A	3.5	1	20	0.5	20	5	104×124×350	106.2×144.3×368.3	110W/150VA	6.6
PA600-0.1B	0V-600V, 0A-0.1A	5	1	30	0.5	30	2.5	104×124×350	106.2×144.3×368.3	100W/130VA	6.6

Options

GP-600B	GP-IB adapter
OP-18-PAB	Connection cable between PA-B and GP-600B (1pcs)
OP-20GC	Front output terminal guard cap (2pcs)
Model + VT	[Factory option] To add handle for no handle models