

# WL900 Radar Level Transmitters

Radar level transmitters are ideal for a variety of water and wastewater applications



- Accurate, non-contact measurement
- Works in conditions where ultrasonic is not acceptable
- Pulse radar measurement range 10" to 50'
- Simple push-button calibration
- Standard 4-20mA signal output
- Optional RS485 digital output

## Description

The WL900 Radar Level Transmitter offers a logical extension to ultrasonic devices. It is suitable for applications that require non-contact liquid level measurement when ultrasonic level measurement is not acceptable.

### Variety of Uses

The WL900 is ideal for a variety of water and wastewater applications involving a reflective liquid that has a foaming surface, vapors, or dusty conditions beyond ultrasonic wave capabilities.

### State of the Art Radar Technology

The WL900 uses a state of the art radar pulse technology, which provides accurate and reliable level measurements over a wide 10 inch to 50 foot range. The unit's microwave antenna rod sends out very short pulses, which reflect off a target and are received back by the antenna for processing.

### Simple Operation

With its single push-button calibration system, the WL900 is easy to set up and maintain. Simply aim the WL900 at your low range level set point and push the button to lock in the setting— then do the same with the high level set point. This may be done before permanent installation by aiming at a wall and using a tape measure to determine your exact range.

### Rugged Design

The unit's rugged NEMA 4 (IP65) housing is available in either aluminum or 316L stainless steel for corrosive environments. A standard 2" NPT (M) process connection allows for quick and versatile installation. In addition, the unit's polypropylene antenna rod is virtually corrosion proof.

## Specifications

### Power

AC: 115 VAC, 60 Hz (± 20%), 1.7 VA

DC: 12 to 30 VDC, 0.07 Amps max. @ 24 VDC

### Outputs

Signal: 4-20 mA, 6.1 uA resolution; 750 ohms

Communication: RS232

Accuracy: ±0.25% of max. target range (in air)

Frequency: 6.3 GHz

Transmitter Power: 50 uW average

Calibration: Push-button or optional programmable

Antenna: Polypropylene over dielectric rod

Beam Angle: 12 degrees

Operating Temp: -40°C to 60°C (-40°F to 140°F)

Operating Pressure: 150 psi max

Installation Category: Class II

Process connection: 2" NPT

Conduit Entry: 1/2" NPT standard

Housing: Aluminum or 316L stainless steel

Ingress Protection: NEMA 4 (IP65)

Approvals: FCC Part 15 - low-power communication device

Weight: 3.6Lbs (1.63Kg)

Dimensions: 4" (10cm) diameter x 18" (45.7cm) long

## Options and Accessories

### WL900-AC Radar Level Transmitter

Power: 115VAC (60Hz), Enclosure: Aluminum

### WL900-DC Radar Level Transmitter

Power: 12 to 30VDC, Enclosure: Aluminum

### WL901-AC Radar Level Transmitter

Power: 115VAC (60Hz), Enclosure: Stainless Steel

### WL901-DC Radar Level Transmitter

Power: 12 to 30VDC, Enclosure: Stainless Steel

Contact  
Global Water  
for all your  
instrumentation  
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control



Global Water

a xylem brand

In the U.S. call toll free  
at 1-800-876-1172  
International: 1-979-690-5560  
Fax: 1-979-690-0440  
Email: globalw@globalw.com

Visit our online catalog at:  
www.globalw.com  
Our Address:  
11390 Amalgam Way  
Gold River, CA 95670