

AM4113T-FVW



Featuring 400nm UV and white

Overview



Dual light source This software controlled feature allows switching between two sets of lighting for examination.



Up to 200x magnification

Have the freedom to magnify from 20x to 50x the closer the Dino-Lite is to the target, using the Dino-Lite knob to focus for each magnification. Achieve an additional 200x when the Dino-Lite is at close range.



Enhanced 1.3 Megapixels It observes with accurate color reproductions and retain details under low lighting with the optimum resolution for detailed live preview and captured images.



USB 2.0 Interface

Digitize the microscopy experience; allow easy recording and sharing of observations in the office or out in the field with a compatible PC or MAC.



Professional measurement tools Use professional measurement tools that are calibratable for assured accuracy and convienently document or share information with the bundled software.



400nm UV illumination 400nm Near UV lighting to illuminate specimens.



Scroll Lock Assure the knobs position with the scroll lock.

Information about working distance and field of view					
Μ	WD	FOV (x)	FOV (y)		
20	48.7	19.6	15.6		
30	21.7	13.0	10.4		
40	9.0	9.8	7.8		
50	1.9	7.8	6.3		
60	-2.3	6.5	5.2		
220	-0.1	1.8	1.4		
230	1.0	1.7	1.4		
240	2.1	1.6	1.3		
M = mag	nification rate	WD = working	WD = working distance (without front cap)		FOV = field of
view DOF= depth of field Unit = mm					



The farther away the lower the magnification obtained

Approximately 50x and 200x magnification at touch proximity

Specification

Model : AM4113T-FVW Dino-Lite Premier Interface : USB 2.0 Product Resolution : 1.3M pixels (SXGA) Magnification Rate : 20x~50x, 200x Sensor : Color CMOS Frame Rate : Up to 30fps -Save Formats : + Image: DinoCapture2.0: BMP, GIF, PNG, MNG, TIF, TGA, PCX, WBMP, JP2, JPC, JPG, PGX, RAS, PNM DinoXcope: PNG, JPEG + Movie: DinoCapture2.0: WMV, FLV, SWF DinoXcope: MOV Microtouch : Touch sensitive trigger on the microscope for taking pictures Lighting : 4white and 4 UV(400nm) LED lights switched by software Measurement Function : Yes Calibration Function : Yes Operating System Supported : Windows 10, 8, 7, Vista, XP; MAC OS 10.4 or later Unit Weight: 105g Unit Dimension : 10.5cm (H) x 3.2cm (D) Package Dimensions : 16cm (L) x 16cm (W) x 6cm (H)