

SINGLE KERNEL GRAIN MOISTURE METER

SINGLE KERNEL GRAIN MOIST



(MODEL : SIGMA-3030)



(THERMAL MINI PRINTER)

FEATURES

- Designed To Measure Each One Kernel At A Time Consecutively.
- High Durability & Low Noise By Small BLDC Motor.
- Kind Of Grain, Measured Number (PCS), Measurement Time (SEC), Average Test Data And Power Condition Appear On LCD.
- Moisture % & Temperature Of 6 Kinds Of Grain Can Be Measured.
- Average Data Is Possible By Grain Number Or Measurement Time.
- Test Results Can Be Printed By Thermal Mini Printer (Option).
- Testing At Dark Place Is Possible By Funcion Of LED Back Light.
- Portable Type And Suitable For Use In Field.
- Easy To Operate And Not Heavy Weight.

SPECIFICATIONS

MODEL	SIGMA-3030			
APPLICATIONS	Paddy, Barley, Naked Barley, Brown Rice, Rice, Wheat			
PRINCIPLE	Electrical Resistance Method			
MEASURING RANGES	Paddy	11.0 ~ 40.0 %	Barley	11.0 ~ 40.0 %
	Naked Barley	11.0 ~ 40.0 %	Brown Rice	11.0 ~ 20.0 %
	Rice	11.0 ~ 20.0 %	Wheat	11.0 ~ 40.0 %
	ACCURACY	± 0.5 % (Less than 20 %)		
RESOLUTION	0.1 %			
MEASURING SPEED	60 PCS/MINUTE			
MEASUREMENT METHODS	By Number Of Kernels	10 ~ 200 PCS		
	By Measurement Time	30 ~ 180 SEC		
TEMP. COMPENSATION	Automatic			

MEASURING TEMP.	5 ~ 50 °C
EXTERNAL OUTPUT	Through RS-232C
POWER SOURCE	AC 100 ~ 240 V / 60Hz
DIMENSIONS	295 (L) × 193 (W) × 281 (H) mm
GROSS WEIGHT	Approx. 8KG
ACCESSORIES	Spoon, Pincette, Power Code

 [MANUAL](#)

 [PRINT](#)

 [CLOSE](#)