

DUCT AIR LEAKAGE TESTER DALT 6900

Automated commercial duct air leakage testing

Kanomax introduces a new Duct Air Leakage Tester (DALT) for commercial duct systems. The instrument provides step-by-step test configuration and automated leakage testing based on the SMACNA HVAC Air Duct Leakage Test Manual. The instrument is designed for easy transport to the job with a small footprint and stair walker dolly.

DUCT LEAKAGE TESTER SPECIFICATIONS		
Duct static pressure range	+/- 10 in. w.g. (+/- 2500 Pa)	
Volumetric flow range	2 to 360 CFM (1 to 170 L/s)	
Testing surface area (at 4 in.w.g.)	Up to 10500 sq. ft.	
Temperature range	-4 to 140 °F (-20 to 60 °C)	
Weight	165 lbs. (75kg)	

^{*}Specifications are subject to change without notice..



FEATURES AND BENEFITS

- Step-by-step test configuration and automated leakage testing based on the SMACNA Test Manual.
- Automatically calculates leakage percent per AABC standards.
- Capable of both positive and negative duct leakage tests.
- Easy transport to the job with a small footprint.
- Option to connect two DALTs for bigger projects.

0000/1000		13:30
0	വെളാടാ	
U.	000202	cfm/ft2
Lim	oit 0.049246	
	Pass	
70.2 ∘⊏		4.000 inH2O
10.2 F	29.9 IIIIg	4.000 1111120
CK	START	SAVE
	70.2 °F	0.008262 Limit 0.049246 Pass 70.2 °F 29.9 inHg

KANOMAX USA, INC.

219 US HWY 206, ANDOVER, NJ 07821 USA

TEL: 973-786-6386 **FAX:** 973-786-7586

E-MAIL: SALES@KANOMAX-USA.COM URL: WWW.KANOMAX-USA.COM