

PCE Americas Inc.
711 Commerce Way
Suite 8
Jupiter
FL-33458
USA
From outside US: +1
Tel: (561) 320-9162
Fax: (561) 320-9176
info@pce-americas.com

PCE Instruments UK Ltd.
Units 12/13
Southpoint Business Park
Ensign way
Hampshire / Southampton
United Kingdom, SO31 4RF
From outside UK: +44
Tel: (0) 2380 98703 0
Fax: (0) 2380 98703 9
info@pce-instruments.com

www.pce-instruments.com/english www.pce-instruments.com

Combustible Gas-leak-detector GA 12

Environmental meter PCE-GA 12

Gas flammable gas detector / Rechargeable battery / Audible alarm / Semi-rigid 400 mm probe / Durability of the probe approx. 5 years / Vibration alarm / Measured value display up to 10000 ppm / Battery and mains operation (AC power adapter)

The environmental meter PCE-GA 12 is a very easy-to-use measuring device. This environmental meter detects combustible gases and emits a vibrating alarm as well as an audible alarm once a combustible gas has been detected by the environmental meter. Thanks to the semi-rigid hose on the gas detection device, the sensor can be aligned in almost any position to reach even inaccessible places.

This makes the gas detection device an ideal measuring device for employees who want to detect sporadically escaping gases (testing of plants during a tour of the plant, checking engines and supply lines, testing gas supply lines). A manual setting of the environmental meter is not necessary as the gas detector automatically calibrates.

- Audible alarm with 85 dB
- Rechargeable battery for mobile use
- Automatic calibration
- Measuring range up to 10000 ppm
- For the detection of combustible gases
- Durability of the sensor about 5 years
- Vibrating alarm when detecting gases
- Sensor changeable

Specifications:

Measuring range At low concentration 0 ... 1000 ppm (only for methane) At high concentration 0 ... 10000 ppm

Acoustic alarm Volume: 85 dB

Sensitivity < 10 ppm (with methane)

Measuring interval < 2 seconds

Display Measurement of combustible gases

on the LC display, bar graphs

Calibration Automatically Warming up 40 seconds

Battery Polymer Li-ion battery 18500 3.7V

Power adapter Primary side: 100 ... 240V, 50/60 Hz, 0.2 A

Secondary side: 5V, 1 A

Automatic shutdown Turns off if the battery capacity is too low

by itself or after 10 minutes if not used.

Sensor durability About 5 years (sensor is interchangeable)

Probe Semi-rigid 400 mm / 16" Weight About 430 g / < 1 lb

Delivery scope:

- 1 x Environmental meter PCE-GA 12
- 1 x Charger 1 x User manual