

TFX 430 + TPX 130 Precision Thermometer

Reference thermometer with exchangeable Pt 100 probe

TFX 430 + TPX 130 Precision Thermometer

Product Description

- High accuracy
- Four-wire measuring system
- Waterproof IP 67
- Battery life approx 5 years
- Exchangeable battery
- Different probes for different applications available

For measuring air, liquids, ductile substances, aggressive media, surfaces





| 1 Common data | |
|--------------------------|---|
| Measuring range | -100 °C+500 °C |
| Accuracy | ±0,05°C (±0,08°F) at -50,00 °C+199,99°C ±0,2°C / ±0,4°F for the rest; device w/o probe ±0,4% of the measurement for the rest; device with probe and factory calibration |
| Resolution | 0.01 °C (-100 °C+199,99 °C) 0.1 °C for the remaining measuring range |
| Operating Temperature | -20 °C+50 °C |
| Storage temperature | -30 °C+70 °C |
| Sample Rate | 1s15s |
| Cable | Pt 100 |
| Measured variables | Temperature |
| IP Rating | IP67 |
| Battery | Lithium 3 V / Typ CR 2477 |
| Battery lifetime | Approx. 5 years |
| Dimensions | 109 x 54 x 22 mm |
| Weight | Approx. 90 g |
| Certificate | Factory calibration certificate |





Accessories

AG 120

Plastic case

Part No. 1341-0619

AG 130

Aluminum case

Part No. 1341-3854

AG 140

Protective cover for thermometer, red

Part No. 1340-5005



AG 150

Wall bracket with 6 clips, plastic

Part No. 1340-5000



AX 110

Extenstion cable 1m silicone for TFX 430 - instruments (LEMO Size 1)

Part No. 1340-5020

TPX 230

TPX 230 Probe

Part No. 1341-5438



TPX 330 Probe

TPX 330

Part No. 1341-5439

Calibration

ISO-calibration

ISO-calibration

Part No. 1020-3590

