



PCE-IR 80 Infrared Thermometer



PCE-IR 80 Infrared thermometer
Food thermometer for non-contact and contact measurement / Up to 330°C (626°F) / Probe
made of stainless steel / Simple operation

The infrared thermometer PCE-IR 80 is used to quickly control the temperature of food. The infrared thermometer is used in the area of canteen kitchens, catering services, refrigerated warehouses and warehouses. The infrared thermometer has two types of measurement. On the one hand, the PCE-IR 80 infrared thermometer can measure the temperature of the object without contact via infrared. Here the measuring range is -35 ... 330°C / -31 ... 626°F. The emissivity of the infrared thermometer is adjustable, so that always best measuring results can be achieved.

On the other hand, the infrared thermometer has a stainless steel needle sensor, so that the meter can also be used as a puncture, infrared thermometer. If the core temperature is measured by this method, the infrared thermometer can measure in the range between -20 ... 260°C / -4 ... 500°F. The unit of the penetration thermometer can be switched between °C and °F. The fast response time of 10 ms and high resolution of 0.1°C / 1.8°F complete the scope of the infrared thermometer. The thermometer is supplied with a CR2032 battery.

- Non-contact and contacting temperature measurement combined in one measuring device only
- Large measuring range
- Suitable for use in the food industry according to HACCP
- Emissivity adjustable (pre-set for food)
- Low response time
- Measurement hold function (Min./Max.)
- Continuous measurement function
- Waterproof, thus simple hygienic cleaning (flushable housing)

Specifications:

Measurement type infrared

Measuring range	-35 ... 330°C / -31 ... 626°F
Resolution	0.1°C / 0.18°F
Accuracy	-35 ... 0°C / -31 ... 32°F : ± 4°C / 7.2°F > 0°C / 32°F : ± 2% v.Mw ± 2°C / 3.6°F

Type of measurement Penetration sensor

Measuring range	-20 ... 260°C / -4 ... 500°F
Resolution	0.1°C / 0.18°F
Accuracy	± 1% of v. Mw. ± 1.5°C / 2.7°F

Optical resolution	4: 1
Emissivity	Adjustable 0.1 ... 1.0
Response time	10 ms
Spectral	8 ... 14 µm
Power supply	3.0V CR2032 battery
Operating conditions	0 ... 50°C / 32 ... 122°F, max. 80% rh
Weight	About 100 g / < 1 lb
Dimensions	151 x 41 x 20 mm / 6 x 1.6 x 0.8 in

Delivery Scope

1 x PCE-IR 80 infrared thermometer

1 x User manual