



Long Hex Key Wrench


Sizes across flats : 1.5~10.0mm KL-1.5~10.0 / 9pcs. set KL-A



- Made of the highest quality alloy steel.
- Induction hardened by complete non-oxidizing decarburization correction method.
- Both sides are flat-faced bit.
- Short side bit for narrow space and offers high torque.
- Long side bit for speedy turning and bolts hard to reach.




Specifications

- Material | Alloy steel
- Heat Treatment | Fully oxide-free heat treatment
- Hardness | 53~61
- Surface treatment | Solid chrome plating



Part #	Hex size across flats (mm)	H×L (mm)	Weight [g]	Torque capacity		EAN-code (4952269)
				N · m	kgf · cm	
KL-15	1.5	14×80	5	0.82	8.36	608328
KL-20	2.0	19×96	8	1.9	19.4	608335
KL-25	2.5	18×111	10	3.8	38.7	608342
KL-30	3.0	20×127	11	6.6	67.3	608359
KL-40	4.0	25×142	20	16	163	608366
KL-50	5.0	28×160	37	30	306	608373
KL-60	6.0	32×180	55	52	530	608380
KL-80	8.0	36×198	110	120	1224	608397
KL-100	10.0	40×225	190	220	2243	608403
KL-A	9pcs. set in package					648034

*Don't use these items with torque exceeding capacity shown above.

Hex diameter across flats (mm)	Cap screw	Hex socket set screw	Hex socket button head screw	Hex socket countersunk head screw
				
1.5	M1.6 M2	M3		
2.0	M2.5	M4	M3	M3
2.5	M3	M5	M4	M4
3.0	M4	M6 W1/4	M5	M5
4.0	M5	M8 W5/16	M6	M6
5.0	M6 W1/4	M10 W3/8	M8	M8
6.0	M8 W5/16	M12 W1/2	M10	M10
8.0	M10 W3/8	M16 W5/8	M12	M12
10.0	M12 W1/2	M20 W3/4	M16	M16