



Short Hex Key Wrench

Sizes across flats : 1.5~10.0mm KS-1.5~10.0 / 9pcs. in package KS-A




- Made of the highest quality alloy steel.
- Induction hardened by complete non-oxidizing decarburization correction method.
- Both sides are flat-faced bit.
- Short side bit for narrow space and offers high torque.
- Long side bit for speedy turning and bolts hard to reach.

Specifications

- Material | Alloy steel

- Heat Treatment | Fully oxide-free heat treatment
- Hardness | 53~61
- Surface treatment | Solid chrome plating



Part #	Hex size across flats (mm)	H×L (mm)	Weight [g]	Torque capacity		EAN-code (4952269)
				N · m	kgf · cm	
KS-15	1.5	14×51	3	0.82	8.36	608427
KS-20	2.0	16×58	5	1.9	19.4	608434
KS-25	2.5	18×65	8	3.8	38.7	608441
KS-30	3.0	20×74	10	6.6	67.3	608458
KS-40	4.0	25×78	13	16	163	608465
KS-50	5.0	28×89	20	30	306	608472
KS-60	6.0	32×101	35	52	530	608489
KS-80	8.0	36×112	70	120	1224	608496
KS-100	10.0	40×128	120	220	2243	608502
KS-A	9pcs. set in package					648041

*Don't use these items with torque exceeding capacity shown above.

Correspondance between hex key and bolts				
Hex diameter across flats (mm)	Cap screw	Hex socket set screw	Hex socket button head screw	Hex socket countersunk head screw
1.5	M1.6 M2	M3		
2.0	M2.5	M4	M3	M3
2.5	M3	M5	M4	M4
3.0	M4	M6 W1/4	M5	M5
4.0	M5	M8 W5/16	M6	M6
5.0	M6 W1/4	M10 W3/8	M8	M8
6.0	M8 W5/16	M12 W1/2	M10	M10
8.0	M10 W3/8	M16 W5/8	M12	M12
10.0	M12 W1/2	M20 W3/4	M16	M16

