

-40°C Biomedical Freezer DW-40L278



Low Noise

World leading refrigeration cabin design to reduce operation noise



Seven Alarm Functions

High/low temperature, power failure, door ajar, sensor error, low battery, remote alarm, high ambient temp



Durable Refrigeration

Shelf style evaporator, fast cooling speed

Ergonomic Design



Lockable design



Intelligent alarm



Foot/Caster design



Test hole design

Specifications

DW-40L278

Technical Data

Type	-40 C Deep Freeer
Cabinet Type	Upright
Climate Class	4
Defrost Mode	Manual
Refrigerant	CFC-Free
Noise Level (dB(A))	40

Performance

Cooling performance(°C)	-40
Temperature Range(°C)	-20~-40

Control

Controller	Microprocessor
Display	LED

Electrical Data

Power Supply(V/Hz)	220-240/50
Power(W)	275
Electrical Current(A)	2.9

Dimensions

Capacity(L/Cu.Ft)	278/9.8
Net/Gross Weight(approx)	115/135(kg) 253.5/297.6(lbs)
Interior Dimensions(W*D*H)	520*435*1230(mm) 20.5*17.1*48.4(in)
Exterior Dimensions(W*D*H)	745*675*1810(mm) 29.3*26.6*71.3(in)
Packing Dimensions(W*D*H)	805*725*1970(mm) 31.7*28.5*77.6(in)
Container load (20'/40'/40'H)	14/28/28



Functions

High/Low Temperature	Y
Remote Alarm	Y
Power Failure	Y
Sensor Error	Y
Low Battery	Y
High Ambient Temp	Y
Door Ajar	Y

Accessories

Caster	Y
Foot	Y
Test Hole	Y
Drawers	6
USB Interface	Optional
Temperature Recorder	Optional

Others

Certificate	CE
-------------	----

Haier Medical and Laboratory Products Co., Ltd

Brand Building, Haier Industrial Park, No. 1
Haier Road, Qingdao, 266101, P.R.China
Tel: +86-0532-88936011 / 5955
Website: www.haiermedical.com



Note: If slight difference occurs between pictures and actual products, please refer to actual products. Our company reserves the right of final interpretation to this brochure and please contact with us for further information you might need.

