

Black Body Sources

Nagman
Black Body
Calibration Source

Table-top / Bench-top Version
For Medium Temperature Ranges

Basic Accuracy : $\pm 0.5\%$ F.S.

For Non-contact Pyrometer Calibration

Model

BBSM

- Compact, Light Weight & Portable
- High Emissivity, Wide Aperture
- Excellent Accuracy & Stability
- Auto-tune PID Controller
- Low Power Consumption
- Cost effective – Best value for Money
- RS-232 Interface & Calibration Software - Optional



SPECIFICATIONS

Model	BBSM
Range	20°C above Ambient to 600°C
Accuracy	Within 0.5% F.S. (Min. 2°C)
Emissivity	0.98
Aperture Dia	25 mm
Stability	±0.5°C
Resolution	1°C
Temperature Control	Auto-tune PID Controller
Heating time (Ambient to max.)	45 Minutes
Stabilization time (above 75°C)	20 minutes
Power Supply / Consumption	230V AC / 50 Hz / 650 W
Dimension (L x D x H)	485 x 430 x 190 mm
Weight	11 Kg.
Housing / Mounting	Bench-top (Portable)

STANDARD DELIVERY

- Basic Instrument
- Mains Cable
- Spare Fuses
- Traceable Calibration Certificate
- Instruction Manual

OPTIONAL

- RS-232 Computer Interface
- "Caltemp" Calibration Software
- Contact Thermocouple (to measure cavity temperature)
- Calibration Certificate from NABL Accredited – as per ISO/IEC 17025:2005 Laboratory
- 115V AC / 60 Hz Model

Manufactured by

Nagman Instruments & Electronics (P) Ltd.

**27th KM Stone, Chennai-Bangalore NH-4, Nazarethpet P.O., Chembarambakkam, Chennai – 600 123.
INDIA.**

Domestic Sales

Phone 044 – 26810280, 1280, 0600, 1300

Fax 044 – 26811703

E-Mail mktgchennai@nagman.com

International Sales

+91-44-26811704, 26811708

+91-44-26811703

exports@nagman.com

www.nagman.com



Specifications subject to change owing to continuous development

Nov. 2015