

## SBEV 1000-2 (600783510) Impact Drill Plastic Carry Case

Order no. 600783510 EAN 4007430313126



Product may differ from Image



- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Thumbwheel for Speed Preselection
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- Rotating carbon brush bridge for maximum performance even in anti-clockwise operation, e.g. for the removal of stubborn screws
- Metabo Marathon-motor with dust protection for long service life
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly
- Forward and reverse rotation
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Restart protection: prevents unintentional start-up after power supply interruption
- Cable-protecting ball joint for optimal freedom of motion when working

## Technical data

## Characteristics

| Rated input power                   | 1010 W                         |
|-------------------------------------|--------------------------------|
| Output power                        | 540 W                          |
| Maximum torque                      | 40 / 14 Nm // 354 / 124 in-lbs |
| Drill-Ø masonry                     | 22 mm / 7/8 "                  |
| Drill-Ø concrete                    | 20 mm / 25/32 "                |
| Drill Ø steel                       | 16 / 10 mm // 5/8 / 3/8 "      |
| Drill-Ø soft wood                   | 40 / 25 mm // 1 9/16 / 1 "     |
| No-load speed                       | 0 - 1000 / 0 - 2800 rpm        |
| Revolutions at rated load           | 1000 / 2800 rpm                |
| Maximum impact rate                 | 53200 bpm                      |
| Gears                               | 2                              |
| Chuck capacity                      | 1.5 - 13 mm // 1/16 - 1/2 "    |
| Collar diameter                     | 43 mm / 1 11/16 "              |
| Drill spindle with hexagonal recess | 6.35 mm / 1/4 "                |
| Drill spindle thread                | 1/2 " - 20 UNF                 |
| Chuck clamping type                 | Geared Chucks                  |
| Weight (without power cable)        | 2.7 kg / 6 lbs                 |
| Cable length                        | 4 m / 13 ft                    |
| Vibration                           |                                |
| Drilling in metal                   | 4.2 m/s <sup>2</sup>           |
| Uncertainty of measurement K        | 1.5 m/s <sup>2</sup>           |
| Impact drilling concrete            | 17 m/s²                        |
| Uncertainty of measurement K        | 1.5 m/s <sup>2</sup>           |
| Noise emission                      |                                |
| Sound pressure level                | 103 dB(A)                      |
| Sound power level (LwA)             | 114 dB(A)                      |
| Uncertainty of measurement K        | 3 dB(A)                        |

## Scope of delivery

Geared Chucks Drilling depth guide Plastic carry case Chuck Keys rubber-coated side handle