

KHA 18 LTX (600210650) Cordless Hammer

18V 2x5.2Ah Li-ion; Charger ASC 55 (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 600210650

EAN 4007430261571



Product may differ from Image



- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Variospeed (V) Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- LED work light for optimum view of the drilling site
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

Technical data

Characteristics

| | |
|-------------------------------------|------------------|
| Type of battery pack | Li-ion |
| Battery voltage | 18 V |
| Battery pack capacity | 2 x 5.2 Ah |
| Max. single blow energy (EPTA) | 2.2 J |
| Maximum impact rate | 4000 bpm |
| Drill-Ø concrete with hammer drills | 24 mm / 1 " |
| Drill-Ø masonry with core bits | 68 mm / 2 5/8 " |
| Drill Ø steel | 13 mm / 1/2 " |
| Drill-Ø soft wood | 25 mm / 1 " |
| No-load speed | 0 - 1100 rpm |
| Bit retainer | SDS-plus |
| Weight (including battery pack) | 2.9 kg / 6.4 lbs |

Vibration

| | |
|------------------------------|-----------------------|
| Hammer drilling concrete | 15 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Chiseling | 13.7 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 87 dB(A) |
| Sound power level (LwA) | 98 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Hammer chuck for tools with SDS-plus shank end
 Carrying strap
 2 Li-Power battery packs (18 V/5.2 Ah)
 Charger ASC 55 "AIR COOLED"
 Plastic carry case
 rubber-coated side handle
 Drilling depth guide