

KHE 56 (600340000) Combination Hammer
(220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 600340000
EAN 4007430167095



Product may differ from Image



- Combination hammer with 2 functions: hammer drilling and chiselling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Optional 30% impact reduction setting for working with more pliant materials
- Electronic soft start for precise spot-drilling
- Optimum heat dissipation and low weight thanks to die cast magnesium gear housing
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Service display, e.g. to indicate when the carbon brush needs to be replaced, and an LED indicating mains voltage
- Lockable switch for comfortable working in continuous operation

Technical data

Characteristics

Max. single blow energy (EPTA)	8.5 J
Maximum impact rate	2840 bpm
Rated input power	1300 W
Drill-Ø concrete with hammer drills	45 mm / 1 3/4 "
No-load speed	0 - 300 rpm
Bit retainer	SDS-max
Collar diameter	66 mm / 2 19/32 "
Weight (without power cable)	6.7 kg / 14.8 lbs
Cable length	6 m / 20 ft

Vibration

Hammer drilling concrete	11.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Chiseling	9.7 m/s ²
Uncertainty of measurement K	2.4 m/s ²

Noise emission

Sound pressure level	96 dB(A)
Sound power level (LwA)	107 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Metabo VibraTech (MVT) side handle
Duster
Plastic carry case
Drilling depth guide
Lubricant for tool shank end